



GRFG Mortar

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 12/27/2017

Revision date: 12/27/2017

Supersedes: 03/18/2016

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : GRFG Mortar
CAS No : Mixture
Product code : 1006
Other means of identification : Basic Speciality

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Refractory

1.3. Supplier

Resco Products, Inc.
One Robinson Plaza, Suite 300
6600 Steubenville Pike
Pittsburgh, PA 15205 - United States
412-494-4491

SDS@RescoProducts.com - WWW.RescoProducts.com

1.4. Emergency telephone number

Emergency number : EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300
Outside USA & Canada +1 703-741-5970

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2B	H320	Causes eye irritation
Carcinogenicity Category 1A	H350	May cause cancer (Inhalation)

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Danger
Hazard statements (GHS-US) : H315 - Causes skin irritation
H319 - Causes serious eye irritation
H350 - May cause cancer (Inhalation)
Precautionary statements (GHS-US) : P202 - Do not handle until all safety precautions have been read and understood.
P280 - Wear Dust respirator, eye protection, protective gloves.
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Magnesium Oxide	(CAS No) 1309-48-4	50 - 75	Not classified
chromium(III) oxide	(CAS No) 1308-38-9	10 - 20	Not classified
iron(III) oxide	(CAS No) 1309-37-1	10 - 20	Not classified
sodium silicate, alkaline 1.6/2.6, 35%<=conc<=55%, aqueous solutions	(CAS No) 1344-09-8	5 - 10	Skin Irrit. 2, H315 Eye Irrit. 2B, H320
aluminium oxide, non-fibrous	(CAS No) 1344-28-1	5 - 10	Not classified
quartz	(CAS No) 14808-60-7	1 - 5	Carc. 1A, H350

Full text of hazard classes and H-statements : see section 16

GRFG Mortar

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.
- First-aid measures after skin contact : Gently wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects (acute and delayed)

- Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.
- Symptoms/effects after inhalation : May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure through inhalation.
- Symptoms/effects after skin contact : Causes skin irritation.
- Symptoms/effects after eye contact : Causes serious eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : No unsuitable extinguishing media known.

5.2. Specific hazards arising from the chemical

- Fire hazard : Not flammable.
- Reactivity : Fire conditions may produce small amounts of hexavalent chromium and other oxidation products.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Stop release.

6.2. Environmental precautions

No additional information available

6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage.
- Methods for cleaning up : On land, sweep or shovel into suitable containers.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Avoid contact with eyes. Avoid contact with skin.
- Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store this product in a dry location where it can be protected from the elements.
- Incompatible products : Strong bases. Strong acids.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

sodium silicate, alkaline 1.6/2.6, 35%<=conc<=55%, aqueous solutions (1344-09-8)

Not applicable

Magnesium Oxide (1309-48-4)

ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³ (Magnesium oxide; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Inhalable fraction)
-------	--------------------------------	--

chromium(III) oxide (1308-38-9)

Not applicable

iron(III) oxide (1309-37-1)

ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ (Iron oxide (Fe ₂ O ₃); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)
-------	--------------------------------	---

GRFG Mortar

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

aluminium oxide, non-fibrous (1344-28-1)		
Not applicable		
quartz (14808-60-7)		
ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)
OSHA	OSHA PEL (TWA) (mg/m ³)	0.05 mg/m ³ Respirable fraction
OSHA	Remark (OSHA)	(3) See Table Z-3.

8.2. Appropriate engineering controls

No additional information available

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

After air drying or heating. Dust when sawing or tear out. Wear appropriate mask

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Granular Mixture.
Color	: Black brown
Odor	: Earthy Odor
Odor threshold	: Not applicable
pH	: No data available
Melting point	: > 2500 °F
Freezing point	: No data available
Boiling point	: Not applicable
Critical temperature	: Not applicable
Critical pressure	: Not applicable
Flash point	: Not applicable
Relative evaporation rate (butyl acetate=1)	: Not applicable
Relative evaporation rate (ether=1)	: Not applicable
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: Not applicable
Vapor pressure at 50 °C	: Not applicable
Relative vapor density at 20 °C	: No data available
Relative density	: 2.5 - 3.5
Solubility	: Moderately soluble in water.
Log Pow	: No data available
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Viscosity	: Not Applicable
Viscosity, kinematic	: Not Applicable
Viscosity, dynamic	: Not Applicable
Explosion limits	: Not applicable
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Fire conditions may produce small amounts of hexavalent chromium and other oxidation products.

GRFG Mortar

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

sodium silicate, alkaline 1.6/2.6, 35%<=conc<=55%, aqueous solutions (1344-09-8)

LD50 oral rat > 2000 mg/kg (Rat)

Magnesium Oxide (1309-48-4)

LD50 oral rat > 5000 mg/kg (Rat; Literature study)

LD50 dermal rabbit > 2000 mg/kg body weight (Rabbit; Literature study)

chromium(III) oxide (1308-38-9)

LD50 oral rat > 15000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male, Experimental value)

LC50 inhalation rat (mg/l) > 5.41 mg/l air (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male/female, Experimental value)

iron(III) oxide (1309-37-1)

LD50 oral rat > 5000 mg/kg (Rat; Literature study)

aluminium oxide, non-fibrous (1344-28-1)

LD50 oral rat > 15900 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male/female, Experimental value)

LC50 inhalation rat (mg/l) 7.6 mg/l air (Equivalent or similar to OECD 403, 1 h, Rat, Male, Experimental value)

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes eye irritation.

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : May cause cancer (Inhalation).

iron(III) oxide (1309-37-1)

IARC group 3 - Not classifiable

quartz (14808-60-7)

IARC group 1 - Carcinogenic to humans

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

Symptoms/effects after inhalation : May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure through inhalation.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

sodium silicate, alkaline 1.6/2.6, 35%<=conc<=55%, aqueous solutions (1344-09-8)

EC50 Daphnia 1 216 mg/l (EC50; 96 h)

LC50 fish 2 210 mg/l (LC50; 96 h)

Magnesium Oxide (1309-48-4)

EC50 Daphnia 1 500-665,TLM; 96 h; Mysidacea

chromium(III) oxide (1308-38-9)

LC50 fish 1 > 2.9 µg/l (ISO 7346-1, 96 h, Danio rerio, Static system, Fresh water, Experimental value)

iron(III) oxide (1309-37-1)

LC50 fish 1 > 1000 mg/l (LC50; 48 h)

GRFG Mortar

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and degradability

GRFG Mortar (Mixture)	
Persistence and degradability	Not established.
sodium silicate, alkaline 1.6/2.6, 35%≤conc≤55%, aqueous solutions (1344-09-8)	
Persistence and degradability	Biodegradability: not applicable. No (test) data on mobility of the components available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
Magnesium Oxide (1309-48-4)	
Persistence and degradability	Biodegradability: not applicable. No (test) data on mobility of the substance available.
ThOD	Not applicable (inorganic)
chromium(III) oxide (1308-38-9)	
Persistence and degradability	Biodegradability in soil: not applicable. Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable (inorganic)
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
iron(III) oxide (1309-37-1)	
Persistence and degradability	Biodegradability: not applicable. Adsorbs into the soil.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
aluminium oxide, non-fibrous (1344-28-1)	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable (inorganic)
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
quartz (14808-60-7)	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

12.3. Bioaccumulative potential

GRFG Mortar (Mixture)	
Bioaccumulative potential	Not established.
sodium silicate, alkaline 1.6/2.6, 35%≤conc≤55%, aqueous solutions (1344-09-8)	
Bioaccumulative potential	No bioaccumulation data available.
Magnesium Oxide (1309-48-4)	
Bioaccumulative potential	Bioaccumulation: not applicable.
chromium(III) oxide (1308-38-9)	
BCF fish 1	260 - 800 (Lepomis macrochirus, Fresh water, Read-across, Fresh weight)
BCF other aquatic organisms 1	116 (Crassostrea sp., Chrome)
BCF other aquatic organisms 2	86 (Mytilus edulis, Chrome)
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).
iron(III) oxide (1309-37-1)	
Bioaccumulative potential	No bioaccumulation data available.
aluminium oxide, non-fibrous (1344-28-1)	
Bioaccumulative potential	No bioaccumulation data available.
quartz (14808-60-7)	
Bioaccumulative potential	No bioaccumulation data available.

12.4. Mobility in soil

chromium(III) oxide (1308-38-9)	
Surface tension	Not applicable (solid)

GRFG Mortar

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

chromium(III) oxide (1308-38-9)	
Ecology - soil	Adsorbs into the soil.

aluminium oxide, non-fibrous (1344-28-1)	
Ecology - soil	No (test) data on mobility of the substance available.

12.5. Other adverse effects

Effect on the global warming : None known
 Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
 Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated

TDG

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

aluminium oxide, non-fibrous (1344-28-1)	
Subject to reporting requirements of United States SARA Section 313	

15.2. International regulations

CANADA

No additional information available

chromium(III) oxide (1308-38-9)	
Listed on the Canadian DSL (Domestic Substances List)	

iron(III) oxide (1309-37-1)	
Listed on the Canadian DSL (Domestic Substances List)	

EU-Regulations

No additional information available

National regulations

quartz (14808-60-7)	
Listed on IARC (International Agency for Research on Cancer)	

15.3. US State regulations

GRFG Mortar (Mixture)	
U.S. - California - Proposition 65 - Other information	This product contains crystalline silica, a chemical known to the state of California to cause cancer.

quartz (14808-60-7)					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

Magnesium Oxide (1309-48-4)	
U.S. - New Jersey - Right to Know Hazardous Substance List	

chromium(III) oxide (1308-38-9)	
U.S. - New Jersey - Right to Know Hazardous Substance List	

iron(III) oxide (1309-37-1)	
U.S. - New Jersey - Right to Know Hazardous Substance List	

aluminium oxide, non-fibrous (1344-28-1)	
U.S. - New Jersey - Right to Know Hazardous Substance List	

GRFG Mortar

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

quartz (14808-60-7)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Revision date : 12/27/2017

Other information : Report language name. English. In the event of any conflict between English and other language versions, the English version shall prevail.

Full text of H-phrases:

H315	Causes skin irritation
H320	Causes eye irritation
H350	May cause cancer

SDS US (GHS HazCom 2012)

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.