

MATERIAL SAFETY DATA SHEET

Resco Products, Inc. - WRI
6th & Center Streets
P.O. Box 28
Tarentum, PA 15804
Emergency Telephone No.: 724-224-8800

Prepared By: Research & Development
Telephone No: 336-299-1441 Ext. 20
Date: 05/26/11
Supersedes Date: 04/27/06

Section 1- Product Name

Material Name: Dolomite Toweling Consistency Mortar
Intended Use: Refractory Material
Product Name: DOL Mortar - T
Brand Code: MIX5000

Section 2- Composition And Information On Hazardous Ingredients

Ingredient	CAS No.	% Weight	OSHA PEL	ACGIH TLV	SEC 313
Calcium Oxide	1305-78-8	30-60	5 mg/m ³	2 mg/m ³	No
Magnesium Oxide	1309-48-4	15-40	15 mg/m ³ Total Particulate	10 mg/m ³ Inhalable	No
Oil	64742-58-1	10-30	5 mg/m ³ Mist	5 mg/m ³ Mist	No
Crystalline Silica (Total)	Not Applicable	0.0-1.0	Not Applicable	Not Applicable	No
Cristobalite	14464-46-1		0.05mg/m ³ Respirable	0.025mg/m ³ Respirable	
Tridymite	15468-32-3		0.05mg/m ³ Respirable	Withdrawn	
Quartz	14808-60-7		0.1 mg/m ³ Respirable	0.025 mg/m ³ Respirable	

Notes: (1) The PEL and TLV values shown above are 8-hour time-weighted averages, unless otherwise specified. "Not Established" means that no PEL or TLV has been assigned. (2) This product has a constituent that contains a mixture of calcium and magnesium oxides, it can be referred to as dead burned dolomite.

Section 3- Hazards Identification

Emergency Overview: Do not fight fire with water, keep material dry. Dust may be irritating to skin, eyes, gastrointestinal tract, and mucous membranes.

Primary Route(s) of Entry for Particulate: Note that inhalation would be after drying the product.

Eye: Yes **Skin:** Yes **Inhalation:** Yes **Ingestion:** Yes

Potential Adverse Health Effects:

Acute:	Eye: Severe irritation, intense tearing, burns.
	Skin: Removes natural skin oils; blotches, itching and superficial burns in case of sweating.
	Inhalation: Dust of this product may be irritating to respiratory tract.
	Ingestion: Sore throat, stomach aches, diarrhea, vomiting.
Chronic:	Eye: Possible blindness when exposure is prolonged.
	Skin: None known.
	Inhalation: Prolonged or repeated inhalation of dusts of this product in excess of the stated PEL or TLV may cause lung disease (Silicosis). According to the International Agency for Research on Cancer (IARC), there is sufficient evidence in humans for the carcinogenicity of inhaled crystalline silica in the form of quartz or cristobalite from occupational sources.
	Ingestion: None known.

Carcinogenicity: Crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC Group 1, NTP).

California Proposition 65: This product contains crystalline silica, a chemical known to the State of California to cause cancer.

Signs and Symptoms of Overexposure: Coughing can result from overexposure to dust.

Medical Conditions Generally Aggravated by Exposure to Particles: Pre-existing diseases or other conditions of the lungs, skin, eyes, and mucous membranes.

Section 4- First Aid Measures

Eye Contact: Flush product from eyes using large amounts of water for at least 15 minutes, if irritation continues seek medical attention.

Skin Contact: Wash product from skin using soap and water, if irritation continues, seek medical attention.

Inhalation: If exposed to excessive levels of dust remove victim to fresh air. If necessary, seek medical attention.

Ingestion: Do not induce vomiting. Seek medical attention.

Section 5- Fire Fighting Measures

Flash Point: Of oil additive >300°F.

Flammable Limits: Not Applicable

LEL: Not Applicable

UEL: Not Applicable

Autoignition Temperature: Not Applicable

Extinguishing Media: Use regular foam, carbon dioxide, or dry chemical media to fight fires.

Fire Fighting Instructions: Water or foam may cause frothing. Reacts with water to form: Ca(OH)₂, Mg(OH)₂, and heat.

Fire Fighting Equipment: Fire fighters should wear NIOSH approved, positive pressure, self-contained breathing apparatus (SCBA) and full protective clothing (bunker gear) when fighting fires.

Hazardous Combustion Products: Burning may produce carbon monoxide and other toxic fumes.

Flame Propagation or Burning Rate of Solid Material: Not Applicable

Flammability Classification (As defined by 29 CFR 1910.1200): Not Flammable

Section 6- Accidental Release Measures

Scoop or shovel material into a container, do not use water. All personnel engaged in cleanup operations should adhere to the instructions outlined in section 8 for personal protection. Disposal of wastes from cleanup operations should be carried out in accordance to the guidelines outlined in Section 13.

Section 7- Handling And Storage

Handling: Avoid direct contact with product or dust, by wearing protective clothing, using approved respiratory protection, and wearing gloves of the impermeable type.

Storage: The product should be stored in a dry location and protected from humidity. Pallet protection such as shrink-wrap or stretch-wrap should be kept in place until the product is required for installation.

Section 8- Exposure Control/Personal Protection

Engineering Controls: Process enclosures, local exhaust ventilation, or other engineering process controls may be necessary to keep any air contaminants associated with this product within their TLV's. This is particularly true if the user operation generates dust, vapors, or mist.

Respiratory Protection: The following instructions pertain to dried material such as in tear out or sawing dried or fired material. Since this product is a proprietary mixture of unique ingredients, it does not have an established limit for airborne concentration (PEL or TLV), which workers can routinely be exposed to without suffering adverse health effects. This MSDS is prepared to alert customers and other users to the various components of the product and their relative quantity and toxicity in the product as provided. The user must review his/her own circumstances and then determine what is required to establish a respiratory protection program that meets OSHA 1910.134 requirements. If workplace conditions warrant respiratory protection, use MSHA/NIOSH approved units as listed in the current 29 CFR 1910.134 for the existing conditions. Actual respirator selection should be made after consultation with a competent health and safety professional.

Eye Protection: Industrial-type safety glasses offer some protection, goggles offer more. Contact lenses should not be worn when working with lime products.

Protective Gloves: Use as needed to prevent direct skin contact.

Other Protective Clothing or Equipment: Wear clothing designed to limit direct exposure to product, or dust, vapors, or mist associated with product. If clothing becomes contaminated, it should be laundered before wearing again. Maintain good personal hygiene. Wash hands thoroughly before eating or drinking.

Section 9- Physical And Chemical Properties

Appearance: Paste, brown color	Vapor Pressure: Not Applicable
Odor: Slight petroleum	Vapor Density: Not Applicable
Water solubility: See section 10-Chemical Stability	pH: Not Applicable
Density (H₂O=1): 2.80-2.95 g/cm ³	Boiling Point: Not Applicable
Melting Point: Greater than 2,500 °F	

Section 10- Stability And Reactivity

Chemical Stability: Reacts with water to form: Ca(OH)₂, Mg(OH)₂, and heat.

Conditions to avoid: Vicinity of incompatible materials.

Incompatible Materials: Acids; reactive fluoridated brominated or phosphorous compounds; aluminum (may form hydrogen gas), reactive metals; organic acid anhydrides; nitro-organic compounds; interhalogenated compounds.

Hazardous Decomposition: None

Hazardous Polymerization: None

Reactivity: Reacts with acids to form calcium salts while generating heat.

Section 11- Toxicological Information

	LD ₅₀	LC ₅₀
Calcium Oxide	No Data	No Data
Magnesium Oxide	No Data	No Data
Oil	No Data	No Data
Crystalline Silica (Total)		
Cristobalite	No Data	No Data
Tridymite	No Data	No Data
Quartz	No Data	No Data

Target Organs	
Calcium Oxide	Eyes, skin, respiratory, and gastrointestinal tract
Magnesium Oxide	Eyes and respiratory system
Oil	Eyes, skin, and respiratory system
Crystalline Silica (Total)	
Cristobalite	Respiratory
Tridymite	Respiratory
Quartz	Respiratory
Long Term Toxicity	
Calcium Oxide	Possible blindness
Magnesium Oxide	Not Available
Oil	May cause lung damage
Crystalline Silica (Total)	
Cristobalite	Repeated and prolonged inhalations may cause lung disease (silicosis).
Tridymite	Repeated and prolonged inhalations may cause lung disease (silicosis).
Quartz	Repeated and prolonged inhalations may cause lung disease (silicosis).
Short Term Toxicity	
Calcium Oxide	Irritation of eyes, skin, respiratory, and gastrointestinal tract
Magnesium Oxide	Not Available
Oil	Irritation of eyes, skin, and respiratory system
Crystalline Silica (Total)	
Cristobalite	Repeated and prolonged inhalations may cause lung disease (silicosis).
Tridymite	Repeated and prolonged inhalations may cause lung disease (silicosis).
Quartz	Repeated and prolonged inhalations may cause lung disease (silicosis).

Section 12- Ecological Information

Accidental Release: Uncontrolled spillage in surface waters should be avoided, since the increase in pH could be detrimental to fish. Material is harmful to aquatic life in high concentrations.

Section 13- Disposal Considerations

Waste Disposal Method: The as manufactured refractory, or dust from this material, is not considered a hazardous waste as defined by 40 CFR 261. However, used product (and dust generated during maintenance and tear-out operations) may be contaminated with other hazardous substances from the particular application (for example, metals). Therefore, appropriate waste analysis may be necessary to determine proper disposal. Waste characterization and disposal/treatment methods should be determined by a qualified environmental professional in accordance with applicable federal, state, and local regulations.

Section 14-Transport Information

DOT (Department of Transportation) Classification under 49 CFR 172.101: Not Regulated

UN (United Nations) Number: Not Applicable

NA (North American) Number: Not Applicable

Section 15- Regulatory Information

Resco Products, Inc. considers this product to be hazardous as defined by the OSHA Hazardous Communications Standard (29 CFR 1910.1200). Section 2 chemicals, which must be addressed, and the summary of regulatory and other lists upon which they appear are:

INGREDIENT	CAS NUMER	LIST
Calcium Oxide	1305-78-8	1,2,3,4
Magnesium Oxide	1309-48-4	1,2,3,4
Oil	64742-58-1	1,2,3,4
Crystalline Silica	Not Applicable	
Cristobalite	14464-46-1	1,2,3,4
Tridymite	15468-32-3	1,2,3,4
Quartz	14808-60-7	1,2,3,4

The lists are as follows:

1. ACGIH TLV "Threshold Limit Values" (2010)
2. OSHA Air Contaminates- Permissible Exposure Limits
3. Canadian Domestic Substance List
4. EPA TSCA Chemical Inventory List

SARA Title III: Section 311/312 Hazardous Categories: Irritant

Section 16- Other Information

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein; however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.