

## MATERIAL SAFETY DATA SHEET

Resco Products, Inc.  
Penn Center West  
Building 2, Suite 430  
Pittsburgh, PA 15276  
Emergency Telephone No. : 412-494-4491

Prepared By: Research & Development  
Telephone No: 336-299-1441 Ext. 20  
Date: 1/21/10  
Supersedes Date: 07/05/06

### Section 1 – Product Name

**Common Name:** Refractory Plastic  
**Intended Use:** Refractory Material  
**Product Name:** Rescoram 10 CR  
**Brand Code:** MIX0553

### Section 2 – Composition and Information on Hazardous Ingredients

| <u>Ingredient</u>          | <u>CAS No.</u> | <u>% Weight</u> | <u>OSHA PEL</u>  | <u>ACGIH TLV</u>   | <u>Sec. 313</u> |
|----------------------------|----------------|-----------------|--|--|-----------------|
| Alumina                    | 1344-28-1      | 60-100          | 15 mg/ m <sup>3</sup> Total Dust<br>5 mg/m <sup>3</sup> Respirable | Withdrawn<br>Al Metal & Insoluble<br>Compounds 1 mg/m <sup>3</sup><br>Respirable | No              |
| Crystalline Silica (Total) | Not Applicable | 0.5-1.5         | Not Applicable   | Not Applicable   | No              |
| Cristobalite               | 14464-46-1     |                 | 0.05mg/m <sup>3</sup> Respirable                                   | 0.025 mg/m <sup>3</sup> Respirable   |                 |
| Tridymite                  | 15468-32-3     |                 | 0.05mg/m <sup>3</sup> Respirable                                   | Withdrawn  |                 |
| Quartz                     | 14808-60-7     |                 | 0.1 mg/m <sup>3</sup> Respirable                                   | 0.025 mg/m <sup>3</sup> Respirable   |                 |
| Phosphoric Acid            | 7664-38-2      | 3-7             | 1 mg/m <sup>3</sup>  | 1 mg/m <sup>3</sup>  | No              |
| Chromium (III) Oxide       | 1308-38-9      | 7-13            | 0.5 mg/m <sup>3</sup> as Cr  | 0.5 mg/m <sup>3</sup>  | Yes             |

Notes: (1) The PEL and TLV values shown above are 8-hour time-weighted averages, unless otherwise specified. "Not Established" means that no PEL or TLV has been assigned.

### Section 3 – Hazards Identification

**Emergency Overview:** No unusual fire or spill hazard. Dusts may be irritating to skin, eyes and mucous membranes.

**Primary Route(s) of Entry for Particulate:** **Eye:** Yes **Skin:** Yes **Inhalation:** Yes **Ingestion:** No

**Potential Adverse Health Effects:**

|                |   |
|----------------|---|
| <b>Acute</b>   | Eye: Dusts of this product may be irritating.   |
|                | Skin: This product may be irritating to the skin.   |
|                | Inhalation: Dusts of this product may be irritating to respiratory tract.   |
| <b>Chronic</b> | Eye: None known   |
|                | Skin: This product may be irritating to the skin.   |
|                | Inhalation: Prolonged breathing of dust of this product in excess of the stated PEL or TLV may cause lung disease (Silicosis). According to the International Agency for Research on Cancer (IARC), there is sufficient evidence in humans for the carcinogenicity of inhaled crystalline silica in the form of quartz or cristobalite from occupational sources. |

**Carcinogenicity:** Crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC Group 1, NTP).

**California Proposition 65:** This product contains crystalline silica, a chemical known to the State of California to cause cancer. This product contains Chromite (Cr<sup>+</sup>+3) which may in normal use, be converted chemically to a chromate (Cr<sup>+</sup>+6) hexavalent chrome, a chemical known to the State of California to cause cancer.

**Signs and Symptoms of Overexposure:** Coughing can result from overexposure to dust.

**Medical Conditions Generally Aggravated by Exposure to Particles:** Pre-existing disease or other conditions of the lungs, skin, eyes and mucous membranes.

### Section 4- First Aid Measures

**Eye Contact:** Flush product from eyes using large amounts of water. If irritation continues, seek medical attention.

**Skin Contact:** Wash product from skin using soap and water. If irritation continues, seek medical attention.

**Inhalation:** If exposed to excessive levels of dusts or vapors during heating, remove victim to fresh air. Seek medical attention if coughing or other symptoms persist.

**Ingestion:** As shipped, product not likely to be ingested; but if it occurs, do not induce vomiting. Seek medical attention.

### Section 5 – Fire Fighting Measure

**Flash Point:** Not Applicable

**Flammable Limits:** Not Applicable

**LEL:** Not Applicable

**UEL:** Not Applicable

**Product Name: Rescoram 10 CR**

**Date: 09/21/10**

**Autoignition Temperature:** Not Applicable

**Extinguishing Media:** As appropriate for surrounding fire.

**Fire Fighting Instructions:** As appropriate for surrounding fire.

**Fire Fighting Equipment:** Fire fighters should wear NIOSH approved, positive pressure, self-contained breathing apparatus (SCBA) and full protective clothing (bunker gear) when fighting fires.

**Hazardous Combustion Products:** Fire conditions may produce small amounts of hexavalent chromium and other oxidation products.

**Flame Propagation or Burning Rate of Solid Material:** Not Applicable

**Flammability Classification (As defined by 29 CFR 1910.1200):** Not Flammable

#### **Section 6 – Accidental Release Measures**

If dusts are generated during the spill, these should be collected by gently sweeping the material into a dustpan or collecting with a vacuum device. All personnel engaged in cleanup operations should adhere to the instructions outlined in Section 8 for personal protection. Disposal of wastes from cleanup operations should be carried out in accordance with the guidelines outlined in Section 13.

#### **Section 7 – Handling and Storage**

**Handling:** Avoid direct contact with product or dusts from product by wearing protective clothing, using approved respiratory protection and wearing gloves of the impermeable type.

**Storage:** The product should be stored in a dry location and away from sources of heat (furnaces, boilers, incinerators, etc.). Pallet protection such as shrink-wrap or stretch-wrap should be kept in place until the product is required for installation.

#### **Section 8 – Exposure Control/Personal Protection**

**Engineering Controls:** Process enclosures, local exhaust ventilation, or other engineering process controls may be necessary to keep any air contaminants associated with this product within their TLV's. This is particularly true if user operation generates dust.

**Respiratory Protection:** Since this product is a proprietary mixture of unique ingredients, it does not have an established limit for airborne concentration (PEL or TLV), which workers can routinely be exposed to without suffering adverse health effects. This MSDS is prepared to alert customers and other users to the various components of the product and their relative quantity and toxicity in the product as it is provided. The user must review his/her own circumstances and then determine what is required to establish a respiratory protection program that meets OSHA 1910.134 requirements. If workplace conditions warrant respiratory protection, use MSHA/NIOSH approved units as listed in the current 29 DFR 1910.134 for the existing conditions. Some type of respiratory protection is recommended for even the best conditions. Actual respirator selection should be made after consultation with a competent health and safety professional.

**Eye Protection:** Industrial type safety glasses offer some protection, goggles offer more.

**Protective Gloves:** As needed to prevent direct skin contact.

**Other Protective Clothing or Equipment:** Wear clothing designed to limit direct exposure to product or dusts associated with product. If clothing becomes contaminated, it should be laundered before wearing again. Maintain good personal hygiene. Wash hands thoroughly before eating or drinking.

#### **Section 9 – Physical and Chemical Properties**

**Appearance:** Stiff Plastic Mass, Green Color

**Vapor Pressure (mm Hg):** Not Applicable

**Odor:** Earthy Odor

**Vapor Density (Air=1):** Not Applicable

**Water Solubility:** Slight

**pH (10% solids):** 1.5-2.5

**Density (H<sub>2</sub>O=1):** 2.7

**Boiling Point (°C):** Not Applicable

**% Volatile (By Weight):** 0

**Melting Point:** Greater than 2,000°F

#### **Section 10 – Stability and Reactivity**

**Chemical Stability:** This product is stable under normal conditions for shipping, storage and installation.

**Conditions to Avoid:** None

**Incompatible Material:** Fine active metals. Chromic oxide may react with alkali at high temperatures under oxidizing conditions.

**Hazardous Decomposition:** None

**Hazardous Polymerization:** Not Applicable

**Reactivity:** Chemically Setting

#### **Section 11 – Toxicological Information**

|                    | <b>LD<sub>50</sub></b> | <b>LC<sub>50</sub></b> |
|--------------------|------------------------|------------------------|
| Alumina            | No Data                | No Data                |
| Crystalline Silica |                        |                        |
| Cristobalite       | No Data                | No Data                |
| Tridymite          | No Data                | No Data                |
| Quartz             | No Data                | No Data                |

|                            |   |         |
|----------------------------|---|---------|
| Phosphoric Acid            | No Data   | No Data |
| Chromium (III) Oxide       | No Data   | No Data |
| <b>Target Organs</b>       |   |         |
| Alumina                    | Respiratory   |         |
| Crystalline Silica         |   |         |
| Cristobalite               | Respiratory   |         |
| Tridymite                  | Respiratory   |         |
| Quartz                     | Respiratory   |         |
| Phosphoric Acid            | Skin & Respiratory  |         |
| Chromium (III) Oxide       | Eyes, skin and mucous membranes.                                      |         |
| <b>Long Term Toxicity</b>  |   |         |
| Alumina                    | No Data   |         |
| Crystalline Silica         |   |         |
| Cristobalite               | Repeated and prolonged inhalations may cause lung disease (Silicosis) |         |
| Tridymite                  | Repeated and prolonged inhalations may cause lung disease (Silicosis) |         |
| Quartz                     | Repeated and prolonged inhalations may cause lung disease (Silicosis) |         |
| Phosphoric Acid            | Irritation to Skin and Respiratory organs                             |         |
| Chromium (III) Oxide       | Not classifiable as a carcinogen (ACGIH).                             |         |
| <b>Short Term Toxicity</b> |   |         |
| Alumina                    | No Data   |         |
| Crystalline Silica         |   |         |
| Cristobalite               | Repeated and prolonged inhalations may cause lung disease (Silicosis) |         |
| Tridymite                  | Repeated and prolonged inhalations may cause lung disease (Silicosis) |         |
| Quartz                     | Repeated and prolonged inhalations may cause lung disease (Silicosis) |         |
| Phosphoric Acid            | Irritation to Skin and Respiratory organs                             |         |
| Chromium (III) Oxide       | Irritant to skin, eyes and mucous membranes                           |         |

**Section 12 – Ecotoxicological Information**

**Accidental Release:** No information has been developed regarding the ecotoxicity or environmental fate of this product.

**Section 13 – Disposal Considerations**

**Waste Disposal Method:** The as manufactured refractory, or dust from this material, is not considered a hazardous waste as defined by 40 CFR 261. However, used product (and dusts generated during maintenance and tear-out operations) may be contaminated with other hazardous substances from the particular application (for example, metals). Chromite (Cr<sup>+3</sup>) may in normal use, be converted chemically to a chromate (Cr<sup>+6</sup>). Hexavalent chromium (Cr<sup>+6</sup>) is considered a hazardous material. Wastes from this product may or may not be classified as a hazardous waste. Therefore, appropriate waste analysis may be necessary to determine proper disposal. Waste characterization and disposal / treatment methods should be determined by a qualified environmental professional in accordance with applicable federal, state, and local regulations

**Section 14 – Transport Information**

**DOT (Department of Transportation) Classification under 49 CFR 172.101:** Not Regulated

**UN (United Nations) Number:** Not Applicable

**NA (North American) Number:** Not Applicable

**Section 15 – Regulatory Information**

Resco Products, Inc. considers this product to be hazardous as defined by the OSHA Hazardous Communications Standard (29 CFR 1910.1200). Section 2 chemicals, which must be addressed, and the summary of regulatory and other lists upon which they appear are:

| Ingredient           | CAS Number | List (s)   |
|----------------------|------------|------------|
| Alumina              | 1344-28-1  | 1,2,3,4    |
| Crystalline Silica   |            |            |
| Cristobalite         | 14464-46-1 | 1,2,3,4    |
| Tridymite            | 15468-32-3 | 1,2,3,4    |
| Quartz               | 14808-60-7 | 1,2,3,4    |
| Phosphoric Acid      | 7664-38-2  | 1,2,3,4    |
| Chromium (III) Oxide | 1308-38-9  | 1, 2, 3, 4 |

The lists are as follows:

1. ACGIH TLV "Threshold Limit Values"
2. OSHA Air Contaminants – Permissible Exposure Limits (2008)
3. Canadian Domestic Substances List
4. EPA TSCA Chemical Inventory List

**WHMIS Hazard Class (Canada):** D2A

**Product Name: Rescoram 10 CR**

**Date: 09/21/10**

**SARA Title III:**

Section 313 Toxic Chemicals: See section 2

***Section 16 – Other Information***

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein; however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.