



Technical Data

PERMAGUN™ S-II (Formerly BG-9378) HIGH MgO GUNNING MIX

FEATURES	A high MgO gunning mix designed for minimum rebound and maximum corrosion and erosion resistance. Specifically recommended for hot or cold maintenance of basic linings where space is restricted, such as degasser snorkels.										
CHEMICAL ANALYSIS (Ignited)	<table border="0"> <tr> <td>MgO (by Diff.)</td> <td>92.1%</td> </tr> <tr> <td>SiO₂</td> <td>4.0</td> </tr> <tr> <td>CaO</td> <td>1.8</td> </tr> <tr> <td>Al₂O₃</td> <td>1.2</td> </tr> <tr> <td>Fe₂O₃</td> <td>0.9</td> </tr> </table>	MgO (by Diff.)	92.1%	SiO ₂	4.0	CaO	1.8	Al ₂ O ₃	1.2	Fe ₂ O ₃	0.9
MgO (by Diff.)	92.1%										
SiO ₂	4.0										
CaO	1.8										
Al ₂ O ₃	1.2										
Fe ₂ O ₃	0.9										
PACKAGING	Standard 55 pound (25 kg) moisture-proof bags - Also available in 2000 and 4000 pound bulk containers										

The properties shown on this data sheet represent typical average results generated using standard ASTM test methods (unless otherwise noted) conducted under controlled condition (using standard rectangular shapes), and should not be considered to be guaranteed specifications. Properties are subject to normal manufacturing statistical standard deviation ranges, and Resco Products, Inc. reserves the right to modify the properties and specifications at any time without prior notice.

RESCO PRODUCTS disclaims any express or implied warranties based on this sheet.

02/05/08 is the date that this data sheet was updated. Check with your RESCO sales representative or RESCO website to determine you have the current sheet