



Mortars

Product Data

RESCOSET N-60

RESCOSET N-60 is a dry air setting magnesia-chrome mortar. This mortar is designed to lay up basic brick. The mortar is in the 60% magnesia class. Suggested uses are to lay up all varieties of basic brick used for working and safety linings in both steel and non-ferrous applications.

Classification: Dry Basic Refractory Mortar

Screen Sizing: +28 Mesh less than 3%

Chemical Analysis (%):
(Calcined Basis)

Silica	SiO ₂	1.8
Alumina	Al ₂ O ₃	7.8
Titania	TiO ₂	0.3
Iron Oxide	Fe ₂ O ₃	10.3
Lime	CaO	0.6
Magnesia	MgO	60.3
Chromic Oxide	Cr ₂ O ₃	18.9

The properties shown on this data sheet represent typical average results generated using standard ASTM test methods (unless otherwise noted) conducted under controlled condition (using standard rectangular shapes), and should not be considered to be guaranteed specifications. Properties are subject to normal manufacturing statistical standard deviation ranges, and Resco Products, Inc. reserves the right to modify the properties and specifications at any time without prior notice.

RESCO PRODUCTS disclaims any express or implied warranties based on this sheet.

02/05/08 is the date that this data sheet was updated. Check with your RESCO sales representative or RESCO website to determine you have the current sheet