



PRODUCT DATA

Brand Name: RESCOCOAT G

Description: RESCOCOAT G is an air setting, silica-based refractory coating containing a carbon addition. The carbon addition improves non-sticking or non-wetting properties of the coating. RESCOCOAT G is shipped in a wet, ready-to-use consistency.

Physical properties shown are average values of samples taken under controlled conditions
ASTM test methods used where applicable

Maximum Service Temperature : 2500°F (1371°C)

Material Weight Required per Cubic Foot : 2.13 lbs. (approximate)

Typical Chemical Analysis (%)
(Dry Basis)

Alumina (Al ₂ O ₃)	16.9
Silica (SiO ₂)	63.4
Iron Oxide (Fe ₂ O ₃)	2.3
Titania (TiO ₂)	0.9
Lime (CaO)	0.2
Alkalis (Na ₂ O+K ₂ O)	4.2
Carbon	12.1

Standard Packaging: 50 lb. (22.7 kg.) plastic pail

Brand Code: 7574

The properties shown on this data sheet represent typical average results using standard ASTM test methods (unless otherwise noted) conducted under controlled condition (using standard rectangular shapes), and should not be considered to be guaranteed specifications. Properties are subject to normal manufacturing statistical standard deviation ranges, and Resco Products, Inc. reserves the right to modify the properties and specifications at any time without prior notice.

RESCO PRODUCTS disclaims any express or implied warranties based on this sheet.

04/17/19 is the date that this data sheet was updated. Check with your RESCO sales representative or RESCO website to determine you have the current sheet.

One Robinson Plaza - Suite 300, 6600 Steubenville Pike, Pittsburgh, PA, 15205 Phone: 888-283-5505