

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 3/15/2015 Revision date: 7/12/2024 Supersedes: 6/15/2021

SECTION 1: Identification				
1.1. Identification				
Product form	: Mixture			
Product name	: Alutab			
CAS-No. Product code	: Mixture : 0768			
Other means of identification	: Alumina-Silicate Sp	eciality		
I.2. Recommended use and restrictions o				
Jse of the substance/mixture	: Refractory			
Recommended use	: Industrial use			
1.3. Supplier Resco Products, Inc.				
One Robinson Plaza. Suite 300				
6600 Steubenville Pike				
Pittsburgh, PA, 15205				
Jnited States F 412-494-4491				
SDS@RescoProducts.com - WWW.RescoProduct	<u>s.com</u>			
1.4. Emergency telephone number				
Emergency number		Y (CHEMTREC) USA & ada +1 703-741-5970	Canada 1-800	-424-9300
SECTION 2: Hazard(s) identification	Outside USA & Can	ada +1705-741-5970		
2.1. Classification of the substance or mi	cture			
GHS US classification				
Skin corrosion/irritation Category 2	H31			
Serious eye damage/eye irritation Category 2B	H32	5		ian)
Carcinogenicity Category 1A Full text of H statements : see section 16	H35	0 May cause (cancer (Inhalat	lion)
2.2. GHS Label elements, including preca	utionary statements			
GHS US labeling				
Hazard pictograms (GHS US)	: 🔨			
Signal word (GHS US)	: Danger	•		
Hazard statements (GHS US)	: H315 - Causes skin	irritation		
	H320 - Causes eye			
Propositionany atotements (CLIC LIC)	H350 - May cause o	ancer (Inhalation) ptection, Dust respirator,	protoctivo alo	
Precautionary statements (GHS US)				ter for several minutes. Remove
		esent and easy to do. Co		
		irritation occurs: Get me		
	P337+P313 - If eye P260 - Do not breat	irritation persists: Get m	edical advice/a	attention.
2.3. Other hazards which do not result in				
No additional information available				
2.4. Unknown acute toxicity (GHS US)				
No additional information available				
SECTION 3: Composition/Information	on ingredients			
3.1. Substances				
Not applicable				
3.2. Mixtures				
Name		Product identifier	%	GHS US classification
aluminium oxide, non-fibrous		CAS-No.: 1344-28-1	75 – 95	Not classified
Sodium Silicate Dry		CAS-No.: 1344-09-8 CAS-No.: 14808-60-7	5 – 10	Not classified
quartz		1. NG NA + 1/000 60 7	1-5	Carc. 1A, H350

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First-aid measures	
4.1. Description of first aid measures	
First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact First-aid measures after eye contact	 IF ON SKIN: Gently wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present
	and easy to do. Continue rinsing.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.
4.2. Most important symptoms and effects (
Potential Adverse human health effects and symptoms	: Harmful: danger of serious damage to health by prolonged exposure through inhalation.
Symptoms/effects after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. May cause cancer by inhalation.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes eye irritation.
4.3. Immediate medical attention and special No additional information available	al treatment, if necessary
SECTION 5: Fire-fighting measures	
5.1. Suitable (and unsuitable) extinguishing	
Suitable extinguishing media Unsuitable extinguishing media	 Use extinguishing media appropriate for surrounding fire. In case of fire, all extinguishing media allowed.
5.2. Specific hazards arising from the chem	
Fire hazard	: Not flammable.
5.3. Special protective equipment and preca	
Firefighting instructions Protection during firefighting	 Fight fire with normal precautions from a reasonable distance. Do not enter fire area without proper protective equipment, including respiratory protection.
SECTION 6: Accidental release measur	
6.1. Personal precautions, protective equips 6.1.1. For non-emergency personnel	ment and emergency procedures
Emergency procedures	: Do not breathe dust. Avoid contact with skin and eyes.
6.1.2. For emergency responders Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area. On land, sweep or shovel into suitable containers.
6.2. Environmental precautions	
Prevent entry to sewers and public waters.	
6.3. Methods and material for containment a	and cleaning up
Methods for cleaning up	: On land, sweep or shovel into suitable containers. Minimize generation of dust.
6.4. Reference to other sections	
See Heading 8. Exposure controls and personal prot	ection
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Avoid raising dust. Avoid contact with skin and eyes. Do not breathe dust.
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work thoroughly after handling.
7.2. Conditions for safe storage, including a	
Storage conditions	: Store this product in a dry location where it can be protected from the elements.
SECTION 8: Exposure controls/persona	al protection
8.1. Control parameters	
Alutab (Mixture)	
No additional information available aluminium oxide, non-fibrous (1344-28-1)	
USA - ACGIH - Occupational Exposure Limits	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

quartz (14808-60-7)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	0.025 mg/m ³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)
USA - OSHA - Occupational Exposure Limits	
Local name	Silica, crystalline quartz, respirable dust
OSHA PEL (TWA) [1]	0.05 mg/m ³ respirable dust
Remark (OSHA)	(3) See Table Z-3.
Sodium Silicate Dry (1344-09-8)	
No additional information available	
8.2. Appropriate engineering controls	
Appropriate engineering controls	: Ensure that there is a suitable ventilation system. Emergency eye wash fountain with clean water.
8.3. Individual protection measures/Person	al protective equipment
Personal protective equipment: Avoid all unnecessary exposure.	
Hand protection:	
Wear protective gloves.	
Eye protection:	
Chemical goggles or safety glasses	
Skin and body protection:	
Wear suitable protective clothing	
Respiratory protection:	
Wear appropriate mask	
Do not eat, drink or smoke during use. SECTION 9: Physical and chemical pro	
9.1. Information on basic physical and che	
Physical state	: Solid : Granular mixture.
Appearance Color	: Off-white
Odor	: earthy
Odor threshold	: No data available
pH	: >10
pH solution concentration	
	: 10 %
Melting point Freezing point	: 10 %
Melting point	: 10 % : > 1100 °C : No data available : No data available
Melting point Freezing point Boiling point Flash point	 10 % > 1100 °C No data available No data available No data available No data available
Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1)	 10 % > 1100 °C No data available
Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas)	 10 % > 1100 °C No data available
Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure	 10 % > 1100 °C No data available
Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C	 10 % > 1100 °C No data available
Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C Relative density	 10 % > 1100 °C No data available 2 - 3
Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C	 10 % > 1100 °C No data available
Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature	 10 % > 1100 °C No data available
Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature	: 10% : > $1100 °C$: No data available : $2 - 3$: Moderately soluble in water. : No data available : No data available
Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Viscosity, kinematic	 10 % > 1100 °C No data available 2 - 3 Moderately soluble in water. No data available No tata available Not Applicable
Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Viscosity, kinematic Viscosity, dynamic	 10 % > 1100 °C No data available 2 - 3 Moderately soluble in water. No data available
Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Viscosity, kinematic Viscosity, dynamic Explosion limits	 10 % > 1100 °C No data available 2 - 3 Moderately soluble in water. No data available
Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Viscosity, kinematic Viscosity, dynamic Explosion limits Explosive properties	 10 % > 1100 °C No data available 2 - 3 Moderately soluble in water. No data available
Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Viscosity, kinematic Viscosity, kinematic Viscosity, dynamic Explosion limits Explosive properties Oxidizing properties	 10 % > 1100 °C No data available 2 - 3 Moderately soluble in water. No data available
Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Viscosity, kinematic Viscosity, kinematic Viscosity, dynamic Explosive properties Oxidizing properties 9.2. Other information	 10 % > 1100 °C No data available 2 - 3 Moderately soluble in water. No data available
Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Viscosity, kinematic Viscosity, kinematic Viscosity, dynamic Explosion limits Explosive properties Oxidizing properties	 10 % > 1100 °C No data available 2 - 3 Moderately soluble in water. No data available
Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Viscosity, kinematic Viscosity, kinematic Viscosity, dynamic Explosion limits Explosive properties Oxidizing properties 9.2. Other information No additional information available	 10 % > 1100 °C No data available 2 - 3 Moderately soluble in water. No data available

Air Setting.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.2. Chemical stability	
Stable under normal conditions of use.	
10.3. Possibility of hazardous reactions	
Not established.	
10.4. Conditions to avoid	
Avoid dust formation.	
10.5. Incompatible materials	
No additional information available	
10.6. Hazardous decomposition products	
No additional information available	
SECTION 11: Toxicological information	
11.1. Information on toxicological effects	
Acute toxicity (oral)	: Not classified
Acute toxicity (dermal) Acute toxicity (inhalation)	: Not classified : Not classified
aluminium oxide, non-fibrous (1344-28-1)	
	A 15000 mallas badu waisht (Esuivalant as aimiles to OEOD 404. Dat Mala (famile
LD50 oral rat	> 15900 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LC50 Inhalation - Rat	> 2.3 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))
Sodium Silicate Dry (1344-09-8)	
LD50 oral rat	> 2000 mg/kg (Rat, Oral)
Skin corrosion/irritation	: Causes skin irritation. pH: > 10
aluminium oxide, non-fibrous (1344-28-1)	
рН	9 – 10.5 (aqueous suspension, 33 %)
quartz (14808-60-7)	
рН	6 - 7
Sodium Silicate Dry (1344-09-8)	
рН	11 – 13
Serious eye damage/irritation	: Causes eye irritation. pH: > 10
aluminium oxide, non-fibrous (1344-28-1)	
рН	9 – 10.5 (aqueous suspension, 33 %)
quartz (14808-60-7)	
рН	6 - 7
Sodium Silicate Dry (1344-09-8)	
рН	11 – 13
	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer (Inhalation).
quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard Viscosity, kinematic	: Not classified : Not Applicable
viocosty, monato	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

aluminium oxide, non-fibrous (1344-28-1)	
Viscosity, kinematic	Not applicable (solid)
-	Inhalation.
	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
symptoms	
Symptoms/effects after inhalation :	Danger of serious damage to health by prolonged exposure through inhalation. May cause
	cancer by inhalation.
Symptoms/effects after skin contact :	Causes skin irritation.
	Causes eye irritation.
SECTION 12: Ecological information	
12.1. Toxicity	
aluminium oxide, non-fibrous (1344-28-1)	
LC50 - Fish [1]	> 100 mg/l (96 h, Salmo trutta, Literature study)
EC50 - Crustacea [1]	> 100 mg/l (48 h, Daphnia magna, Literature study)
Sodium Silicate Dry (1344-09-8)	
LC50 - Fish [1]	210 mg/l (96 h, Brachydanio rerio, Pure substance)
EC50 - Crustacea [1]	216 mg/l (96 h, Daphnia magna, Pure substance)
12.2. Persistence and degradability	
Alutab (Mixture)	
Persistence and degradability	Not established.
aluminium oxide, non-fibrous (1344-28-1)	
Persistence and degradability	Not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
quartz (14808-60-7)	
Persistence and degradability	Not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
Sodium Silicate Dry (1344-09-8)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
12.3. Bioaccumulative potential	
Alutab (Mixture)	
Bioaccumulative potential	Not established.
aluminium oxide, non-fibrous (1344-28-1)	
Bioaccumulative potential	No data available.
quartz (14808-60-7)	
Bioaccumulative potential	No data available.
Sodium Silicate Dry (1344-09-8)	
Bioaccumulative potential	No bioaccumulation data available.
12.4. Mobility in soil	
aluminium oxide, non-fibrous (1344-28-1)	No data available in the literature
Surface tension Ecology - soil	No data available in the literature No data available.
Sodium Silicate Dry (1344-09-8)	No (test) data an mahility of the component(a) subjects
Ecology - soil	No (test) data on mobility of the component(s) available.
12.5. Other adverse effects	Nene Incur
5 5	None known No other effects known.
SECTION 13: Disposal considerations	
13.1. Disposal methods	
	Dispose in a safe manner in accordance with local/national regulations.
SECTION 14: Transport information	
In accordance with DOT / TDG / IMDG / IATA	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

		120, 2012 / Rules and Rege				
Department of Transpo	ortation (DOT)					
In accordance with DOT						
Not regulated						
Transportation of Dang	gerous Goods					
Not regulated						
Transport by sea						
Not regulated						
Air transport Not regulated						
SECTION 15: Regu	latory information					
15.1. US Federal regu						
All components of this pr	oduct are present and listed a	as Active on the United S	tates Environmental Pro	tection Agency Toxic	Substances Control Act	
(TSCA) inventory						
aluminium oxide, no						
· · ·	equirements of the United Sta					
Note	Aluminum	section 313 chemical list o oxide contained in this pro- ring, processing, or other	oduct is non-fibrous, and	thus is not a section	313 material. Only	
15.2. International reg		3, p. 2 2 2 2 2 3				
CANADA						
aluminium oxide, no						
Listed on the Canadian	DSL (Domestic Substances Li	st)				
Sodium Silicate Dry	(1344-09-8)					
	OSL (Domestic Substances Li	st)				
EU-Regulations						
No additional information National regulations	available					
quartz (14808-60-7)						
Listed on IARC (Internati	onal Agency for Research on	Cancer)				
15.3. US State regula	tions					
Alutab (Mixture)						
U.S California - Propos	sition 65 - Other information		crystalline silica, a chemi mation go to WWW.P65		of California to cause	
				vannings.oa.gov		
quartz (14808-60-7)						
U.S California -	U.S California -	U.S California -	U.S California -	No significant risk	Maximum allowable	
Proposition 65 - Carcinogens List	Proposition 65 - Developmental Toxicity	Proposition 65 - Reproductive Toxicity - Female	Proposition 65 - Reproductive Toxicity - Male	level (NSRL)	dose level (MADL)	
Yes	No	No	No			
Component		State or local regul	lations			
aluminium oxide, non-fib	rous (1344-28-1)	State or local regulations U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List U.S Dependencie - DTK (Pictute Know List)				
Quartz (14808-60-7)		Substance List; U.S Pennsylvania - RTK (Right to Know) List U.S New Jersey - Right to Know Hazardous Substance List				
SECTION 16: Other	r information					
according to Federal Reg	ister / Vol. 77, No. 58 / Monda	av. March 26. 2012 / Rule	s and Regulations			
Revision date		7/12/2024				
Other information	:			any conflict between I	English and other language	
Full text of H-phrases		versions, the English ve	ersion shall prevail.			
	ses skin irritation					
	Causes eye irritation					
	cause cancer					
Safety Data Sheet (SDS),	USA					
	mmendations set forth herein	are taken from sources b	pelieved to be accurate a	as of the date herein, h	nowever, Resco Products,	

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.