



Dibond 60 L

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)
Issue date: 5/1/2015 Revision date: 8/26/2025 Supersedes: 9/12/2022

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Product name : Dibond 60 L
CAS-No. : Mixture
Product code : 5240 = Mix3812

1.2. Other means of identification

Other means of identification : Magnesita-Chrome Brick

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Refractory Brick
Recommended use : Industrial use

1.4. Supplier's details

RHI Magnesita
One Robinson Plaza, Suite 300
6600 Steubenville Pike
Pittsburgh, PA, 15205
United States
T 412-494-4491

Resco_SDS.TDS@rhimagnesita.com - WWW.RescoProducts.com

1.5. Emergency phone number

Emergency number : EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300
Outside USA & Canada +1 703-741-5970

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation, Category 2 H315 Causes skin irritation.
Specific target organ toxicity – Single exposure, Category 3, H335 May cause respiratory irritation from dust in sawing or tear out operations.
Respiratory tract irritation
Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning
Hazard statements (GHS US) : H335 - May cause respiratory irritation from dust in sawing or tear out operations.
H315 - Causes skin irritation
Dust from sawing or tear out may irritate eye.
Precautionary statements (GHS US) : P280 - Wear Safety shoes, protective gloves, eye protection.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

Other hazards which do not result in classification : Dust from sawing or tear out may irritate eye.

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Magnesium Oxide	CAS-No.: 1309-48-4	30 – 60	Not classified
Transvaal Chrome Ore	CAS-No.: 1308-31-2	30 – 60	Not classified

Full text of hazard classes and H-statements : see section 16

Dibond 60 L

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: Dust when sawing or tear out. Allow affected person to breathe fresh air.
First-aid measures after skin contact	: Gently wash with plenty of soap and water.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: Cough.
-----------------------------------	----------

4.3. Indication of immediate medical attention and special treatment needed, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: In case of fire, all extinguishing media allowed.

5.2. Specific hazards arising from the chemical

Fire hazard	: Not flammable.
Hazardous decomposition products in case of fire	: Fire conditions may produce small amounts of hexavalent chromium and other oxidation products.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Protective equipment	: Safety shoes. Protective gloves. Safety glasses.
Emergency procedures	: Avoid contact with skin. Avoid contact with eyes.

For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment.
----------------------	--

6.2. Methods and materials for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: On land, sweep or shovel into suitable containers.

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Hygiene measures	: Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Wash skin thoroughly with mild soap and water.
------------------	---

7.2. Conditions for safe storage, including incompatibilities

Storage conditions	: Store this product in a dry location where it can be protected from the elements.
Incompatible products	: Strong acids. Chromic oxide may react with alkali at high temperatures under oxidizing conditions.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Magnesium Oxide (1309-48-4)

USA - ACGIH - Occupational Exposure Limits

ACGIH® TLV® TWA	10 mg/m³ inhalable dust
-----------------	-------------------------

USA - OSHA - Occupational Exposure Limits

OSHA PEL TWA	10 mg/m³ respirable dust
--------------	--------------------------

Transvaal Chrome Ore (1308-31-2)

USA - ACGIH - Occupational Exposure Limits

ACGIH® TLV® TWA	0.05 mg/m³ inhalable dust
-----------------	---------------------------

8.2. Appropriate engineering controls

Appropriate engineering controls	: Dust when sawing or tear out. Provide adequate ventilation to minimize dust concentrations.
----------------------------------	---

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Dibond 60 L

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Hand protection:	
Wear protective gloves.	
Eye protection:	
Chemical goggles or safety glasses	
Skin and body protection:	
Safety shoes. Wear suitable protective clothing	
Respiratory protection:	
Dust when sawing or tear out. Wear appropriate mask	
SECTION 9 Physical and chemical properties	
9.1. Basic physical and chemical properties	
Physical state	: Solid
Appearance	: Solid in various shapes.
Color	: Dark
Odor	: None
Odor threshold	: No data available
pH	: No data available
Melting point	: > 2500 °F
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Flammability (solid, gas)	: Not flammable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: ≈ 3
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosion limits	: No data available
Particle characteristics	: No data available
9.2. Data relevant with regard to physical hazard classes (supplemental)	
No additional information available	
SECTION 10 Stability and reactivity	
10.1. Reactivity	
Fire conditions may produce small amounts of hexavalent chromium and other oxidation products.	
10.2. Chemical stability	
No additional information available	
10.3. Possibility of hazardous reactions	
No additional information available	
10.4. Conditions to avoid	
No additional information available	
10.5. Incompatible materials	
No additional information available	
10.6. Hazardous decomposition products	
No additional information available	
SECTION 11 Toxicological information	
11.1. Information on toxicological effects	
Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Magnesium Oxide (1309-48-4)	
LD50 oral rat	> 5000 mg/kg (Rat, Literature study, Oral)

Dibond 60 L

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Magnesium Oxide (1309-48-4)	
LD50 dermal rabbit	> 2000 mg/kg body weight (Rabbit, Literature study, Dermal)
Skin corrosion/irritation	: Causes skin irritation.
Magnesium Oxide (1309-48-4)	
pH	11 (10 %)
Serious eye damage/irritation	: Not classified
Magnesium Oxide (1309-48-4)	
pH	11 (10 %)
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation from dust in sawing or tear out operations.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Magnesium Oxide (1309-48-4)	
Viscosity, kinematic	Not applicable (solid)
Symptoms/effects after inhalation	: Cough.
SECTION 12 Ecological information	
12.1. Ecotoxicity	
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified
12.2. Persistence and degradability	
Dibond 60 L (Mixture)	
Persistence and degradability	Rapidly degradable
Magnesium Oxide (1309-48-4)	
Persistence and degradability	Not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
Transvaal Chrome Ore (1308-31-2)	
Persistence and degradability	Not established.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
12.3. Bioaccumulative potential	
Magnesium Oxide (1309-48-4)	
Bioaccumulative potential	No bioaccumulation data available.
Transvaal Chrome Ore (1308-31-2)	
Bioaccumulative potential	No data available.
12.4. Mobility in soil	
Magnesium Oxide (1309-48-4)	
Surface tension	No data available in the literature
Ecology - soil	No data available.
Transvaal Chrome Ore (1308-31-2)	
Ecology - soil	No data available.
12.5. Other adverse effects	
Ozone	: Not classified
Fluorinated greenhouse gases	: No

Dibond 60 L

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 13 Disposal considerations

Product/Packaging disposal recommendations : Chromite (Cr⁺³) may in normal use be converted chemically to a chromate (Cr⁺⁶). Hexavalent chromium (Cr⁺⁶) is considered a hazardous material.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

Department of Transportation (DOT)

In accordance with DOT

Not regulated

Transportation of Dangerous Goods

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

Transvaal Chrome Ore	CAS-No. 1308-31-2	30 – 60%
----------------------	-------------------	----------

15.2. International regulations

CANADA

Magnesium Oxide (1309-48-4)

Listed on the Canadian DSL (Domestic Substances List)

Transvaal Chrome Ore (1308-31-2)

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. State regulations

Dibond 60 L (Mixture)

U.S. - California - Proposition 65 - Other information	This product contains chromite (Cr ⁺³) which may in normal use, be converted chemically to a chromate (Cr ⁺⁶) hexavalent chrome, a chemical known to the State of California to cause cancer.
--	---

Transvaal Chrome Ore (1308-31-2)

U.S. - California - Proposition 65 - Other information	This product contains chromite (Cr ⁺³) which may in normal use, be converted chemically to a chromate (Cr ⁺⁶) hexavalent chrome, a chemical known to the State of California to cause cancer.
--	---

Component	State or local regulations
Magnesium Oxide(1309-48-4)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Transvaal Chrome Ore(1308-31-2)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Revision date : 8/26/2025

Issue date : 5/1/2015

Other information : Report language name. English. In the event of any conflict between English and other language versions, the English version shall prevail.

Full text of hazard classes and H-statements

H315	Causes skin irritation
H335	May cause respiratory irritation

Safety Data Sheet (SDS), USA

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, RHI Magnesita makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.