

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 4/21/2023 Revision date: 4/21/2023 Supersedes: 10/29/2020

SECTION 1: Identification			
1.1. Identification			
Product form Product name CAS-No. Product code	: Mixture : Kricon 30 : Mixture : 0951 Alwaina Silinata Contact Decided Contacta		
Other means of identification	: Alumina-Silicate Cement Bonded Castable		
1.2. Recommended use and restrictions on			
Use of the substance/mixture Recommended use	: Refractory : Industrial use		
1.3. Supplier			
Resco Products, Inc. One Robinson Plaza, Suite 300 6600 Steubenville Pike Pittsburgh, PA, 15205 United States 412-494-4491 <u>SDS@RescoProducts.com</u> - <u>WWW.RescoProducts</u>	.com		
1.4. Emergency telephone number			
Emergency number	: EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300 Outside USA & Canada +1 703-741-5970		
SECTION 2: Hazard(s) identification			
2.1. Classification of the substance or mixt	ure		
GHS US classification Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2B Carcinogenicity Category 1A Full text of H statements : see section 16	H315Causes skin irritationH320Causes eye irritationH350May cause cancer (Inhalation)		
2.2. GHS Label elements, including precau	tionary statements		
GHS US labeling Hazard pictograms (GHS US)			
Signal word (GHS US) Hazard statements (GHS US) Precautionary statements (GHS US)	rd statements (GHS US) : H315 - Causes skin irritation H320 - Causes eye irritation H350 - May cause cancer (Inhalation)		
2.3. Other hazards which do not result in c	lassification		
No additional information available			
2.4. Unknown acute toxicity (GHS US)			
No additional information available			
SECTION 3: Composition/Information	on ingredients		
3.1. Substances			
Not applicable			
3.2. Mixtures			
Name	Product identifier % GHS US classification		
cristobalite	CAS-No.: 14464-46-1 10 – 20 Carc. 1A, H350		
aluminium oxide, non-fibrous	CAS-No.: 1344-28-1 5 – 10 Not classified		
Calcium Aluminate Cement	CAS-No.: 65997-16-2 1 – 5 Skin Irrit. 2, H315 Eye Irrit. 2B, H320		
quartz	CAS-No.: 14808-60-7 1 – 5 Carc. 1A, H350		

Safety Data Sheet

Full text of hazard classes and H-statements : see se	action 16		
SECTION 4: First-aid measures			
4.1. Description of first aid measures			
First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).		
First-aid measures after inhalation First-aid measures after skin contact	 Allow affected person to breathe fresh air. Allow the victim to rest. Gently wash with plenty of soap and water. 		
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present		
First-aid measures after ingestion	and easy to do. Continue rinsing. Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.		
4.2. Most important symptoms and effects (
Potential Adverse human health effects and	: Based on available data, the classification criteria are not met.		
symptoms			
Symptoms/effects after inhalation	: May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure through inhalation.		
Symptoms/effects after skin contact	: Causes skin irritation.		
Symptoms/effects after eye contact	: Causes eye irritation.		
4.3. Immediate medical attention and special No additional information available	in treatment, in necessary		
SECTION 5: Fire-fighting measures			
5.1. Suitable (and unsuitable) extinguishing			
Suitable extinguishing media Unsuitable extinguishing media	 Use extinguishing media appropriate for surrounding fire. In case of fire, all extinguishing media allowed. 		
5.2. Specific hazards arising from the chem			
Fire hazard	: Not flammable.		
5.3. Special protective equipment and preca	· · · · · · · · · · · · · · · · · · ·		
Firefighting instructions	: Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.		
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.		
SECTION 6: Accidental release measure	es		
6.1. Personal precautions, protective equip	nent and emergency procedures		
6.1.1. For non-emergency personnel Emergency procedures	: Do not breathe dust. Avoid contact with skin and eyes.		
6.1.2. For emergency responders			
Protective equipment Emergency procedures	 Equip cleanup crew with proper protection. Ventilate area. On land, sweep or shovel into suitable containers. 		
6.2. Environmental precautions			
Prevent entry to sewers and public waters.			
6.3. Methods and material for containment a	and cleaning up		
Methods for cleaning up	: On land, sweep or shovel into suitable containers. Minimize generation of dust.		
6.4. Reference to other sections			
See Heading 8. Exposure controls and personal prote	ection.		
SECTION 7: Handling and storage			
7.1. Precautions for safe handling	. De not bondle until ell cofety propositione have been read and an dender the definition of the		
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Avoid raising dust. Avoid contact with skin and eyes. Do not breathe dust.		
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.		
7.2. Conditions for safe storage, including a			
Storage conditions	: Store this product in a dry location where it can be protected from the elements.		
Incompatible products	: Strong bases. Strong acids.		
SECTION 8: Exposure controls/persona			
8.1. Control parameters			
Kricon 30 (Mixture) No additional information available			

Safety Data Sheet

Calcium Aluminate Cement (65997-16-2)	
No additional information available	
cristobalite (14464-46-1)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	0.025 mg/m ³ respirable dust
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) [1]	0.05 mg/m ³ respirable dust
aluminium oxide, non-fibrous (1344-28-1)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	1 mg/m ³ respirable dust
quartz (14808-60-7)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	0.025 mg/m³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)
USA - OSHA - Occupational Exposure Limits	
Local name	Silica, crystalline quartz, respirable dust
OSHA PEL (TWA) [1]	0.05 mg/m ³ respirable dust
Remark (OSHA)	(3) See Table Z-3.
8.2. Appropriate engineering controls	
Appropriate engineering controls 8.3. Individual protection measures/Personal Personal protective equipment: Avoid all unnecessary exposure.	: Provide adequate ventilation to minimize dust concentrations. I protective equipment
Hand protection:	
Wear protective gloves.	
Eye protection:	
Chemical goggles or safety glasses	
Skin and body protection:	
Wear suitable protective clothing	
Respiratory protection:	
Wear appropriate mask	
Other information: Do not eat, drink or smoke during use.	
SECTION 9: Physical and chemical prop	erties
9.1. Information on basic physical and chem	
	: Solid : Granular mixture.
	: Gray : earthy
Odor threshold	No data available
pH Melting point	: No data available : > 2500 °F
Freezing point	No data available
Boiling point Flash point	: No data available : No data available
Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure	No data available Not flammable. No data available

Safety Data Sheet

Relative vapor density at 20°C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Viscosity, kinematic Viscosity, dynamic Explosion limits Explosive properties Oxidizing properties 9.2. Other information No additional information available	 No data available ≈ 2.3 Slightly soluble. No data available
SECTION 10: Stability and reactivity	
10.1. Reactivity	
Hydraulic setting.	
10.2. Chemical stability	
Stable under normal conditions of use.	
10.3. Possibility of hazardous reactions	
Not established.	
10.4. Conditions to avoid	
Avoid dust formation.	
10.5. Incompatible materials	
Strong acids. Strong bases. 10.6. Hazardous decomposition products	
No additional information available	
SECTION 11: Toxicological information	
11.1. Information on toxicological effects	
Acute toxicity (oral) Acute toxicity (dermal)	: Not classified : Not classified
Acute toxicity (inhalation)	: Not classified
aluminium oxide, non-fibrous (1344-28-1)	
LD50 oral rat	> 15900 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LC50 Inhalation - Rat	> 2.3 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))
Skin corrosion/irritation	Causes skin irritation.
Calcium Aluminate Cement (65997-16-2)	
рН	≤ 13
cristobalite (14464-46-1)	
pH	6 – 7
aluminium oxide, non-fibrous (1344-28-1)	
рН	9 – 10.5 (aqueous suspension, 33 %)
quartz (14808-60-7)	
pH	6 - 7
•	Causes eye irritation.
Calcium Aluminate Cement (65997-16-2)	
pH	≤ 13
cristobalite (14464-46-1)	
pH	6 - 7

Safety Data Sheet

aluminium oxide, non-fibrous (1344-28-1)			
рН	9 – 10.5 (aqueous suspension, 33 %)		
quartz (14808-60-7)			
рН	6 - 7		
Respiratory or skin sensitization	: Not classified		
Germ cell mutagenicity Carcinogenicity	: Not classified : May cause cancer (Inhalation).		
quartz (14808-60-7)			
IARC group	1 - Carcinogenic to humans		
Reproductive toxicity STOT-single exposure STOT-repeated exposure	: Not classified : Not classified : Not classified		
Aspiration hazard Viscosity, kinematic	: Not classified : Not classified : Not Applicable		
aluminium oxide, non-fibrous (1344-28-1)			
Viscosity, kinematic	Not applicable (solid)		
symptoms	: Based on available data, the classification criteria are not met.		
Symptoms/effects after inhalation	: May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure through inhalation.		
Symptoms/effects after skin contact Symptoms/effects after eye contact	: Causes skin irritation. : Causes eye irritation.		
SECTION 12: Ecological information			
12.1. Toxicity			
aluminium oxide, non-fibrous (1344-28-1)			
LC50 - Fish [1]	> 100 mg/l (96 h, Salmo trutta, Literature study)		
EC50 - Crustacea [1]	> 100 mg/l (48 h, Daphnia magna, Literature study)		
12.2. Persistence and degradability			
Kricon 30 (Mixture)			
Persistence and degradability	Not established.		
cristobalite (14464-46-1)			
Persistence and degradability	Mineral. Not applicable.		
Chemical oxygen demand (COD)	Not applicable		
ThOD	Not applicable		
BOD (% of ThOD)	Not applicable		
aluminium oxide, non-fibrous (1344-28-1)			
Persistence and degradability	Not applicable.		
Chemical oxygen demand (COD)	Not applicable		
ThOD	Not applicable		
quartz (14808-60-7)			
Persistence and degradability	Not applicable.		
Biochemical oxygen demand (BOD)	Not applicable		
Chemical oxygen demand (COD)	Not applicable		
ThOD	Not applicable		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potent	ial	
Kricon 30 (Mixture)		
Bioaccumulative potential	Not established.	
cristobalite (14464-46-1)		
Bioaccumulative potential	No data available.	
aluminium oxide, non-fibrous	s (1344-28-1)	
Bioaccumulative potential	No data available.	
quartz (14808-60-7)		
Bioaccumulative potential	No data available.	
12.4. Mobility in soil		
cristobalite (14464-46-1)		
Ecology - soil	No data available.	
aluminium oxide, non-fibrous	s (1344-28-1)	
Surface tension	No data available in the literature	
Ecology - soil	No data available.	
12.5. Other adverse effects		
Effect on the global warming	: None known	
SECTION 13: Disposal cor	siderations	
13.1. Disposal methods		
Product/Packaging disposal recomr Ecology - waste materials	nendations : Dispose in a safe manner in accordance with local/national regulations. : Avoid release to the environment.	
SECTION 14: Transport inf	iormation	
In accordance with DOT / TDG / IM Department of Transportation (I In accordance with DOT Not regulated Transportation of Dangerous Go Not regulated Transport by sea Not regulated Air transport Not regulated	ΟΟΤ)	
SECTION 15: Regulatory in	hformation	
15.1. US Federal regulations		
All components of this product are (TSCA) inventory	present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act	
aluminium oxide, non-fibrous	s (1344-28-1)	
Not subject to reporting requirement	nts of the United States SARA Section 313	
lote Note: The section 313 chemical list contains "CAS # 1344-28-1 Aluminum Oxide (Fibrous forms)"; the Aluminum oxide contained in this product is non-fibrous, and thus is not a section 313 material. Only manufacturing, processing, or otherwise use of aluminum oxide in the fibrous form triggers reporting.		
15.2. International regulations	ŝ	
CANADA		
Calcium Aluminate Cement (65997-16-2)		

Listed on the Canadian DSL (Domestic Substances List)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

cristobalite (14464-4					
Listed on the Canadian	DSL (Domestic Substances Lis	st)			
aluminium oxide, no	on-fibrous (1344-28-1)				
Listed on the Canadian	DSL (Domestic Substances Li	st)			
EU-Regulations No additional informatior National regulations	n available				
quartz (14808-60-7)					
Listed on IARC (Interna	tional Agency for Research on	Cancer)			
15.3. US State regula	ations				
Kricon 30 (Mixture)					
U.S California - Proposition 65 - Other information		This product contains crystalline silica, a chemical known to the state of California to cause cancer. For more information go to WWW.P65Warnings.ca.gov			
cristobalite (14464-4	46-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		
quartz (14808-60-7)					
U.S California -	U.S California -	U.S California -	U.S California -	No significant risk	Maximum allowable
Proposition 65 - Carcinogens List	Proposition 65 - Developmental Toxicity	Proposition 65 - Reproductive Toxicity - Female	Proposition 65 - Reproductive Toxicity - Male	level (NSRL)	dose level (MADL)
Yes	No	No	No		
Component		State or least result	ations		
Cristobalite (14464-46-1)		State or local regulations U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List			
aluminium oxide, non-fibrous (1344-28-1)		U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List			
Quartz (14808-60-7)		U.S New Jersey - Right to Know Hazardous Substance List			
SECTION 16: Othe	er information				
	gister / Vol. 77, No. 58 / Monda		es and Regulations		
Other information : F		4/21/2023 Report language name. English. In the event of any conflict between English and other language versions, the English version shall prevail.			
Full text of H-phrases					
H315 Cau	uses skin irritation				

Full text of H-phrases		
H315	Causes skin irritation	
H320	Causes eye irritation	
H350	May cause cancer	
Cofety Data Chaot (CDC) LICA		

Safety Data Sheet (SDS), USA This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.