

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 4/24/2023 Revision date: 4/24/2023 Supersedes: 10/29/2020

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Kricon 32
CAS-No. : Mixture
Product code : 0956

Other means of identification : Alumina-Silicate Cement Bonded Castable

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Refractory Recommended use : Industrial use

1.3. Supplier

Resco Products, Inc.
One Robinson Plaza, Suite 300
6600 Steubenville Pike
Pittsburgh, PA, 15205
United States
412-494-4491

SDS@RescoProducts.com - WWW.RescoProducts.com

1.4. Emergency telephone number

Emergency number : EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300

Outside USA & Canada +1 703-741-5970

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2B

Carcinogenicity Category 1A

H315

Causes skin irritation

Causes eye irritation

Causes eye irritation

May cause cancer (Inhalation)

Full text of H statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)





Signal word (GHS US) : Danger

Hazard statements (GHS US) : H315 - Causes skin irritation H320 - Causes eye irritation

H350 - May cause cancer (Inhalation)

Precautionary statements (GHS US) : P280 - Wear eye protection, Dust respirator, protective gloves.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention.

P260 - Do not breathe dust.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
aluminium oxide. non-fibrous	CAS-No.: 1344-28-1	7.0	Not classified
Calcium Aluminate Cement	CAS-No.: 65997-16-2	1 – 5	Skin Irrit. 2. H315
			Eye Irrit. 2B, H320
cristobalite	CAS-No.: 14464-46-1	0.1 – 0.5	Carc. 1A, H350

Full text of hazard classes and H-statements : see section 16

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice

(show the label where possible).

First-aid measures after inhalation : Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Gently wash with plenty of soap and water.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and : Based on available data, the classification criteria are not met.

symptoms

Symptoms/effects after inhalation : May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure

through inhalation.
: Causes skin irritation.

Symptoms/effects after eye contact : Causes eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

Symptoms/effects after skin contact

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : In case of fire, all extinguishing media allowed.

5.2. Specific hazards arising from the chemical

Fire hazard : Not flammable.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering

environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Do not breathe dust. Avoid contact with skin and eyes.

6.1.2. For emergency respondersProtective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area. On land, sweep or shovel into suitable containers.

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : On land, sweep or shovel into suitable containers. Minimize generation of dust.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Avoid raising dust.

Avoid contact with skin and eyes. Do not breathe dust.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store this product in a dry location where it can be protected from the elements.

Incompatible products : Strong bases. Strong acids.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Kricon 32 (Mixture)

No additional information available

4/24/2023 (Revision date) EN (English US) 2/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Calcium Aluminate Cement (65997-16-2)		
No additional information available		
cristobalite (14464-46-1)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	0.025 mg/m³ respirable dust	
USA - OSHA - Occupational Exposure Limits		
OSHA PEL (TWA) [1]	0.05 mg/m³ respirable dust	
aluminium oxide, non-fibrous (1344-28-1)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA 1 mg/m³ respirable dust		

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide adequate ventilation to minimize dust concentrations.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid

Appearance : Granular mixture.
Color : Grav

Odor : earthy

Odor threshold : No data available

pH : No data available

Melting point : > 2000 °F Freezing point : No data available

Boiling point : No data available Flash point : No data available Relative evaporation rate (butyl acetate=1) : No data available

Flammability (solid, gas) : Not flammable. Vapor pressure : No data available Relative vapor density at 20°C : No data available Relative density : $\approx 2.5 (\le 3)$ Solubility : Slightly soluble.

Partition coefficient n-octanol/water (Log Pow)

Auto-ignition temperature

Decomposition temperature

Viscosity, kinematic

Viscosity, dynamic

Explosion limits

No data available

No data available

No data available

No data available

Oxidizing properties

9.2. Other information

No additional information available

Explosive properties

4/24/2023 (Revision date) EN (English US) 3/6

No data available No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

11 20, 2012 / Rules and Regulations
Not classified
Not classified
Not classified
> 15900 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
> 2.3 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))
Causes skin irritation.
≤ 13
6 – 7
9 – 10.5 (aqueous suspension, 33 %)
Causes eye irritation.
≤ 13
6 – 7
<u></u>
9 – 10.5 (aqueous suspension, 33 %)
Not classified
Not classified Not classified
Not classified Not classified May cause cancer (Inhalation).
Not classified Not classified May cause cancer (Inhalation). Not classified
Not classified Not classified May cause cancer (Inhalation). Not classified Not classified
Not classified Not classified May cause cancer (Inhalation). Not classified
Not classified Not classified May cause cancer (Inhalation). Not classified Not classified Not classified
Not classified Not classified May cause cancer (Inhalation). Not classified Not classified Not classified Not classified Not classified

4/24/2023 (Revision date) EN (English US) 4/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Potential Adverse human health effects and : Based on available data, the classification criteria are not met. symptoms Symptoms/effects after inhalation May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure through inhalation. Causes skin irritation. Symptoms/effects after skin contact Symptoms/effects after eye contact Causes eye irritation. **SECTION 12: Ecological information** 12.1. Toxicity aluminium oxide, non-fibrous (1344-28-1) LC50 - Fish [1] > 100 mg/l (96 h, Salmo trutta, Literature study) EC50 - Crustacea [1] > 100 mg/l (48 h, Daphnia magna, Literature study) 12.2. Persistence and degradability Kricon 32 (Mixture) Persistence and degradability Not established. cristobalite (14464-46-1) Persistence and degradability Mineral. Not applicable. Chemical oxygen demand (COD) Not applicable ThOD Not applicable BOD (% of ThOD) Not applicable aluminium oxide, non-fibrous (1344-28-1) Persistence and degradability Not applicable. Chemical oxygen demand (COD) Not applicable ThOD Not applicable 12.3. Bioaccumulative potential Kricon 32 (Mixture) Bioaccumulative potential Not established. cristobalite (14464-46-1) Bioaccumulative potential No data available. aluminium oxide, non-fibrous (1344-28-1) Bioaccumulative potential No data available. 12.4. Mobility in soil cristobalite (14464-46-1) Ecology - soil No data available. aluminium oxide, non-fibrous (1344-28-1)

No data available in the literature Surface tension Ecology - soil No data available.

12.5. Other adverse effects

Effect on the global warming : None known

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

Department of Transportation (DOT)

In accordance with DOT

Not regulated

Transportation of Dangerous Goods

Not regulated Transport by sea Not regulated

Air transport Not regulated

4/24/2023 (Revision date) EN (English US) 5/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

aluminium oxide, non-fibrous (1344-28-1)

Not subject to reporting requirements of the United States SARA Section 313

Note: The section 313 chemical list contains "CAS # 1344-28-1 Aluminum Oxide (Fibrous forms)"; the Aluminum oxide contained in this product is non-fibrous, and thus is not a section 313 material. Only manufacturing, processing, or otherwise use of aluminum oxide in the fibrous form triggers reporting.

15.2. International regulations

CANADA

Calcium Aluminate Cement (65997-16-2)

Listed on the Canadian DSL (Domestic Substances List)

cristobalite (14464-46-1)

Listed on the Canadian DSL (Domestic Substances List)

aluminium oxide, non-fibrous (1344-28-1)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

Kricon 32 (Mixture)

U.S. - California - Proposition 65 - Other information

This product contains crystalline silica, a chemical known to the state of California to cause cancer. For more information go to WWW.P65Warnings.ca.gov

cristo	halita	(14464-	46-1)

CHStobalite (14404 40	<u>'</u>				
U.S California -	U.S California -	U.S California -	U.S California -	No significant risk	Maximum allowable
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	level (NSRL)	dose level (MADL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity	Reproductive Toxicity		
_		- Female	- Male		
Yes	No	No	No		

Component	State or local regulations
Cristobalite (14464-46-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous
	Substance List; U.S Pennsylvania - RTK (Right to Know) List
aluminium oxide, non-fibrous (1344-28-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous
	Substance List; U.S Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 4/24/2023

Other information : Report language name. English. In the event of any conflict between English and other language

versions, the English version shall prevail.

	receive, and engineer receive process	
Full text of H-phrases		
H315	Causes skin irritation	
H320	Causes eye irritation	
H350	May cause cancer	

Safety Data Sheet (SDS), USA

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.

4/24/2023 (Revision date) EN (English US) 6/6