



LL 90 PB-C 3% Graphite

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 8/14/2023 Revision date: 8/14/2023 Supersedes: 1/13/2023

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : LL 90 PB-C 3% Graphite
CAS-No. : Mixture
Product code : 8628
Other means of identification : Alumina-Silicate Wet Chemically Bonded Mortar-Slurry

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Refractory
Recommended use : Industrial use

1.3. Supplier

Resco Products, Inc.
One Robinson Plaza, Suite 300
6600 Steubenville Pike
Pittsburgh, PA, 15205
United States
412-494-4491
SDS@RescoProducts.com - WWW.RescoProducts.com

1.4. Emergency telephone number

Emergency number : EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300
Outside USA & Canada +1 703-741-5970

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Serious eye damage/eye irritation, Category 2B	H320	Causes eye irritation
Carcinogenicity, Category 1A	H350	May cause cancer (After drying or heating, Inhalation).

Full text of H-statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) : H315 - Causes skin irritation.
H320 - Causes eye irritation
H350 - May cause cancer (After drying or heating, Inhalation).

Precautionary statements (GHS US) : P202 - Do not handle until all safety precautions have been read and understood.
P280 - Wear eye protection, protective gloves, protective clothing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
aluminium oxide, non-fibrous	CAS-No.: 1344-28-1	50 – 75	Not classified
phosphoric acid, conc=75%, aqueous solution	CAS-No.: 7664-38-2	5 – 10	Skin Corr. 1B, H314
graphite	CAS-No.: 7782-42-5	1 – 5	Not classified
quartz	CAS-No.: 14808-60-7	1 – 5	Carc. 1A, H350

Full text of hazard classes and H-statements : see section 16

LL 90 PB-C 3% Graphite

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Gently wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects (acute and delayed)

Potential adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/effects after inhalation	: After drying or heating. May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure through inhalation.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: No unsuitable extinguishing media known.

5.2. Specific hazards arising from the chemical

Fire hazard	: Not flammable.
-------------	------------------

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: If spilled, may cause the floor to be slippery.
----------------------	---

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Stop release.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Plug the leak, cut off the supply.
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage.

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Avoid contact with eyes. Avoid contact with skin.
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store in original container. Keep container closed when not in use.
Incompatible products	: Strong bases. Avoid contact with materials: such as sulfides and sulfites which could release toxic gases, mixing with strong bases because high heat of reaction can generate steam, and metals which could liberate hydrogen, a flammable gas.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

LL 90 PB-C 3% Graphite

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

LL 90 PB-C 3% Graphite (Mixture)

No additional information available

aluminium oxide, non-fibrous (1344-28-1)

USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA	1 mg/m ³ respirable dust
---------------	-------------------------------------

phosphoric acid, conc=75%, aqueous solution (7664-38-2)

No additional information available

graphite (7782-42-5)

USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA	2 mg/m ³ (Respirable fraction)
---------------	---

quartz (14808-60-7)

USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA	0.025 mg/m ³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)
---------------	--

USA - OSHA - Occupational Exposure Limits

Local name	Silica, crystalline quartz, respirable dust
------------	---

OSHA PEL TWA [1]	0.05 mg/m ³ respirable dust
------------------	--

Remark (OSHA)	(3) See Table Z-3.
---------------	--------------------

8.2. Appropriate engineering controls

Appropriate engineering controls : Emergency eye wash fountain with clean water.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

After air drying or heating. Dust when sawing or tear out. Wear appropriate mask

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Slurry.
Colour	: Grey
Odour	: Acid Odor
Odour threshold	: No data available
pH	: < 3
Melting point	: > 2500 °F
Freezing point	: ≈ 32 °F
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Not flammable.
Vapour pressure	: No data available

LL 90 PB-C 3% Graphite

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative vapour density at 20°C	: No data available
Relative density	: ≈ 2.4
Solubility	: Moderately soluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: Not Applicable
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Air Setting.

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

Strong bases. Avoid contact with materials: such as sulfides and sulfites which could release toxic gases, mixing with strong bases because high heat of reaction can generate steam, and metals which could liberate hydrogen, a flammable gas.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

aluminium oxide, non-fibrous (1344-28-1)

LD50 oral rat	> 15900 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LC50 Inhalation - Rat	> 2.3 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))

phosphoric acid, conc=75%, aqueous solution (7664-38-2)

ATE US (oral)	4400 mg/kg bodyweight
---------------	-----------------------

graphite (7782-42-5)

LD50 oral rat	> 2000 mg/kg (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Female, Experimental value, Oral)
LC50 Inhalation - Rat	> 2000 mg/m ³ air (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (dust))

Skin corrosion/irritation : Causes skin irritation.
pH: < 3

aluminium oxide, non-fibrous (1344-28-1)

pH	9 – 10.5 (aqueous suspension, 33 %)
----	-------------------------------------

phosphoric acid, conc=75%, aqueous solution (7664-38-2)

pH	0 – 0.5 (20 °C)
----	-----------------

LL 90 PB-C 3% Graphite

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

graphite (7782-42-5)

pH 7 (1.3 %)

quartz (14808-60-7)

pH 6 – 7

Serious eye damage/irritation : Causes eye irritation.
pH: < 3

aluminium oxide, non-fibrous (1344-28-1)

pH 9 – 10.5 (aqueous suspension, 33 %)

phosphoric acid, conc=75%, aqueous solution (7664-38-2)

pH 0 – 0.5 (20 °C)

graphite (7782-42-5)

pH 7 (1.3 %)

quartz (14808-60-7)

pH 6 – 7

Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : May cause cancer (After drying or heating, Inhalation).

quartz (14808-60-7)

IARC group 1 - Carcinogenic to humans

Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified
Viscosity, kinematic : Not Applicable

aluminium oxide, non-fibrous (1344-28-1)

Viscosity, kinematic Not applicable (solid)

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met.
Symptoms/effects after inhalation : After drying or heating. May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure through inhalation.
Symptoms/effects after skin contact : Causes skin irritation.
Symptoms/effects after eye contact : Causes serious eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

aluminium oxide, non-fibrous (1344-28-1)

LC50 - Fish [1] > 100 mg/l (96 h, Salmo trutta, Literature study)
EC50 - Crustacea [1] > 100 mg/l (48 h, Daphnia magna, Literature study)

graphite (7782-42-5)

LC50 - Fish [1] > 100 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1] > 100 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Behaviour)
EC50 72h - Algae [1] > 100 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)
EC50 72h - Algae [2] > 100 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Cell numbers)

12.2. Persistence and degradability

LL 90 PB-C 3% Graphite (Mixture)

Persistence and degradability Not established.

aluminium oxide, non-fibrous (1344-28-1)

Persistence and degradability Not applicable.

LL 90 PB-C 3% Graphite

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

aluminium oxide, non-fibrous (1344-28-1)

Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

phosphoric acid, conc=75%, aqueous solution (7664-38-2)

Persistence and degradability	Biodegradability: not applicable.
-------------------------------	-----------------------------------

graphite (7782-42-5)

Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

quartz (14808-60-7)

Persistence and degradability	Not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

12.3. Bioaccumulative potential

LL 90 PB-C 3% Graphite (Mixture)

Bioaccumulative potential	Not established.
---------------------------	------------------

aluminium oxide, non-fibrous (1344-28-1)

Bioaccumulative potential	No data available.
---------------------------	--------------------

phosphoric acid, conc=75%, aqueous solution (7664-38-2)

Bioaccumulative potential	No test data of component(s) available.
---------------------------	---

graphite (7782-42-5)

Bioaccumulative potential	Not bioaccumulative.
---------------------------	----------------------

quartz (14808-60-7)

Bioaccumulative potential	No data available.
---------------------------	--------------------

12.4. Mobility in soil

aluminium oxide, non-fibrous (1344-28-1)

Surface tension	No data available in the literature
Ecology - soil	No data available.

phosphoric acid, conc=75%, aqueous solution (7664-38-2)

Ecology - soil	Highly mobile in soil.
----------------	------------------------

12.5. Other adverse effects

Effect on global warming	: None known
Other information	: Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

Department of Transportation (DOT)

In accordance with DOT

Not regulated

Transportation of Dangerous Goods

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

aluminium oxide, non-fibrous (1344-28-1)

Not subject to reporting requirements of the United States SARA Section 313

LL 90 PB-C 3% Graphite

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

aluminium oxide, non-fibrous (1344-28-1)

Note	Note: The section 313 chemical list contains "CAS # 1344-28-1 Aluminum Oxide (Fibrous forms)"; the Aluminum oxide contained in this product is non-fibrous, and thus is not a section 313 material. Only manufacturing, processing, or otherwise use of aluminum oxide in the fibrous form triggers reporting.
------	--

phosphoric acid, conc=75%, aqueous solution (7664-38-2)

Not subject to reporting requirements of the United States SARA Section 313

CERCLA RQ 5000 lb

15.2. International regulations

CANADA

aluminium oxide, non-fibrous (1344-28-1)

Listed on the Canadian DSL (Domestic Substances List)

phosphoric acid, conc=75%, aqueous solution (7664-38-2)

Listed on the Canadian DSL (Domestic Substances List)

graphite (7782-42-5)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

quartz (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

LL 90 PB-C 3% Graphite (Mixture)

U.S. - California - Proposition 65 - Other information	This product contains crystalline silica, a chemical known to the state of California to cause cancer. For more information go to WWW.P65Warnings.ca.gov
--	--

quartz (14808-60-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

Component

State or local regulations

aluminium oxide, non-fibrous (1344-28-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
phosphoric acid, conc=75%, aqueous solution (7664-38-2)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Graphite (7782-42-5)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Quartz (14808-60-7)	U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 8/14/2023

Other information : Report language name. English. In the event of any conflict between the English and other language versions, the English version shall prevail.

Full text of H-statements

H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H320	Causes eye irritation
H350	May cause cancer.

Safety Data Sheet (SDS), USA

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.