



MaxLine 10 AFX

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 11/16/2020

Revision date: 11/16/2020

Supersedes: 03/19/2019

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : MaxLine 10 AFX
CAS-No. : Mixture
Product code : 7166
Other means of identification : Resin Bonded, Magnesia-Carbon Brick

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Refractory Brick
Recommended use : Industrial use

1.3. Supplier

Resco Products, Inc.
One Robinson Plaza, Suite 300
6600 Steubenville Pike
Pittsburgh, PA 15205 - United States
412-494-4491

SDS@RescoProducts.com - WWW.RescoProducts.com

1.4. Emergency telephone number

Emergency number : EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300
Outside USA & Canada +1 703-741-5970

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Germ cell mutagenicity Category 1B H340 May cause genetic defects
Carcinogenicity Category 1A H350 May cause cancer

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
Hazard statements (GHS US) : H340 - May cause genetic defects
H350 - May cause cancer
Precautionary statements (GHS US) : P202 - Do not handle until all safety precautions have been read and understood.
P280 - Wear Safety shoes, protective clothing, eye protection, protective gloves.
P261 - Sawing or tear out operations- Avoid breathing dust.

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : This product contains minor amounts of materials derived from petroleum and/or coal (such as petroleum pitch and/or coal tar pitch). These materials, in turn, contain compounds, which are carcinogenic. Petroleum pitch contains poly-nuclear aromatic compounds, some of which have been identified as carcinogenic. Based on this, NIOSH has identified petroleum pitch as a carcinogenic material. IARC has reported that there is sufficient evidence for the carcinogenicity of "untreated and mildly refined mineral oils" in humans, but no adequate data is available to evaluate the carcinogenicity of "highly refined mineral oils". Coal tars are by products of the destructive distillation of coal to produce coke and/or gas, and are believed to contain from 400-10,000 separate compounds. One important class of compounds present in coal tars is the so-called polycyclic aromatic hydrocarbons (PAHs). While not all PAHs have been determined to be human carcinogens, many have. The NTP Seventh Annual Report on Carcinogens (1994) listed 15 PAH compounds which "may reasonably be anticipated to be carcinogens".

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Magnesium Oxide	(CAS-No.) 1309-48-4	75 - 95	Not classified
graphite	(CAS-No.) 7782-42-5	5 - 10	Not classified
Phenolic Resin	(CAS-No.) 108-95-2	1 - 5	Not classified
Aluminum - metal powder	(CAS-No.) 7429-90-5	1 - 5	Not classified

MaxLine 10 AFX

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
Coal Tar Pitch	(CAS-No.) 65996-93-2	0.5 – 1	Muta. 1B, H340 Carc. 1A, H350

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Allow affected person to breathe fresh air. Allow the victim to rest.
- First-aid measures after skin contact : Gently wash with plenty of soap and water.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- First-aid measures after ingestion : Rinse mouth. Get medical advice/attention if you feel unwell. Do not induce vomiting.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after inhalation : May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure through inhalation.
- Symptoms/effects after skin contact : Causes skin irritation.
- Symptoms/effects after eye contact : Causes eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : In case of fire, all extinguishing media allowed.

5.2. Specific hazards arising from the chemical

- Fire hazard : Product will not burn, but does contain small quantities of chemicals which can generate toxic and/or irritating vapors when initially heated. Under fire conditions hazardous combustion products such as carbon monoxide may be generated.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Fight fire with normal precautions from a reasonable distance.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Protective equipment : Safety shoes. Safety glasses. Protective gloves.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.

6.2. Environmental precautions

No additional information available

6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage.
- Methods for cleaning up : Collect spillage. Mechanically recover the product.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Avoid contact with skin and eyes. Do not breathe Dust when sawing or tear out.
- Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store this product in a dry location where it can be protected from the elements.
- Incompatible products : Strong acids. Oxidizing agent.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

MaxLine 10 AFX (Mixture)	
No additional information available	
Magnesium Oxide (1309-48-4)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (mg/m ³)	10 mg/m ³ inhalable dust
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) (mg/m ³)	10 mg/m ³ respirable dust
graphite (7782-42-5)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (mg/m ³)	2 mg/m ³ (Respirable fraction)

MaxLine 10 AFX

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Phenolic Resin (108-95-2)

No additional information available

Coal Tar Pitch (65996-93-2)

USA - ACGIH - Occupational Exposure Limits

ACGIH TWA (mg/m³)

0.2 mg/m³ (Coal tar pitch volatiles, as benzene soluble aerosol; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)

Aluminum - metal powder (7429-90-5)

USA - ACGIH - Occupational Exposure Limits

ACGIH TWA (mg/m³)

1 mg/m³ (Respirable fraction)

8.2. Appropriate engineering controls

Appropriate engineering controls : Dust when sawing or tear out. Provide adequate ventilation to minimize dust concentrations.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Solid in various shapes.
Color	: Black
Odor	: Resin Odor
Odor threshold	: No data available
pH	: No data available
Melting point	: > 2800 °F
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: ≈ 2.9
Solubility	: Insoluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

May release smoke when heated. Combustion products include carbon monoxide, carbon dioxide, and hydrocarbon vapors.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

MaxLine 10 AFX

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Magnesium Oxide (1309-48-4)	
LD50 oral rat	> 5000 mg/kg (Rat, Literature study, Oral)
LD50 dermal rabbit	> 2000 mg/kg body weight (Rabbit, Literature study, Dermal)

graphite (7782-42-5)	
LD50 oral rat	> 2000 mg/kg (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Female, Experimental value, Oral)
LC50 Inhalation - Rat	> 2000 mg/m ³ air (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (dust))

Coal Tar Pitch (65996-93-2)	
LD50 oral rat	> 15000 mg/kg body weight (Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : May cause genetic defects.
Carcinogenicity : May cause cancer.

Phenolic Resin (108-95-2)	
IARC group	3 - Not classifiable

Coal Tar Pitch (65996-93-2)	
IARC group	1 - Carcinogenic to humans

Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified
Viscosity, kinematic : No data available
Symptoms/effects after inhalation : May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure through inhalation.
Symptoms/effects after skin contact : Causes skin irritation.
Symptoms/effects after eye contact : Causes eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

graphite (7782-42-5)	
LC50 fish 1	> 100 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Static system, Fresh water, Experimental value, Lethal)
EC50 Daphnia 1	> 100 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Behaviour)

Coal Tar Pitch (65996-93-2)	
LC50 fish 1	128 mg/l (LL50; OECD 203: Fish, Acute Toxicity Test; 96 h; Pagrus major; Semi-static system; Salt water; Experimental value)
EC50 Daphnia 1	> 100 mg/l (EL50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
LC50 fish 2	100-1000,LL50; OECD 203: Fish, Acute Toxicity Test; 96 h; Oryzias latipes; Semi-static system; Fresh water; Experimental value
Threshold limit algae 1	220 mg/l (EL50; OECD 201: Alga, Growth Inhibition Test; 72 h; Desmodesmus subspicatus; Static system; Fresh water; Experimental value)

12.2. Persistence and degradability

Magnesium Oxide (1309-48-4)	
Persistence and degradability	Not applicable.
Chemical oxygen demand (COD)	Not applicable

MaxLine 10 AFX

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Magnesium Oxide (1309-48-4)	
ThOD	Not applicable
graphite (7782-42-5)	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
Coal Tar Pitch (65996-93-2)	
Persistence and degradability	No test data available. Adsorbs into the soil.
Aluminum - metal powder (7429-90-5)	
Persistence and degradability	Biodegradability in soil: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

12.3. Bioaccumulative potential

Magnesium Oxide (1309-48-4)	
Bioaccumulative potential	No bioaccumulation data available.
graphite (7782-42-5)	
Bioaccumulative potential	No bioaccumulation data available.
Coal Tar Pitch (65996-93-2)	
Bioaccumulative potential	No test data available.
Aluminum - metal powder (7429-90-5)	
Bioaccumulative potential	No test data of component(s) available.

12.4. Mobility in soil

Magnesium Oxide (1309-48-4)	
Ecology - soil	No data available.
Coal Tar Pitch (65996-93-2)	
Partition coefficient n-octanol/water (Log Koc)	Koc,12600-800000; Calculated value; log Koc; 4.1-5.9; Calculated value
Aluminum - metal powder (7429-90-5)	
Ecology - soil	Contains component(s) that adsorb(s) into the soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Do not discharge into the sewer.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated

Transportation of Dangerous Goods

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

MaxLine 10 AFX (Mixture)		
Not listed on the United States TSCA (Toxic Substances Control Act) inventory		
Note	This information must be included in all SDS's that are copied and distributed for this material.	
All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:		
Aluminum - metal powder	CAS-No. 7429-90-5	1 – 5%

MaxLine 10 AFX

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Phenolic Resin (108-95-2)	
Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	1000 lb
RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	10000 lb 500lb if the substance is solid in powder form with particle size less than 100 microns, or is in solution or molten form
Aluminum - metal powder (7429-90-5)	
Note	This information must be included in all SDS's that are copied and distributed for this material.

15.2. International regulations

CANADA

Magnesium Oxide (1309-48-4)	
Listed on the Canadian DSL (Domestic Substances List)	
graphite (7782-42-5)	
Listed on the Canadian DSL (Domestic Substances List)	
Phenolic Resin (108-95-2)	
Listed on the Canadian DSL (Domestic Substances List)	
Coal Tar Pitch (65996-93-2)	
Listed on the Canadian DSL (Domestic Substances List)	

EU-Regulations

No additional information available

National regulations

Coal Tar Pitch (65996-93-2)	
Listed on IARC (International Agency for Research on Cancer)	

15.3. US State regulations

MaxLine 10 AFX (Mixture)	
U.S. - California - Proposition 65 - Other information	This product contains coal-tar pitch, a chemical known to the State of California to cause cancer. For more information go to WWW.P65Warnings.ca.gov
Component	State or local regulations
Magnesium Oxide (1309-48-4)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Graphite (7782-42-5)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Phenolic Resin (108-95-2)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Coal Tar Pitch (65996-93-2)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 11/16/2020

Other information : Report language name. English. In the event of any conflict between English and other language versions, the English version shall prevail.

Full text of H-phrases:

H340	May cause genetic defects
H350	May cause cancer

SDS US (GHS HazCom 2012)

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.