

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date: 09/23/2021 Supersedes: 09/12/2018 Date of issue: 09/23/2021

SECTION 1: Identification

Identification

Product form Mixture Product name Maxline 13A CAS-No. Mixture Product code 7452

Other means of identification Resin Bonded, Magnesia-Carbon Brick

Recommended use and restrictions on use Use of the substance/mixture : Refractory

1.3. **Supplier**

Resco Products, Inc.

One Robinson Plaza, Suite 300

6600 Steubenville Pike

Pittsburgh, PA 15205 - United States

T 412-494-4491

<u>SDS@RescoProducts.com</u> - <u>WWW.RescoProducts.com</u>

Emergency telephone number

Emergency number : EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300

Outside USA & Canada +1 703-741-5970

SECTION 2: Hazard(s) identification

Classification of the substance or mixture

GHS-US classification

Germ cell mutagenicity H340 May cause genetic defects

Category 1B

Carcinogenicity Category H350 May cause cancer

1A

Full text of H statements : see section 16

GHS Label elements, including precautionary statements

GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) H340 - May cause genetic defects

H350 - May cause cancer

Precautionary statements (GHS-US) P202 - Do not handle until all safety precautions have been read and understood.

P280 - Wear Safety shoes, protective clothing, eye protection, protective gloves.

P261 - Sawing or tear out operations- Avoid breathing dust.

2.3. Other hazards which do not result in classification

No additional information available

Unknown acute toxicity (GHS US) 2.4.

SECTION 3: Composition/Information on ingredients

Substances

Not applicable

Mixtures

Name	Product identifier	%	GHS-US classification
Magnesium Oxide	(CAS-No.) 1309-48-4	75 - 95	Not classified
graphite	(CAS-No.) 7782-42-5	5 - 10	Not classified
Phenolic Resin	(CAS-No.) 108-95-2	1 - 5	Not classified
Aluminum - metal powder	(CAS-No.) 7429-90-5	1 - 5	Not classified
Coal Tar Pitch	(CAS-No.) 65996-93-2	1 - 5	Muta. 1B, H340 Carc. 1A, H350 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.4	December	- £ £! 4 !	id measures
4.1.	Description	or tirst a	in measures

First-aid measures general Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.

09/11/2018 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after skin contact : Gently wash with plenty of soap and water.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

First-aid measures after ingestion : Rinse mouth. Get medical advice/attention if you feel unwell. Do not induce vomiting.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure

through inhalation.

Symptoms/effects after skin contact : Causes skin irritation.
Symptoms/effects after eye contact : Causes eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

Reactivity

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : No unsuitable extinguishing media known.

5.2. Specific hazards arising from the chemical

Fire hazard : Product will not burn, but does contain small quantities of chemicals which can generate toxic

and/or irritating vapors when initially heated. Under fire conditions hazardous combustion

products such as carbon monoxide may be generated.

: May release smoke when heated. Combustion products include carbon monoxide, carbon

dioxide, and hydrocarbon vapors.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire with normal precautions from a reasonable distance.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Safety shoes. Safety glasses. Protective gloves.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

6.2. Environmental precautions

No additional information available

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Collect spillage. Mechanically recover the product.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Avoid contact with

skin and eyes. Do not breathe Dust when sawing or tear out.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store this product in a dry location where it can be protected from the elements.

Incompatible products : Strong acids. Oxidizing agent.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Magnesium Oxide (1	1309-48-4)	
ACGIH	ACGIH TWA (mg/m³)	10 mg/m³ (Magnesium oxide; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Inhalable fraction)
graphite (7782-42-5)		
ACGIH	ACGIH TWA (mg/m³)	2 mg/m³ (Graphite (all forms except graphite fibers); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)
Phenolic Resin (108	-95-2)	
Not applicable		
Coal Tar Pitch (6599	06-93-2)	
ACGIH	ACGIH TWA (mg/m³)	0.2 mg/m³ (Coal tar pitch volatiles, as benzene soluble aerosol; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
Aluminum - metal pe	owder (7429-90-5)	
Not applicable		

09/11/2018 EN (English US) 2/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Appropriate engineering controls

No additional information available

Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

: Solid Physical state

Appearance Solid in various shapes.

Black

Color Odor : Resin Odor Odor threshold : No data available

рΗ No data available

: > 2800 °F Melting point

Freezing point : No data available : No data available Boiling point : No data available Flash point Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available Vapor pressure : No data available Relative vapor density at 20 °C : No data available

Relative density : ≈ 2.9

Solubility : Insoluble in water. : No data available Log Pow : No data available Auto-ignition temperature Decomposition temperature : No data available Viscosity, kinematic : No data available Viscosity, dynamic No data available : No data available **Explosion limits** Explosive properties : No data available Oxidizing properties : No data available

Other information 9.2.

No additional information available

SECTION 10: Stability and reactivity

May release smoke when heated. Combustion products include carbon monoxide, carbon dioxide, and hydrocarbon vapors.

10.2. **Chemical stability**

Stable under normal conditions.

Possibility of hazardous reactions

No additional information available

Conditions to avoid

No additional information available

Incompatible materials

No additional information available

Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

Information on toxicological effects

09/11/2018 EN (English US) 3/6

Safety Data Sheet

Persistence and degradability

Biochemical oxygen demand (BOD)

Chemical oxygen demand (COD)

graphite (7782-42-5)
Persistence and degradability

ThOD

ThOD

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3,	,
Acute toxicity	: Not classified
Magnesium Oxide (1309-48-4)	
LD50 oral rat	> 5000 mg/kg (Rat; Literature study)
LD50 dermal rabbit	> 2000 mg/kg body weight (Rabbit; Literature study)
graphite (7782-42-5)	
LD50 oral rat	> 2000 mg/kg (Rat; OECD 423: Acute Oral Toxicity – Acute Toxic Class Method; Experimental
ED30 01al 1at	value)
Coal Tar Pitch (65996-93-2)	
LD50 oral rat	> 15000 mg/kg body weight (Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.
Coal Tar Pitch (65996-93-2)	
IARC group	1 - Carcinogenic to humans
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated	: Not classified
exposure	
Aspiration hazard Symptoms/effects after inhalation	Not classifiedMay cause cancer by inhalation. Danger of serious damage to health by prolonged exposure
Symptoms/effects after inflatation	through inhalation.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes eye irritation.
SECTION 12: Ecological information	
12.1. Toxicity	
Magnesium Oxide (1309-48-4)	
EC50 Daphnia 1	500-665,TLM; 96 h; Mysidacea
graphite (7782-42-5)	
LC50 fish 1	> 100 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Danio rerio; Static system;
	Fresh water; Experimental value)
EC50 Daphnia 1	> 100 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna;
·	Static system; Fresh water; Experimental value)
Threshold limit algae 1	> 100 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella
	subcapitata; Static system; Fresh water; Experimental value)
Threshold limit algae 2	> 100 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella
	subcapitata; Static system; Fresh water; Experimental value)
Coal Tar Pitch (65996-93-2)	
` '	128 mg/l (LL50; OECD 203: Fish, Acute Toxicity Test; 96 h; Pagrus major; Semi-static system;
LC50 fish 1	Salt water; Experimental value)
EC50 Daphnia 1	> 100 mg/l (EL50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
LC50 fish 2	100-1000,LL50; OECD 203: Fish, Acute Toxicity Test; 96 h; Oryzias latipes; Semi-static system; Fresh water; Experimental value
Threshold limit algae 1	220 mg/l (EL50; OECD 201: Alga, Growth Inhibition Test; 72 h; Desmodesmus subspicatus;
This shou in the digue 1	Static system; Fresh water; Experimental value)
12.2. Persistence and degradability	
Magnesium Oxide (1309-48-4)	
waynesium Oxide (1303-40-4)	T

09/11/2018 EN (English US) 4/6

Not applicable (inorganic)

Not applicable

Not applicable

Not applicable

Biodegradability: not applicable.

Biodegradability: not applicable. No (test)data on mobility of the substance available.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

cording to Federal Register / Vol. 77, No. 507 Monaday, Marieri 20, 2012 / Rates and Regulations		
graphite (7782-42-5)		
Coal Tar Pitch (65996-93-2)		
Persistence and degradability	No test data available. Adsorbs into the soil.	
Aluminum - metal powder (7429-90-5)		
Persistence and degradability	Biodegradability in soil: not applicable.	
Biochemical oxygen demand (BOD)	Not applicable	
Chemical oxygen demand (COD)	Not applicable	
ThOD	Not applicable	
BOD (% of ThOD)	Not applicable	
12.3. Bioaccumulative potential		
Magnesium Oxide (1309-48-4)		
Bioaccumulative potential	Bioaccumulation: not applicable.	
graphite (7782-42-5)		

Bioaccumulative potential		
Coal Tar Pitch (65996-93-2)		

Bioaccumulative potential

No test data available.

No bioaccumulation data available.

Aluminum - metal powder (7429-90-5)

Bioaccumulative potential No test data of component(s) available.

12.4. Mobility in soil

Coal Tar Pitch (65996-93-2)	
Log Koc	Koc,12600-800000; Calculated value; log Koc; 4.1-5.9; Calculated value
Aluminum - metal powder (7429-90-5)	
Ecology - soil	Contains component(s) that adsorb(s) into the soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Do not discharge into the sewer.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated

Transportation of Dangerous Goods

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

Maxline 13A (Mixture)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Aluminum - metal powder (7429-90-5)

Subject to reporting requirements of United States SARA Section 313

15.2. International regulations

CANADA

No additional information available

Coal Tar Pitch (65996-93-2)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Coal Tar Pitch (65996-93-2)

Listed on IARC (International Agency for Research on Cancer)

09/11/2018 EN (English US) 5/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

Maxline 13A (Mixture)	
U.S California - Proposition 65 - Other	This product contains coal-tar pitch, a chemical known to the State of California to cause
information	cancer.

Magnesium Oxide (1309-48-4)

U.S. - New Jersey - Right to Know Hazardous Substance List

graphite (7782-42-5)

U.S. - New Jersey - Right to Know Hazardous Substance List

Coal Tar Pitch (65996-93-2)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

Aluminum - metal powder (7429-90-5)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Revision date : 09/23/2021

Other information : Report language

: Report language name. English. In the event of any conflict between English and other

language versions, the English version shall prevail.

Full text of H-phrases:

H340	May cause genetic defects
H350	May cause cancer
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

SDS US (GHS HazCom 2012)

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.

09/11/2018 EN (English US) 6/6