

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product name : Nuline 10-99  
CAS-No. : Mixture  
Product code : 4850  
Other means of identification : Resin Bonded Magnesia-Carbon Brick

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Refractory Brick  
Recommended use : Industrial use

#### 1.3. Supplier

Resco Products, Inc.  
One Robinson Plaza, Suite 300  
6600 Steubenville Pike  
Pittsburgh, PA, 15205  
United States  
412-494-4491  
[SDS@RescoProducts.com](mailto:SDS@RescoProducts.com) - [WWW.RescoProducts.com](http://WWW.RescoProducts.com)

#### 1.4. Emergency telephone number

Emergency number : EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300  
Outside USA & Canada +1 703-741-5970

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2B	H320	Causes eye irritation
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335	May cause respiratory irritation

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning  
Hazard statements (GHS US) : H315 - Causes skin irritation  
H320 - Causes eye irritation  
H335 - May cause respiratory irritation  
Precautionary statements (GHS US) : P280 - Wear eye protection, protective gloves, Safety shoes.

#### 2.3. Other hazards which do not result in classification

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

No additional information available

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Magnesium Oxide	CAS-No.: 1309-48-4	75 – 95	Not classified
graphite	CAS-No.: 7782-42-5	10 – 20	Not classified
Phenolic Resin	CAS-No.: 108-95-2	1 – 5	Not classified
Aluminum - metal powder	CAS-No.: 7429-90-5	1 – 5	Not classified
Si	CAS-No.: 7440-21-3	1 – 5	Not classified

Full text of hazard classes and H-statements : see section 16

# Nuline 10-99

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice.
First-aid measures after inhalation	: Dust when sawing or tear out. Remove the victim into fresh air.
First-aid measures after skin contact	: Gently wash with plenty of soap and water.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Rinse mouth with water. Do not induce vomiting.

#### 4.2. Most important symptoms and effects (acute and delayed)

Most Important Symptoms/Effects	: No additional information available.
---------------------------------	--

#### 4.3. Immediate medical attention and special treatment, if necessary

No additional information available

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: No unsuitable extinguishing media known.

#### 5.2. Specific hazards arising from the chemical

Fire hazard	: Non-flammable. Do not breathe fumes from fires or vapors from decomposition.
-------------	--

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Exercise caution when fighting any chemical fire.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus.
Other information	: Product will not burn, but does contain small quantities of chemicals which can generate toxic and/or irritating vapors when initially heated. Under fire conditions hazardous combustion products such as carbon monoxide may be generated. The phenolic resin binder may undergo incomplete combustion when temperature is applied to this product. The intent of this note is as follows: (1) to apprise the customer/user of the potential for incomplete combustion, and (2) to advise that the chemical compounds produced by incomplete combustion by poor air handling practices may exceed TLV's for specific air contaminants. The specific chemical compounds which may be produced include but are not limited to: carbon monoxide, formaldehyde, phenol, alcohols, glycols, and other solvents.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Protective equipment	: Safety glasses. Protective gloves. Safety shoes.
Emergency procedures	: Avoid contact with skin and eyes.

##### 6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Collect spillage. On land, sweep or shovel into suitable containers.

#### 6.2. Environmental precautions

No additional information available

#### 6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Mechanically recover the product.

#### 6.4. Reference to other sections

No additional information available

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling	: Avoid contact with skin and eyes.
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store this product in a dry location where it can be protected from the elements.
Incompatible products	: Strong acids.
Incompatible materials	: Oxidizing agents and strong acids.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

# Nuline 10-99

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Nuline 10-99 (Mixture)</b>	
No additional information available	
<b>Magnesium Oxide (1309-48-4)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA	10 mg/m <sup>3</sup> inhalable dust
<b>USA - OSHA - Occupational Exposure Limits</b>	
OSHA PEL (TWA) [1]	10 mg/m <sup>3</sup> respirable dust
<b>graphite (7782-42-5)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA	2 mg/m <sup>3</sup> (Respirable fraction)
<b>Phenolic Resin (108-95-2)</b>	
No additional information available	
<b>Aluminum - metal powder (7429-90-5)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA	1 mg/m <sup>3</sup> (Respirable fraction)
<b>Si (7440-21-3)</b>	
No additional information available	
<b>8.2. Appropriate engineering controls</b>	
Appropriate engineering controls : Dust when sawing or tear out. Provide adequate ventilation to minimize dust concentrations.	
<b>8.3. Individual protection measures/Personal protective equipment</b>	
<b>Personal protective equipment:</b>	
Avoid all unnecessary exposure.	
<b>Hand protection:</b>	
Wear protective gloves.	
<b>Eye protection:</b>	
Chemical goggles or safety glasses	
<b>Skin and body protection:</b>	
Safety shoes. Wear suitable protective clothing	
<b>Respiratory protection:</b>	
Dust when sawing or tear out. Wear appropriate mask	
<b>SECTION 9: Physical and chemical properties</b>	
<b>9.1. Information on basic physical and chemical properties</b>	
Physical state	: Solid
Appearance	: Solid in various shapes.
Color	: Black
Odor	: Resin Odor
Odor threshold	: No data available
pH	: No data available
Melting point	: > 2800 °F
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not flammable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: ≈ 2.9
Solubility	: Insoluble in water.

# Nuline 10-99

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

No additional information available

### 10.5. Incompatible materials

Strong acids.

### 10.6. Hazardous decomposition products

The phenolic resin binder may undergo incomplete combustion when temperature is applied to this product. The intent of this note is as follows: (1) to apprise the customer/user of the potential for incomplete combustion, and (2) to advise that the chemical compounds produced by incomplete combustion by poor air handling practices may exceed TLV's for specific air contaminants. The specific chemical compounds which may be produced include but are not limited to: carbon monoxide, formaldehyde, phenol, alcohols, glycols, and other solvents.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

<b>Magnesium Oxide (1309-48-4)</b>	
LD50 oral rat	> 5000 mg/kg (Rat, Literature study, Oral)
LD50 dermal rabbit	> 2000 mg/kg body weight (Rabbit, Literature study, Dermal)
<b>graphite (7782-42-5)</b>	
LD50 oral rat	> 2000 mg/kg (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Female, Experimental value, Oral)
LC50 Inhalation - Rat	> 2000 mg/m <sup>3</sup> air (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (dust))
<b>Si (7440-21-3)</b>	
LD50 oral rat	> 5000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Read-across, Oral, 14 day(s))
LD50 dermal rabbit	> 5000 mg/kg body weight (24 h, Rabbit, Read-across, Dermal, 14 day(s))
Skin corrosion/irritation	: Causes skin irritation.
<b>Magnesium Oxide (1309-48-4)</b>	
pH	11 (10 %)
<b>graphite (7782-42-5)</b>	
pH	7 (1.3 %)
Serious eye damage/irritation	: Causes eye irritation.
<b>Magnesium Oxide (1309-48-4)</b>	
pH	11 (10 %)

# Nuline 10-99

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>graphite (7782-42-5)</b>	
pH	7 (1.3 %)
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
<b>Phenolic Resin (108-95-2)</b>	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
<b>Magnesium Oxide (1309-48-4)</b>	
Viscosity, kinematic	Not applicable (solid)
Most Important Symptoms/Effects	: No additional information available.
<b>SECTION 12: Ecological information</b>	
<b>12.1. Toxicity</b>	
<b>graphite (7782-42-5)</b>	
LC50 - Fish [1]	> 100 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	> 100 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Behaviour)
EC50 72h - Algae [1]	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)
EC50 72h - Algae [2]	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Cell numbers)
<b>Si (7440-21-3)</b>	
LC50 - Fish [1]	100 mg/l (Pisces)
ErC50 algae	250 mg/l (Equivalent or similar to OECD 201, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Weight of evidence)
<b>12.2. Persistence and degradability</b>	
<b>Magnesium Oxide (1309-48-4)</b>	
Persistence and degradability	Not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
<b>graphite (7782-42-5)</b>	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
<b>Aluminum - metal powder (7429-90-5)</b>	
Persistence and degradability	Biodegradability in soil: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

# Nuline 10-99

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Si (7440-21-3)</b>		
Persistence and degradability	Biodegradability: not applicable.	
Chemical oxygen demand (COD)	Not applicable (inorganic)	
ThOD	Not applicable (inorganic)	
<b>12.3. Bioaccumulative potential</b>		
<b>Magnesium Oxide (1309-48-4)</b>		
Bioaccumulative potential	No bioaccumulation data available.	
<b>graphite (7782-42-5)</b>		
Bioaccumulative potential	Not bioaccumulative.	
<b>Aluminum - metal powder (7429-90-5)</b>		
Bioaccumulative potential	No test data of component(s) available.	
<b>Si (7440-21-3)</b>		
Bioaccumulative potential	Not bioaccumulative.	
<b>12.4. Mobility in soil</b>		
<b>Magnesium Oxide (1309-48-4)</b>		
Surface tension	No data available in the literature	
Ecology - soil	No data available.	
<b>Aluminum - metal powder (7429-90-5)</b>		
Ecology - soil	Contains component(s) that adsorb(s) into the soil.	
<b>Si (7440-21-3)</b>		
Ecology - soil	Highly mobile in soil.	
<b>12.5. Other adverse effects</b>		
No additional information available		
<b>SECTION 13: Disposal considerations</b>		
<b>13.1. Disposal methods</b>		
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.		
<b>SECTION 14: Transport information</b>		
In accordance with DOT / TDG / IMDG / IATA <b>Department of Transportation (DOT)</b> In accordance with DOT Not regulated <b>Transportation of Dangerous Goods</b> Not regulated <b>Transport by sea</b> Not regulated <b>Air transport</b> Not regulated		
<b>SECTION 15: Regulatory information</b>		
<b>15.1. US Federal regulations</b>		
<b>Nuline 10-99 (Mixture)</b>		
Note	This information must be included in all SDS's that are copied and distributed for this material.	
All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:		
Aluminum - metal powder	CAS-No. 7429-90-5	1 – 5%

# Nuline 10-99

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Phenolic Resin (108-95-2)</b>	
Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	1000 lb
RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	10000 lb 500lb if the substance is solid in powder form with particle size less than 100 microns, or is in solution or molten form

<b>Aluminum - metal powder (7429-90-5)</b>	
Note	This information must be included in all SDS's that are copied and distributed for this material.

### 15.2. International regulations

#### CANADA

<b>Magnesium Oxide (1309-48-4)</b>	
Listed on the Canadian DSL (Domestic Substances List)	

<b>graphite (7782-42-5)</b>	
Listed on the Canadian DSL (Domestic Substances List)	

<b>Phenolic Resin (108-95-2)</b>	
Listed on the Canadian DSL (Domestic Substances List)	

<b>Si (7440-21-3)</b>	
Listed on the Canadian DSL (Domestic Substances List)	

#### EU-Regulations

No additional information available

#### National regulations

No additional information available

### 15.3. US State regulations

Component	State or local regulations
Magnesium Oxide (1309-48-4)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Graphite (7782-42-5)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Phenolic Resin (108-95-2)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Si (7440-21-3)	U.S. - New Jersey - Right to Know Hazardous Substance List

## SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date

: 6/9/2023

Other information

: Report language name. English. In the event of any conflict between English and other language versions, the English version shall prevail.

<b>Full text of H-phrases</b>	
H315	Causes skin irritation
H320	Causes eye irritation
H335	May cause respiratory irritation

Safety Data Sheet (SDS), USA

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.