

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 3/3/2015 Revision date: 5/17/2024 Supersedes: 2/11/2021

SECTION 1: Identification				
1.1. Identification				
Product form Product name CAS-No. Product code Other means of identification	: Mixture : Paco SD Laying M : Mixture : 0219 : Alumina-Silicate Sp			
1.2. Recommended use and restrictions or		Joolanty		
Use of the substance/mixture Recommended use	: Refractory : Industrial use			
1.3. Supplier				
Resco Products, Inc. One Robinson Plaza, Suite 300 6600 Steubenville Pike Pittsburgh, PA, 15205 United States T 412-494-4491 SDS@RescoProducts.com - WWW.RescoProducts	com			
1.4. Emergency telephone number			Capada 1 800	424 9300
Emergency number		_Y (CHEMTREC) USA		-424-3000
SECTION 2: Hazard(s) identification				
2.1. Classification of the substance or mix	ture			
GHS-US classification Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2B Carcinogenicity, Category 1A Full text of H-statements: see section 16	H3 H3 H3	20 Causes eye		on).
2.2. GHS Label elements, including precau	tionary statements			
GHS US labelling Hazard pictograms (GHS US)				
Signal word (GHS US) Hazard statements (GHS US)	: Danger : H315 - Causes skir H320 - Causes eye H350 - May cause	irritation		
Precautionary statements (GHS US)	 P280 - Wear eye protection, Dust Respirator, protective gloves. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P260 - Do not breathe dust. 			
2.3. Other hazards which do not result in c	lassification			
No additional information available				
2.4. Unknown acute toxicity (GHS US)				
No additional information available SECTION 3: Composition/information	on ingre <u>dients</u>			
3.1. Substances				
Not applicable				
3.2. Mixtures				
Name		Product identifier	%	GHS-US classification
quartz		CAS-No.: 14808-60-7	20 - 50	Carc. 1A, H350
sodium metasilicate		CAS-No.: 6834-92-0	1 – 5	Skin Corr. 1A, H314 STOT SE 3, H335
Full text of hazard classes and H-statements : see s	section 16	1	1	10101000, 1000

Safety Data Sheet

SECTION 4: First-aid measures	
4.1. Description of first aid measures	
First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Gently wash with plenty of soap and water.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present
First-aid measures after ingestion	and easy to do. Continue rinsing. : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.
4.2. Most important symptoms and effects	
Potential adverse human health effects and	: May cause cancer by inhalation. Harmful: danger of serious damage to health by prolonged
symptoms	exposure through inhalation.
Symptoms/effects after inhalation	: May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure
Symptoms/effects after skin contact	through inhalation. : Causes skin irritation.
Symptoms/effects after eye contact	: Causes eye irritation.
4.3. Immediate medical attention and speci	al treatment, if necessary
No additional information available	
SECTION 5: Fire-fighting measures	
5.1. Suitable (and unsuitable) extinguishing	g media
Suitable extinguishing media Unsuitable extinguishing media	: Use extinguishing media appropriate for surrounding fire. : In case of fire, all extinguishing media allowed.
5.2. Specific hazards arising from the chem	nical
Fire hazard	: Not flammable.
5.3. Special protective equipment and prec	autions for fire-fighters
Firefighting instructions Protection during firefighting	: Fight fire with normal precautions from a reasonable distance. : Do not enter fire area without proper protective equipment, including respiratory protection.
SECTION 6: Accidental release measur	res
6.1. Personal precautions, protective equip	ment and emergency procedures
6.1.1. For non-emergency personnel	
Emergency procedures	: Do not breathe dust. Avoid contact with skin and eyes.
6.1.2. For emergency responders Protective equipment	- Equip cleanup grow with proper protection
Emergency procedures	 Equip cleanup crew with proper protection. Ventilate area. On land, sweep or shovel into suitable containers.
6.2. Environmental precautions	
Prevent entry to sewers and public waters.	
6.3. Methods and material for containment	and cleaning up
Methods for cleaning up	: On land, sweep or shovel into suitable containers. Minimise generation of dust.
6.4. Reference to other sections	
See Section 8. Exposure controls and personal prote	ection.
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Avoid raising dust.
Hygiene measures	 Avoid contact with skin and eyes. Do not breathe dust. Wash Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work thoroughly after handling.
7.2. Conditions for safe storage, including	
Storage conditions	: Store this product in a dry location where it can be protected from the elements.
SECTION 8: Exposure controls/person	
8.1. Control parameters	
Paco SD Laying Mix (Mixture)	
No additional information available	
sodium metasilicate (6834-92-0)	
No additional information available	

Safety Data Sheet

quartz (14808-60-7)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	0.025 mg/m ³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)
USA - OSHA - Occupational Exposure Limits	
Local name	Silica, crystalline quartz, respirable dust
OSHA PEL TWA [1]	0.05 mg/m ³ respirable dust
Remark (OSHA)	(3) See Table Z-3.
8.2. Appropriate engineering controls	
	: Provide adequate ventilation to minimize dust concentrations.
8.3. Individual protection measures/Persona	I protective equipment
Personal protective equipment: Avoid all unnecessary exposure.	
Hand protection:	
Wear protective gloves.	
Eye protection:	
Chemical goggles or safety glasses	
Skin and body protection:	
Wear suitable protective clothing	
Respiratory protection:	
Wear appropriate mask	
Other information: Do not eat, drink or smoke during use.	
SECTION 9: Physical and chemical prop	perties
9.1. Information on basic physical and chem	ical properties
Physical state	: Solid
Appearance	: Granular mixture.
Colour	: brown
Odour	: earthy
Odour threshold	: No data available
pH Molting point	: No data available
Melting point	: > 2000 °F
Freezing point Boiling point	: No data available : No data available
Flash point	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Not flammable.
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Solubility	: Slightly soluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature Decomposition temperature	: No data available
Viscosity, kinematic	: No data available : Not Applicable
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
9.2. Other information	
No additional information available	
SECTION 10: Stability and reactivity	
10.1. Reactivity	
None known.	
10.2. Chemical stability	
Stable under normal conditions of use.	

Safety Data Sheet

10.3. Possibility of hazardous reactions	
Not established.	
10.4. Conditions to avoid	
Avoid dust formation.	
10.5. Incompatible materials	
No additional information available	
10.6. Hazardous decomposition products	
No additional information available	
SECTION 11: Toxicological informatio	'n
11.1. Information on toxicological effects	
Acute toxicity (oral)	: Not classified
Acute toxicity (dermal) Acute toxicity (inhalation)	: Not classified : Not classified
sodium metasilicate (6834-92-0)	
LD50 oral rat	1152 – 1349 mg/kg bodyweight (Rat, Male / female, Experimental value, 10 % aqueous solution, Oral, 7 day(s))
LD50 dermal rat	> 5000 mg/kg bodyweight (EPA OPPTS 870.1200: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Aqueous solution, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 2.06 mg/l (EPA OPPTS 870.1300: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Aqueous solution, Inhalation (vapours), 14 day(s))
Skin corrosion/irritation	: Causes skin irritation.
sodium metasilicate (6834-92-0)	
PH	No data available in the literature
•	
quartz (14808-60-7)	
рН	6 - 7
Serious eye damage/irritation	: Causes eye irritation.
sodium metasilicate (6834-92-0)	
рН	No data available in the literature
quartz (14808-60-7)	
рН	6 - 7
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer (Inhalation).
quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans
Reproductive toxicity STOT-single exposure	Not classified
sodium metasilicate (6834-92-0)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: Not Applicable
sodium metasilicate (6834-92-0)	
Viscosity, kinematic	Not applicable (solid)
Likely routes of exposure	: Inhalation.
Potential adverse human health effects and symptoms	: May cause cancer by inhalation. Harmful: danger of serious damage to health by prolonged exposure through inhalation.
Symptoms Symptoms/effects after inhalation	: May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure
	through inhalation.
Symptoms/effects after skin contact	: Causes skin irritation.

Safety Data Sheet

Symptoms/effects after eye contact :	Causes eye irritation.
SECTION 12: Ecological information	
12.1. Toxicity	
sodium metasilicate (6834-92-0)	
LC50 - Fish [1]	210 mg/l (ISO 7346-1, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value)
EC50 - Crustacea [1]	1700 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
12.2. Persistence and degradability	
Paco SD Laying Mix (Mixture)	
Persistence and degradability	Not established.
sodium metasilicate (6834-92-0)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
quartz (14808-60-7)	
Persistence and degradability	Not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
12.3. Bioaccumulative potential	
Paco SD Laying Mix (Mixture)	
Bioaccumulative potential	Not established.
sodium metasilicate (6834-92-0)	
Bioaccumulative potential	Not bioaccumulative.
quartz (14808-60-7)	
Bioaccumulative potential	No data available.
12.4. Mobility in soil	
sodium metasilicate (6834-92-0)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for adsorption in soil.
12.5. Other adverse effects	
Effect on global warming : Other information :	None known
SECTION 13: Disposal considerations	No other effects known.
13.1. Disposal methods	
	Dispose in a safe manner in accordance with local/national regulations.
SECTION 14: Transport information	
In accordance with DOT / TDG / IMDG / IATA Department of Transportation (DOT) In accordance with DOT Not regulated Transportation of Dangerous Goods Not regulated Transport by sea Not regulated	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Air transport Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

CANADA

sodium metasilicate (6834-92-0)

Listed on the Canadian DSL (Domestic Substances List) **EU-Regulations** No additional information available

National regulations

quartz (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

Paco SD Laying Mix (Mixture)

U.S. - California - Proposition 65 - Other information This product contains crystalline silica, a chemical known to the state of California to cause cancer. For more information go to WWW.P65Warnings.ca.gov

quartz (14808-60-7)					
U.S California -	U.S California -	U.S California -			Maximum allowable
Proposition 65 - Carcinogens List	Proposition 65 - Developmental Toxicity	Proposition 65 - Reproductive Toxicity	Proposition 65 - Reproductive Toxicity	level (NSRL)	dose level (MADL)
Carolinogene List	Developmental roxioty	- Female	- Male		
Yes	No	No	No		

Component	State or local regulations	
Quartz (14808-60-7)	U.S New Jersey - Right to Know Hazardous Substance List	
SECTION 16: Other information	tion	
according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations		
Revision date	: 5/17/2024	

Other information

- 5/17/2024
- : Report language name. English. In the event of any conflict between the English and other language versions, the English version shall prevail.

Full text of H-statements	
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H320	Causes eye irritation
H335	May cause respiratory irritation.
H350	May cause cancer.

Safety Data Sheet (SDS), USA

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.