

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 5/1/2015 Revision date: 5/20/2024 Supersedes: 3/2/2021

SECTION 1: Identification		
1.1. Identification		
Product form Product name CAS-No. Product code	: Mixture : PermaCast FG-HS : Mixture : 1018 : Basic Speciality	
1.2. Recommended use and restrictions on u		
Use of the substance/mixture	: Refractory	
Recommended use	: Industrial use	
1.3. Supplier		
Resco Products, Inc. One Robinson Plaza, Suite 300 6600 Steubenville Pike Pittsburgh, PA, 15205 United States T 412-494-4491 SDS@RescoProducts.com - WWW.RescoProducts.com	om	
1.4. Emergency telephone number		
Emergency number	: EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300 Outside USA & Canada +1 703-741-5970	
SECTION 2: Hazard(s) identification		
2.1. Classification of the substance or mixtu	re	
GHS US classification		
Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2B Specific target organ toxicity – Single exposure, Categore Respiratory tract irritation Full text of H statements : see section 16	H315 Causes skin irritation H320 Causes eye irritation gory 3, H335 May cause respiratory irritation	
2.2. GHS Label elements, including precaution	onary statements	
GHS US labeling Hazard pictograms (GHS US)		
Signal word (GHS US) Hazard statements (GHS US)	: Warning : H315 - Causes skin irritation H320 - Causes eye irritation H335 - May cause respiratory irritation	
Precautionary statements (GHS US)	: P280 - Wear protective gloves/protective clothing/eye protection/face protection.	
2.3. Other hazards which do not result in cla	ssification	
No additional information available		
2.4. Unknown acute toxicity (GHS US)		
No additional information available		
SECTION 3: Composition/Information or	n ingredients	
3.1. Substances		
Not applicable		
3.2. Mixtures		
Name	Product identifier % GHS US classificat	ion
Magnesium Oxide	CAS-No.: 1309-48-4 50 – 75 Not classified	
chromium(III) oxide	CAS-No.: 1308-38-9 10 – 20 Not classified	
iron(III) oxide aluminium oxide, non-fibrous	CAS-No.: 1309-37-1 10 – 20 Not classified CAS-No.: 1344-28-1 10 – 20 Not classified	
Full text of hazard classes and H-statements : see see	tion 16	
SECTION 4: First-aid measures		
4.1. Description of first aid measures	Allow offerted person to breath free brit	
First-aid measures after inhalation	: Allow affected person to breathe fresh air.	

Safety Data Sheet

o o <i>i i</i>	
	 Gently wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Do NOT induce vomiting. Get medical advice/attention if you feel unwell.
4.2. Most important symptoms and effects (acute and delayed)
	: May cause respiratory irritation.
4.3. Immediate medical attention and specia	
No additional information available	
SECTION 5: Fire-fighting measures	
5.1. Suitable (and unsuitable) extinguishing	media
Suitable extinguishing media	 Use extinguishing media appropriate for surrounding fire. In case of fire, all extinguishing media allowed.
5.2. Specific hazards arising from the chemi	ical
Fire hazard	: Not flammable.
5.3. Special protective equipment and preca	utions for fire-fighters
	: Fight fire with normal precautions from a reasonable distance.
	: Do not enter fire area without proper protective equipment, including respiratory protection.
SECTION 6: Accidental release measure	
6.1. Personal precautions, protective equipr	nent and emergency procedures
6.1.1. For non-emergency personnel	. In case of incident statementilation, wear requirements restartion. Protective states. Or fate states
Protective equipment Emergency procedures	 [In case of inadequate ventilation] wear respiratory protection. Protective gloves. Safety glasses. Avoid contact with skin. Avoid contact with eyes.
6.1.2. For emergency responders	. Avoid contact with skin. Avoid contact with eyes.
Protective equipment	: Do not attempt to take action without suitable protective equipment.
6.2. Environmental precautions	
Do not discharge into drains.	
6.3. Methods and material for containment a	nd cleaning up
	: Collect spillage.
Methods for cleaning up	: On land, sweep or shovel into suitable containers.
6.4. Reference to other sections	
No additional information available	
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Hygiene measures	: Do not eat, drink or smoke when using this product. Wash skin thoroughly with mild soap and water.
7.2. Conditions for safe storage, including a	ny incompatibilities
Storage conditions	: Store this product in a dry location where it can be protected from the elements.
Incompatible products	: Strong acids.
SECTION 8: Exposure controls/persona	I protection
8.1. Control parameters	
PermaCast FG-HS (Mixture)	
No additional information available	
Magnesium Oxide (1309-48-4)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	10 mg/m ³ inhalable dust
USA - OSHA - Occupational Exposure Limits OSHA PEL (TWA) [1]	10 mg/m ³ respirable dust
chromium(III) oxide (1308-38-9)	
No additional information available	
iron(III) oxide (1309-37-1)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	5 mg/m ³ (Respirable fraction)
aluminium oxide, non-fibrous (1344-28-1)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	1 mg/m ³ respirable dust
·	

Safety Data Sheet

	according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations	
8.2. Appropriate engineering controls		
Appropriate engineering controls	: Provide adequate ventilation to minimize dust concentrations.	
8.3. Individual protection measures/Person	nal protective equipment	
Hand protection:		
Wear protective gloves.		
Eye protection:		
Chemical goggles or safety glasses		
Skin and body protection:		
Wear suitable protective clothing		
Respiratory protection:		
In case of inadequate ventilation wear respiratory p	protection.	
SECTION 9: Physical and chemical pro	operties	
9.1. Information on basic physical and che	mical properties	
Physical state Appearance Color Odor Odor threshold pH Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Uiscosity, kinematic Viscosity, dynamic Explosion limits Explosive properties Oxidizing properties 9.2. Other information	 Solid Granular powder. Green Gray odorless No data available No data available > 2000 °F No data available 	
No additional information available		
SECTION 10: Stability and reactivity		
10.1. Reactivity	walent chromium and other ovidation products	
Fire conditions may produce small amounts of hexavalent chromium and other oxidation products. 10.2. Chemical stability		
No additional information available		
10.3. Possibility of hazardous reactions		
No additional information available		
10.4. Conditions to avoid		
No additional information available		
10.5. Incompatible materials		
No additional information available		
10.6. Hazardous decomposition products		
No additional information available		

Safety Data Sheet

SECTION 11: Toxicological information		
11.1. Information on toxicological effects		
Acute toxicity (oral)	Not classified	
	Not classified Not classified	
Magnesium Oxide (1309-48-4)		
LD50 oral rat	> 5000 mg/kg (Rat, Literature study, Oral)	
LD50 dermal rabbit	> 2000 mg/kg body weight (Rabbit, Literature study, Dermal)	
chromium(III) oxide (1308-38-9)		
LD50 oral rat	> 5000 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))	
LC50 Inhalation - Rat	> 5.41 mg/l air (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))	
iron(III) oxide (1309-37-1)		
LD50 oral rat	> 10000 mg/kg body weight (Rat, Male, Experimental value, Oral)	
LC50 Inhalation - Rat	5.05 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))	
aluminium oxide, non-fibrous (1344-28-1)		
LD50 oral rat	> 15900 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))	
LC50 Inhalation - Rat	> 2.3 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))	
Skin corrosion/irritation :	Causes skin irritation.	
Magnesium Oxide (1309-48-4)		
рН	11 (10 %)	
chromium(III) oxide (1308-38-9)		
рН	No data available in the literature	
iron(III) oxide (1309-37-1)		
рН	7 (5 %)	
aluminium oxide, non-fibrous (1344-28-1)		
рН	9 – 10.5 (aqueous suspension, 33 %)	
Serious eye damage/irritation :	Causes eye irritation.	
Magnesium Oxide (1309-48-4)		
рН	11 (10 %)	
chromium(III) oxide (1308-38-9)		
рН	No data available in the literature	
iron(III) oxide (1309-37-1)		
рН	7 (5 %)	
aluminium oxide, non-fibrous (1344-28-1)		
рН	9 – 10.5 (aqueous suspension, 33 %)	
Germ cell mutagenicity:Carcinogenicity:Reproductive toxicity:	Not classified Not classified Not classified Not classified	
STOT-single exposure :	May cause respiratory irritation.	

Safety Data Sheet

STOT-repeated exposure Aspiration hazard Viscosity, kinematic	 Not classified Not classified No data available
Magnesium Oxide (1309-48-4)	
Viscosity, kinematic	Not applicable (solid)
chromium(III) oxide (1308-38-9)	
Viscosity, kinematic	Not applicable (solid)
iron(III) oxide (1309-37-1)	
Viscosity, kinematic	Not applicable (solid)
aluminium oxide, non-fibrous (1344-28-	1)
Viscosity, kinematic	Not applicable (solid)
Symptoms/effects after inhalation	: May cause respiratory irritation.
SECTION 12: Ecological information	n
12.1. Toxicity	
chromium(III) oxide (1308-38-9)	
LC50 - Fish [1]	> 10000 mg/l (ISO 7346-1, 96 h, Danio rerio, Static system, Fresh water, Experimental value, GLP)
iron(III) oxide (1309-37-1)	
EC50 - Crustacea [1]	> 100 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
aluminium oxide, non-fibrous (1344-28-	1)
LC50 - Fish [1]	> 100 mg/l (96 h, Salmo trutta, Literature study)
EC50 - Crustacea [1]	> 100 mg/l (48 h, Daphnia magna, Literature study)
12.2. Persistence and degradability	
Magnesium Oxide (1309-48-4)	
Persistence and degradability	Not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
chromium(III) oxide (1308-38-9)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
iron(III) oxide (1309-37-1)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
aluminium oxide, non-fibrous (1344-28-	1)
Persistence and degradability	Not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

Safety Data Sheet

Bioaccumulative potential Not bioaccumulative. aluminium oxide, non-fibrous (1344-28-1)		
ted for this material.		
ted for ances		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

chromium(III) o	xide (1308-38-9)	
	g requirements of United	States SARA Section 313
aluminium oxid	le, non-fibrous (1344-	28-1)
		United States SARA Section 313
Note		Note: The section 313 chemical list contains "CAS # 1344-28-1 Aluminum Oxide (Fibrous forms)"; the Aluminum oxide contained in this product is non-fibrous, and thus is not a section 313 material. Only manufacturing, processing, or otherwise use of aluminum oxide in the fibrous form triggers reporting.
15.2. Internation	nal regulations	
CANADA Magnesium Ox	ide (1309-48-4)	
	adian DSL (Domestic Sub	stances List)
chromium(III) o	xide (1308-38-9)	
Listed on the Cana	adian DSL (Domestic Sub	stances List)
iron(III) oxide (1	1309-37-1)	
Listed on the Cana	adian DSL (Domestic Sub	stances List)
aluminium oxid	le, non-fibrous (1344-	28-1)
	adian DSL (Domestic Sub	
EU-Regulations No additional inform National regulatio No additional inform	ns	
15.3. US State r	egulations	
PermaCast FG-	HS (Mixture)	
U.S California - information	Proposition 65 - Other	This product contains chromite (Cr*+3) which may in normal use, be converted chemically to a chromate (Cr*+6) hexavalent chrome, a chemical known to the State of California to cause cancer.
Component		State or local regulations
Magnesium Oxide	(1309-48-4)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
chromium(III) oxid	e (1308-38-9)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List
iron(III) oxide (130	9-37-1)	U.S New Jersey - Right to Know Hazardous Substance List
aluminium oxide, non-fibrous (1344-28-1)		U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
SECTION 16:	Other information	
according to Federa	al Register / Vol. 77, No. 5	8 / Monday, March 26, 2012 / Rules and Regulations
Revision date		: 5/20/2024
Other information		: Report language name. English. In the event of any conflict between English and other language versions, the English version shall prevail.
Full text of H-phr	ases	
H315	Causes skin irritation	
H320	Causes eve irritation	

H320Causes eye irritationH335May cause respiratory irritation

Safety Data Sheet (SDS), USA

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.