



PermaCast FG Ram Cast

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 03/02/2021

Revision date: 03/02/2021

Supersedes: 01/30/2019

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : PermaCast FG Ram Cast
CAS-No. : Mixture
Product code : 1021
Other means of identification : Basic Speciality

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Refractory
Recommended use : Industrial use

1.3. Supplier

Resco Products, Inc.
One Robinson Plaza, Suite 300
6600 Steubenville Pike
Pittsburgh, PA 15205 - United States
412-494-4491

SDS@RescoProducts.com - WWW.RescoProducts.com

1.4. Emergency telephone number

Emergency number : EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300
Outside USA & Canada +1 703-741-5970

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation Category 2 H315 Causes skin irritation
Serious eye damage/eye irritation Category 2B H320 Causes eye irritation
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation H335 May cause respiratory irritation

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning
Hazard statements (GHS US) : H315 - Causes skin irritation
H320 - Causes eye irritation
H335 - May cause respiratory irritation

Precautionary statements (GHS US) : P280 - Wear protective gloves/protective clothing/eye protection/face protection.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Magnesium Oxide	(CAS-No.) 1309-48-4	50 – 75	Not classified
chromium(III) oxide	(CAS-No.) 1308-38-9	20 – 50	Not classified
iron(III) oxide	(CAS-No.) 1309-37-1	10 – 20	Not classified
aluminium oxide, non-fibrous	(CAS-No.) 1344-28-1	5 – 10	Not classified

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Allow affected person to breathe fresh air.
First-aid measures after skin contact : Gently wash with plenty of soap and water.
First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion : Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause respiratory irritation.

PermaCast FG Ram Cast

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media : In case of fire, all extinguishing media allowed.

5.2. Specific hazards arising from the chemical

- Fire hazard : Non-flammable.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Fight fire with normal precautions from a reasonable distance.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Protective equipment : Wear respiratory protection. Protective gloves. Safety glasses.
Emergency procedures : Avoid contact with skin. Avoid contact with eyes.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment.

6.2. Environmental precautions

No additional information available

6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage.
Methods for cleaning up : On land, sweep or shovel into suitable containers.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Hygiene measures : Do not eat, drink or smoke when using this product. Wash skin thoroughly with mild soap and water.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store this product in a dry location where it can be protected from the elements.
Incompatible products : Strong acids.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

PermaCast FG Ram Cast (Mixture)

No additional information available

Magnesium Oxide (1309-48-4)

USA - ACGIH - Occupational Exposure Limits

ACGIH TWA (mg/m³) : 10 mg/m³ inhalable dust

USA - OSHA - Occupational Exposure Limits

OSHA PEL (TWA) (mg/m³) : 10 mg/m³ respirable dust

chromium(III) oxide (1308-38-9)

USA - ACGIH - Occupational Exposure Limits

ACGIH TWA (mg/m³) : 0.003 mg/m³ (Inhalable fraction)

iron(III) oxide (1309-37-1)

USA - ACGIH - Occupational Exposure Limits

ACGIH TWA (mg/m³) : 5 mg/m³ (Respirable fraction)

aluminium oxide, non-fibrous (1344-28-1)

USA - ACGIH - Occupational Exposure Limits

ACGIH TWA (mg/m³) : 1 mg/m³ respirable dust

8.2. Appropriate engineering controls

- Appropriate engineering controls : Provide adequate ventilation to minimize dust concentrations.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

PermaCast FG Ram Cast

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Granular powder.
Color	: dark gray dark green
Odor	: odorless
Odor threshold	: No data available
pH	: No data available
Melting point	: > 2000 °F
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: Slightly soluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Fire conditions may produce small amounts of hexavalent chromium and other oxidation products.

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Magnesium Oxide (1309-48-4)	
LD50 oral rat	> 5000 mg/kg (Rat, Literature study, Oral)
LD50 dermal rabbit	> 2000 mg/kg body weight (Rabbit, Literature study, Dermal)
chromium(III) oxide (1308-38-9)	
LD50 oral rat	> 15000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male, Experimental value, Oral)
LC50 Inhalation - Rat	> 5.41 mg/l air (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol))
iron(III) oxide (1309-37-1)	
LD50 oral rat	> 10000 mg/kg body weight (Rat, Male, Experimental value, Oral)

PermaCast FG Ram Cast

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

aluminium oxide, non-fibrous (1344-28-1)	
LD50 oral rat	> 15900 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)
LC50 Inhalation - Rat	7.6 mg/l air (Equivalent or similar to OECD 403, 1 h, Rat, Male, Experimental value, Inhalation (aerosol))

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after inhalation	: May cause respiratory irritation.

SECTION 12: Ecological information

12.1. Toxicity

chromium(III) oxide (1308-38-9)	
LC50 fish 1	> 2.9 µg/l (ISO 7346-1, 96 h, Danio rerio, Static system, Fresh water, Experimental value, GLP)

iron(III) oxide (1309-37-1)	
EC50 Daphnia 1	> 100 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)

12.2. Persistence and degradability

Magnesium Oxide (1309-48-4)	
Persistence and degradability	Not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

chromium(III) oxide (1308-38-9)	
Persistence and degradability	Biodegradability in soil: not applicable. Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

iron(III) oxide (1309-37-1)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

aluminium oxide, non-fibrous (1344-28-1)	
Persistence and degradability	Not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

12.3. Bioaccumulative potential

Magnesium Oxide (1309-48-4)	
Bioaccumulative potential	No bioaccumulation data available.

chromium(III) oxide (1308-38-9)	
BCF fish 1	260 – 800 (Lepomis macrochirus, Fresh water, Read-across, Fresh weight)
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).

iron(III) oxide (1309-37-1)	
Bioaccumulative potential	No bioaccumulation data available.

aluminium oxide, non-fibrous (1344-28-1)	
Bioaccumulative potential	No data available.

12.4. Mobility in soil

PermaCast FG Ram Cast

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Magnesium Oxide (1309-48-4)	
Ecology - soil	No data available.
chromium(III) oxide (1308-38-9)	
Surface tension	Not applicable (solid)
Ecology - soil	Adsorbs into the soil.
iron(III) oxide (1309-37-1)	
Surface tension	Not applicable (solid)
Ecology - soil	Adsorbs into the soil.
aluminium oxide, non-fibrous (1344-28-1)	
Ecology - soil	No data available.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

No additional information available

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated

Transportation of Dangerous Goods

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

PermaCast FG Ram Cast (Mixture)

Note This information must be included in all SDS's that are copied and distributed for this material.

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

chromium(III) oxide (1308-38-9)

Subject to reporting requirements of United States SARA Section 313

aluminium oxide, non-fibrous (1344-28-1)

Not subject to reporting requirements of the United States SARA Section 313

Note Note: The section 313 chemical list contains "CAS # 1344-28-1 Aluminum Oxide (Fibrous forms)"; the Aluminum oxide contained in this product is non-fibrous, and thus is not a section 313 material. Only manufacturing, processing, or otherwise use of aluminum oxide in the fibrous form triggers reporting.

15.2. International regulations

CANADA

Magnesium Oxide (1309-48-4)

Listed on the Canadian DSL (Domestic Substances List)

chromium(III) oxide (1308-38-9)

Listed on the Canadian DSL (Domestic Substances List)

iron(III) oxide (1309-37-1)

Listed on the Canadian DSL (Domestic Substances List)

aluminium oxide, non-fibrous (1344-28-1)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

PermaCast FG Ram Cast (Mixture)

U.S. - California - Proposition 65 - Other information

This product contains chromite (Cr⁺³) which may in normal use, be converted chemically to a chromate (Cr⁺⁶) hexavalent chrome, a chemical known to the State of California to cause cancer.

PermaCast FG Ram Cast

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component	State or local regulations
Magnesium Oxide (1309-48-4)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
chromium(III) oxide (1308-38-9)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List
aluminium oxide, non-fibrous (1344-28-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
iron(III) oxide (1309-37-1)	U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date

: 03/02/2021

Other information

: Report language name. English. In the event of any conflict between English and other language versions, the English version shall prevail.

Full text of H-phrases:

H315	Causes skin irritation
H320	Causes eye irritation
H335	May cause respiratory irritation

SDS US (GHS HazCom 2012)

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.