

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date: 04/13/2021 Supersedes: 08/13/2020 Issue date: 04/13/2021

SECTION 1: Identification

Identification

Product form Mixture Product name ProGun 28 LI CAS-No. Mixture Product code 1044

Other means of identification Alumina-Silicate Cement Bonded Castable

Recommended use and restrictions on use 1.2.

Use of the substance/mixture : Refractory Recommended use : Industrial use

Supplier

Resco Products. Inc.

One Robinson Plaza, Suite 300

6600 Steubenville Pike

Pittsburgh, PA 15205 - United States

412-494-4491

SDS@RescoProducts.com - WWW.RescoProducts.com

Emergency telephone number

: EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300 **Emergency number**

Outside USA & Canada +1 703-741-5970

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation Category 2 H315 Causes skin irritation Serious eye damage/eye irritation Category 2B H320 Causes eye irritation

Carcinogenicity Category 1A H350 May cause cancer (Inhalation)

Full text of H statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)





Signal word (GHS US) : Danger

Hazard statements (GHS US) H315 - Causes skin irritation H320 - Causes eye irritation H350 - May cause cancer (Inhalation)

: P280 - Wear eye protection, Dust respirator, protective gloves. Precautionary statements (GHS US)

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P332+P313 - If skin irritation occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P260 - Do not breathe dust.

Other hazards which do not result in classification

No additional information available

Unknown acute toxicity (GHS US) 2.4.

Not applicable

SECTION 3: Composition/Information on ingredients

Not applicable

Mixtures

Name	Product identifier	%	GHS US classification
Calcium Aluminate Cement	(CAS-No.) 65997-16-2	20 – 50	Skin Irrit. 2, H315 Eye Irrit. 2B, H320
cristobalite	(CAS-No.) 14464-46-1	10 – 20	Carc. 1A, H350
quartz	(CAS-No.) 14808-60-7	0.5 – 1	Carc. 1A, H350

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. I	Descriptio	n of first	aid measur	es
--------	------------	------------	------------	----

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation Allow affected person to breathe fresh air. Allow the victim to rest. First-aid measures after skin contact

: Wash with plenty of soap and water. Wash contaminated clothing before reuse.

04/13/2021 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

Symptoms/effects after inhalation : May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure

through inhalation.
Causes skin irritation.

Symptoms/effects after skin contact : Causes skin irritation.
Symptoms/effects after eye contact : Causes eye irritation.

Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : In case of fire, all extinguishing media allowed.

5.2. Specific hazards arising from the chemical

Fire hazard : Not flammable.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering

environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Do not breathe dust.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : On land, sweep or shovel into suitable containers. Minimize generation of dust.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Avoid raising dust.

Avoid contact with skin and eyes. Do not breathe dust.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store this product in a dry location where it can be protected from the elements.

Incompatible products : Strong bases. Strong acids.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ProGun 28 LI (Mixture)			
No additional information available			
Calcium Aluminate Cement (65997-16-2)			
No additional information available			
cristobalite (14464-46-1)			
USA - ACGIH - Occupational Exposure Limits			
ACGIH TWA (mg/m³)	0.025 mg/m³ respirable dust		
USA - OSHA - Occupational Exposure Limits			
OSHA PEL (TWA) (mg/m³)	0.05 mg/m³ respirable dust		
quartz (14808-60-7)			
USA - ACGIH - Occupational Exposure Limits			
ACGIH TWA (mg/m³)	0.025 mg/m³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)		
USA - OSHA - Occupational Exposure Limits			
Local name	Silica, crystalline quartz, respirable dust		
OSHA PEL (TWA) (mg/m³)	0.05 mg/m³ respirable dust		
Remark (OSHA)	(3) See Table Z-3.		

04/13/2021 EN (English US) 2/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide adequate ventilation to minimize dust concentrations.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid

Appearance : Granular mixture.
Color : Light gray
Odor : earthy

Odor threshold : Not applicable pH : No data available

: > 2000 °F Melting point Freezing point : Not applicable : Not applicable Boiling point Critical temperature Not applicable Critical pressure Not applicable Not applicable Flash point Relative evaporation rate (butyl acetate=1) : Not applicable Not applicable Relative evaporation rate (ether=1) Flammability (solid, gas) Non flammable.

Vapor pressure Not Applicable Not Applicable Vapor pressure at 50 °C No data available Relative vapor density at 20 °C Relative density : No data available Solubility Slightly soluble. Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : Not applicable Decomposition temperature : No data available No data available Viscosity, kinematic Viscosity, dynamic Not Applicable

Explosion limits : Not applicable
Explosive properties : No data available
Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Hydraulic setting.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Avoid dust formation.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

No additional information available

04/13/2021 EN (English US) 3/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations				
SECTION 11: Toxicological information				
11.1. Information on toxicological effects				
Acute toxicity (oral)	Not classified			
Acute toxicity (dermal)	: Not classified : Not classified			
Acute toxicity (inhalation) Skin corrosion/irritation	: Not classified : Causes skin irritation.			
Serious eye damage/irritation	: Causes eye irritation.			
Respiratory or skin sensitization	Not classified			
Germ cell mutagenicity	Not classified			
Carcinogenicity	: May cause cancer (Inhalation).			
quartz (14808-60-7)				
IARC group	1 - Carcinogenic to humans			
Reproductive toxicity	Not classified			
STOT-single exposure STOT-repeated exposure	: Not classified : Not classified			
Aspiration hazard	: Not classified			
Viscosity, kinematic	: No data available			
Potential Adverse human health effects and	: Based on available data, the classification criteria are not met.			
symptoms				
Symptoms/effects after inhalation	: May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure			
Symptoms/effects after skin contact	through inhalation. : Causes skin irritation.			
Symptoms/effects after eye contact	: Causes eye irritation.			
SECTION 12: Ecological information				
12.1. Toxicity No additional information available				
12.2. Persistence and degradability				
ProGun 28 LI (Mixture)				
Persistence and degradability	Not established.			
1 crosserioe and degradability	Trot established.			
cristobalite (14464-46-1)				
Persistence and degradability	Mineral. Not applicable.			
Chemical oxygen demand (COD)	Not applicable			
ThOD	Not applicable			
BOD (% of ThOD)	Not applicable			
quartz (14808-60-7)				
Persistence and degradability	Not applicable.			
<u> </u>	**			
Biochemical oxygen demand (BOD)	Not applicable			
Chemical oxygen demand (COD)	Not applicable			
ThOD	Not applicable			
12.3. Bioaccumulative potential				
ProGun 28 LI (Mixture)				
Bioaccumulative potential	Not established.			
cristobalite (14464-46-1)				
Bioaccumulative potential	No data available.			
·				
quartz (14808-60-7)	No data available			
Bioaccumulative potential	No data available.			
12.4. Mobility in soil				
cristobalite (14464-46-1)				
Ecology - soil	No data available.			
12.5. Other adverse effects	110 data available.			
Effect on the global warming	None known			
Other information	: No other effects known.			
SECTION 13: Disposal considerations				
13.1. Disposal methods				
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.				
	Avoid release to the environment.			

04/13/2021 EN (English US) 4/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated

Transportation of Dangerous Goods

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

ProGun 28 LI (Mixture)

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

CANADA

Calcium Aluminate Cement (65997-16-2)

Listed on the Canadian DSL (Domestic Substances List)

cristobalite (14464-46-1)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

quartz (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

cristobalite (14464-46-1)

ProGun 28 LI (Mixture)	
U.S California - Proposition 65 - Other	This product contains crystalline silica, a chemical known to the state of California to
information	cause cancer. For more information go to WWW.P65Warnings.ca.gov

U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		
quartz (14808-6	0-7)	•	·		
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

Component	State or local regulations	
Cristobalite (14464-46-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List	
Quartz (14808-60-7)	U.S New Jersey - Right to Know Hazardous Substance List	

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 04/13/2021

Other information : Report language name. English. In the event of any conflict between English and other

language versions, the English version shall prevail.

Full text of H-phrases:

H315	Causes skin irritation
H320	Causes eye irritation
H350	May cause cancer

SDS US (GHS HazCom 2012)

04/13/2021 EN (English US) 5/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.

04/13/2021 EN (English US) 6/6