

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 6/10/2015 Revision date: 6/11/2024 Supersedes: 5/12/2021

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : QuikLite 30
CAS-No. : Mixture
Product code : 8876

Other means of identification : Alumina-Silicate Cement Bonded Castable

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Refractory Recommended use : Industrial use

1.3. Supplier

Resco Products, Inc.
One Robinson Plaza, Suite 300
6600 Steubenville Pike
Pittsburgh, PA, 15205
United States
T 412-494-4491

SDS@RescoProducts.com - WWW.RescoProducts.com

1.4. Emergency telephone number

Emergency number : EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300

Outside USA & Canada +1 703-741-5970

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2B

Carcinogenicity Category 1A

H315

Causes skin irritation

Causes eye irritation

Causes eye irritation

May cause cancer (Inhalation)

Full text of H statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)





Signal word (GHS US) : Danger

Hazard statements (GHS US) : H315 - Causes skin irritation H320 - Causes eye irritation

H350 - May cause cancer (Inhalation)

Precautionary statements (GHS US) : P280 - Wear eye protection, Dust respirator, protective gloves.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention.

P260 - Do not breathe dust.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| oizi mixtaroo | | | |
|------------------------------|---------------------|---------|-----------------------|
| Name | Product identifier | % | GHS US classification |
| Calcium Aluminate Cement | CAS-No.: 65997-16-2 | 10 – 20 | Skin Irrit. 2, H315 |
| | | | Eye Irrit. 2B, H320 |
| aluminium oxide, non-fibrous | CAS-No.: 1344-28-1 | 5 – 10 | Not classified |
| cristobalite | CAS-No.: 14464-46-1 | 5 – 10 | Carc. 1A, H350 |
| quartz | CAS-No.: 14808-60-7 | 1 – 5 | Carc. 1A, H350 |

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of hazard classes and H-statements: see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice

(show the label where possible).

First-aid measures after inhalation : Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Gently wash with plenty of soap and water.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and : Danger of serious damage to health by prolonged exposure through inhalation.

symptoms

Symptoms/effects after inhalation : Danger of serious damage to health by prolonged exposure through inhalation. May cause

cancer by inhalation.

Symptoms/effects after skin contact : Causes skin irritation. Symptoms/effects after eye contact : Causes eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : In case of fire, all extinguishing media allowed.

5.2. Specific hazards arising from the chemical

Fire hazard : Not flammable.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire with normal precautions from a reasonable distance. Prevent fire-fighting water from

entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Do not breathe dust. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area. On land, sweep or shovel into suitable containers.

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : On land, sweep or shovel into suitable containers. Minimize generation of dust.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Avoid raising dust.

Avoid contact with skin and eyes. Do not breathe dust.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store this product in a dry location where it can be protected from the elements.

Incompatible products : Strong bases. Strong acids.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

QuikLite 30 (Mixture)

No additional information available

6/11/2024 (Revision date) EN (English US) 2/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Calcium Aluminate Cement (65997-16-2) | |
|--|--|
| No additional information available | |
| cristobalite (14464-46-1) | |
| USA - ACGIH - Occupational Exposure Limits | |
| ACGIH OEL TWA | 0.025 mg/m³ respirable dust |
| USA - OSHA - Occupational Exposure Limits | |
| OSHA PEL (TWA) [1] | 0.05 mg/m³ respirable dust |
| aluminium oxide, non-fibrous (1344-28-1) | |
| USA - ACGIH - Occupational Exposure Limits | |
| ACGIH OEL TWA | 1 mg/m³ respirable dust |
| quartz (14808-60-7) | |
| USA - ACGIH - Occupational Exposure Limits | |
| ACGIH OEL TWA | 0.025 mg/m³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction) |
| USA - OSHA - Occupational Exposure Limits | |
| Local name | Silica, crystalline quartz, respirable dust |
| OSHA PEL (TWA) [1] | 0.05 mg/m³ respirable dust |
| Remark (OSHA) | (3) See Table Z-3. |
| 8.2. Appropriate engineering controls | |
| Appropriate engineering controls : | Provide adequate ventilation to minimize dust concentrations. |

Appropriate engineering controls

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

| 4 | voia | all | unne | ecessary | exposure. |
|---|------|-----|------|----------|-----------|
| | | | | | |

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask

Other information:

Odor threshold

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid Appearance Granular mixture. Color Light gray earthy Odor

≈ 10.5 рΗ pH solution concentration 10 %

> 2000 °F Melting point No data available Freezing point Boiling point No data available Flash point No data available Relative evaporation rate (butyl acetate=1) No data available Flammability (solid, gas) Not flammable. Vapor pressure No data available Relative vapor density at 20°C No data available Relative density No data available Slightly soluble. Solubility Partition coefficient n-octanol/water (Log Pow) No data available No data available

Auto-ignition temperature Decomposition temperature No data available Viscosity, kinematic Not Applicable Viscosity, dynamic No data available **Explosion limits** No data available Explosive properties No data available

6/11/2024 (Revision date) EN (English US) 3/7

No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Hydraulic setting.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Avoid dust formation.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified

| aluminium | ovido non | -fibrous | /12 <i>/1</i> /2021\ |
|---------------------|------------|-------------|----------------------|
| i aiuiiiiiiiiiiiiii | JXIUE. HUH | -IIDI OUS I | (1344-20-1) |

| aluminum oxide, non-hbrous (1344-26-1) | |
|--|--|
| LD50 oral rat | > 15900 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s)) |
| | > 2.3 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s)) |

Skin corrosion/irritation : Causes skin irritation.

pH: ≈ 10.5

Calcium Aluminate Cement (65997-16-2)

pH ≤ 13

cristobalite (14464-46-1)

pH 6-7

aluminium oxide, non-fibrous (1344-28-1)

pH 9 – 10.5 (aqueous suspension, 33 %)

quartz (14808-60-7)

pH 6-7

Serious eye damage/irritation : Causes eye irritation.

pH: ≈ 10.5

Calcium Aluminate Cement (65997-16-2)

pH ≤ 13

cristobalite (14464-46-1)

pH 6-7

aluminium oxide, non-fibrous (1344-28-1)

pH 9 – 10.5 (aqueous suspension, 33 %)

quartz (14808-60-7)

pH 6-7

Respiratory or skin sensitization : Not classified

6/11/2024 (Revision date) EN (English US) 4/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations | | |
|---|--|--|--|
| , | Not classified May cause cancer (Inhalation). | | |
| quartz (14808-60-7) | | | |
| IARC group | 1 - Carcinogenic to humans | | |
| STOT-single exposure : STOT-repeated exposure : Aspiration hazard : | Not classified Not classified Not classified Not classified Not classified Not Applicable | | |
| Viscosity, kinematic | Not applicable (solid) | | |
| Potential Adverse human health effects and symptoms Symptoms/effects after inhalation : Symptoms/effects after skin contact : | Danger of serious damage to health by prolonged exposure through inhalation. Danger of serious damage to health by prolonged exposure through inhalation. May cause cancer by inhalation. Causes skin irritation. Causes eye irritation. | | |
| SECTION 12: Ecological information | Succession of the succession o | | |
| 12.1. Toxicity | | | |
| aluminium oxide, non-fibrous (1344-28-1) | | | |
| LC50 - Fish [1] | > 100 mg/l (96 h, Salmo trutta, Literature study) | | |
| EC50 - Crustacea [1] | > 100 mg/l (48 h, Daphnia magna, Literature study) | | |
| 12.2. Persistence and degradability | | | |
| QuikLite 30 (Mixture) | | | |
| Persistence and degradability | Not established. | | |
| cristobalite (14464-46-1) | | | |
| Persistence and degradability | Mineral. Not applicable. | | |
| Chemical oxygen demand (COD) | Not applicable | | |
| ThOD | Not applicable | | |
| BOD (% of ThOD) | Not applicable | | |
| aluminium oxide, non-fibrous (1344-28-1) | | | |
| Persistence and degradability | Not applicable. | | |
| | | | |
| Chemical oxygen demand (COD) | Not applicable | | |
| Chemical oxygen demand (COD) ThOD | Not applicable Not applicable | | |
| | | | |
| ThOD | | | |
| ThOD quartz (14808-60-7) | Not applicable | | |
| ThOD quartz (14808-60-7) Persistence and degradability | Not applicable Not applicable. | | |
| ThOD quartz (14808-60-7) Persistence and degradability Biochemical oxygen demand (BOD) | Not applicable Not applicable. Not applicable | | |
| ThOD quartz (14808-60-7) Persistence and degradability Biochemical oxygen demand (BOD) Chemical oxygen demand (COD) | Not applicable Not applicable. Not applicable Not applicable | | |
| ThOD quartz (14808-60-7) Persistence and degradability Biochemical oxygen demand (BOD) Chemical oxygen demand (COD) ThOD | Not applicable Not applicable. Not applicable Not applicable | | |
| ThOD quartz (14808-60-7) Persistence and degradability Biochemical oxygen demand (BOD) Chemical oxygen demand (COD) ThOD 12.3. Bioaccumulative potential | Not applicable Not applicable. Not applicable Not applicable | | |
| ThOD quartz (14808-60-7) Persistence and degradability Biochemical oxygen demand (BOD) Chemical oxygen demand (COD) ThOD 12.3. Bioaccumulative potential QuikLite 30 (Mixture) | Not applicable Not applicable Not applicable Not applicable Not applicable Not applicable | | |

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| aluminium oxide, non-fibrous (1344-28-1) | | | |
|--|-------------------------------------|--|--|
| Bioaccumulative potential | No data available. | | |
| quartz (14808-60-7) | | | |
| Bioaccumulative potential | No data available. | | |
| 12.4. Mobility in soil | | | |
| cristobalite (14464-46-1) | cristobalite (14464-46-1) | | |
| Ecology - soil | No data available. | | |
| aluminium oxide, non-fibrous (1344-28-1) | | | |
| Surface tension | No data available in the literature | | |
| Ecology - soil | No data available. | | |
| 12.5. Other adverse effects | | | |
| | | | |

Effect on the global warming : None known

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

Department of Transportation (DOT)

In accordance with DOT

Not regulated

Transportation of Dangerous Goods

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

aluminium oxide, non-fibrous (1344-28-1)

Not subject to reporting requirements of the United States SARA Section 313

Note

Note: The section 313 chemical list contains "CAS # 1344-28-1 Aluminum Oxide (Fibrous forms)"; the Aluminum oxide contained in this product is non-fibrous, and thus is not a section 313 material. Only manufacturing, processing, or otherwise use of aluminum oxide in the fibrous form triggers reporting.

15.2. International regulations

CANADA

Calcium Aluminate Cement (65997-16-2)

Listed on the Canadian DSL (Domestic Substances List)

cristobalite (14464-46-1)

Listed on the Canadian DSL (Domestic Substances List)

aluminium oxide, non-fibrous (1344-28-1)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

6/11/2024 (Revision date) EN (English US) 6/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Not | ono | l regu | los | one |
|------|-------|--------|-----|-------|
| Ival | iviia | ııeyu | ıaı | IUIIS |

quartz (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

QuikLite 30 (Mixture)

U.S. - California - Proposition 65 - Other information This product contains crystalline silica, a chemical known to the state of California to cause cancer. For more information go to WWW.P65Warnings.ca.gov

| cristobalite | (14464-46- [,] | 1) |
|---------------|-------------------------|-----|
| U.S Californi | a - | U.S |

| U.S California - | Ú.S California - | U.S California - | U.S California - | No significant risk | Maximum allowable |
|------------------|------------------------|-----------------------|-----------------------|---------------------|-------------------|
| Proposition 65 - | Proposition 65 - | Proposition 65 - | Proposition 65 - | level (NSRL) | dose level (MADL) |
| Carcinogens List | Developmental Toxicity | Reproductive Toxicity | Reproductive Toxicity | | |
| | | - Female | - Male | | |
| Yes | No | No | No | | |

quartz (14808-60-7)

| U.S California - | U.S California - | U.S California - | U.S California - | No significant risk | Maximum allowable |
|------------------|------------------------|-----------------------|-----------------------|---------------------|-------------------|
| Proposition 65 - | Proposition 65 - | Proposition 65 - | Proposition 65 - | level (NSRL) | dose level (MADL) |
| Carcinogens List | Developmental Toxicity | Reproductive Toxicity | Reproductive Toxicity | | |
| | | - Female | - Male | | |
| Yes | No | No | No | | |

| Component | State or local regulations |
|--|--|
| Cristobalite (14464-46-1) | U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List |
| aluminium oxide, non-fibrous (1344-28-1) | U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List |
| Quartz (14808-60-7) | U.S New Jersey - Right to Know Hazardous Substance List |

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date 6/11/2024

Report language name. English. In the event of any conflict between English and other language Other information

versions, the English version shall prevail.

| vordione, the English vordion chair provair. | | |
|--|------------------------|--|
| Full text of H-phrases | | |
| H315 | Causes skin irritation | |
| H320 | Causes eye irritation | |
| H350 | May cause cancer | |

Safety Data Sheet (SDS), USA

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.

6/11/2024 (Revision date) EN (English US) 7/7