

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 6/1/2015 Revision date: 8/7/2024 Supersedes: 7/28/2021

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Product name : Rescocast 110G QT

CAS-No. : Mixture Product code : 8961

Other means of identification : Alumina-Silicate Cement Bonded Castable

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Refractory Recommended use : Industrial use

1.3. Supplier

Resco Products, Inc.
One Robinson Plaza, Suite 300
6600 Steubenville Pike
Pittsburgh, PA, 15205
United States
T 412-494-4491

SDS@RescoProducts.com - WWW.RescoProducts.com

1.4. Emergency telephone number

Emergency number : EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300

Outside USA & Canada +1 703-741-5970

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation Category 2 H315 Causes skin irritation Serious eye damage/eye irritation Category 2B H320 Causes eye irritation

Carcinogenicity Category 1A H350 May cause cancer (Inhalation)

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)





Signal word (GHS US) : Danger

Hazard statements (GHS US) : H315 - Causes skin irritation H320 - Causes eye irritation

H350 - May cause cancer (Inhalation)

Precautionary statements (GHS US) : P280 - Wear eye protection, Dust respirator, protective gloves.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention.

P260 - Do not breathe dust.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

o.z. mixturos				
Name	Product identifier	%	GHS US classification	
cristobalite	CAS-No.: 14464-46-1	10 – 20	Carc. 1A, H350	
Calcium Aluminate Cement	CAS-No.: 65997-16-2	10 – 20	Skin Irrit. 2, H315	
			Eye Irrit. 2B, H320	
aluminium oxide, non-fibrous	CAS-No.: 1344-28-1	5 – 10	Not classified	
quartz	CAS-No.: 14808-60-7	1 – 5	Carc. 1A, H350	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of hazard classes and H-statements: see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice

(show the label where possible).

First-aid measures after inhalation : Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Gently wash with plenty of soap and water.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and : Danger of serious damage to health by prolonged exposure through inhalation.

symptoms

Symptoms/effects after inhalation : Danger of serious damage to health by prolonged exposure through inhalation. May cause

cancer by inhalation.

Symptoms/effects after skin contact : Causes skin irritation. Symptoms/effects after eye contact : Causes eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : In case of fire, all extinguishing media allowed.

5.2. Specific hazards arising from the chemical

Fire hazard : Not flammable.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire with normal precautions from a reasonable distance. Prevent fire-fighting water from

entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Do not breathe dust. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area. On land, sweep or shovel into suitable containers.

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : On land, sweep or shovel into suitable containers. Minimize generation of dust.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Avoid raising dust.

Avoid contact with skin and eyes. Do not breathe dust.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store this product in a dry location where it can be protected from the elements.

Incompatible products : Strong bases. Strong acids.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Rescocast 110G QT (Mixture)

No additional information available

8/7/2024 (Revision date) EN (English US) 2/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Calcium Aluminate Cement (65997-16-2)				
No additional information available				
cristobalite (14464-46-1)				
USA - ACGIH - Occupational Exposure Limits				
ACGIH OEL TWA	0.025 mg/m³ respirable dust			
USA - OSHA - Occupational Exposure Limits				
OSHA PEL (TWA) [1]	0.05 mg/m³ respirable dust			
aluminium oxide, non-fibrous (1344-28-1)				
USA - ACGIH - Occupational Exposure Limits				
ACGIH OEL TWA	1 mg/m³ respirable dust			
quartz (14808-60-7)				
USA - ACGIH - Occupational Exposure Limits				
ACGIH OEL TWA	0.025 mg/m³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)			
USA - OSHA - Occupational Exposure Limits				
Local name	Silica, crystalline quartz, respirable dust			
OSHA PEL (TWA) [1]	0.05 mg/m³ respirable dust			
Remark (OSHA)	(3) See Table Z-3.			
8.2. Appropriate engineering controls				

Appropriate engineering controls : Provide adequate ventilation to minimize dust concentrations.

> 2000 °F

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand	protection:
HUHH	pi otcotioii.

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask

Other information:

Melting point

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid Appearance Granular mixture. Color Light gray earthy Odor

Odor threshold No data available ≈ 10.5 рΗ pH solution concentration 10 %

No data available Freezing point Boiling point No data available Flash point No data available Relative evaporation rate (butyl acetate=1) No data available Flammability (solid, gas) Not flammable. Vapor pressure No data available Relative vapor density at 20°C No data available Relative density ≈ 1.8 Slightly soluble. Solubility Partition coefficient n-octanol/water (Log Pow) No data available Auto-ignition temperature No data available

Decomposition temperature No data available Viscosity, kinematic Not Applicable Viscosity, dynamic No data available **Explosion limits** No data available Explosive properties No data available

8/7/2024 (Revision date) EN (English US) 3/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Hydraulic setting.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Avoid dust formation.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified

-1	and and all	man filenana	(4044 00 4)
laiumini	um oxide.	non-fibrous	(1344-28-1)

aluminum oxide, non-ribrous (1544-26-1)		
LD50 oral rat	> 15900 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))	
LC50 Inhalation - Rat	> 2.3 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))	

Skin corrosion/irritation : Causes skin irritation.

pH: ≈ 10.5

6 - 7

Calcium Aluminate Cement (65997-16-2)

pH ≤ 13

cristobalite (14464-46-1)

pH 6-7

aluminium oxide, non-fibrous (1344-28-1)

pH 9 – 10.5 (aqueous suspension, 33 %)

quartz (14808-60-7)

0------

Serious eye damage/irritation : Causes eye irritation. pH: ≈ 10.5

Calcium Aluminate Cement (65997-16-2)

pH ≤ 13

cristobalite (14464-46-1)

pH 6-7

aluminium oxide, non-fibrous (1344-28-1)

pH 9 – 10.5 (aqueous suspension, 33 %)

quartz (14808-60-7)

pH 6-7

Respiratory or skin sensitization : Not classified

8/7/2024 (Revision date) EN (English US) 4/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

according to Federal Register / Vol. 77, No. 58 / Monday, March	according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations			
,	Not classified May cause cancer (Inhalation).			
quartz (14808-60-7)				
IARC group	1 - Carcinogenic to humans			
STOT-single exposure : STOT-repeated exposure : Aspiration hazard :	Not classified Not classified Not classified Not classified Not classified Not Applicable			
Viscosity, kinematic	Not applicable (solid)			
symptoms Symptoms/effects after inhalation : Symptoms/effects after skin contact :	Danger of serious damage to health by prolonged exposure through inhalation. Danger of serious damage to health by prolonged exposure through inhalation. May cause cancer by inhalation. Causes skin irritation. Causes eye irritation.			
SECTION 12: Ecological information				
12.1. Toxicity				
aluminium oxide, non-fibrous (1344-28-1)				
LC50 - Fish [1]	> 100 mg/l (96 h, Salmo trutta, Literature study)			
EC50 - Crustacea [1]	> 100 mg/l (48 h, Daphnia magna, Literature study)			
12.2. Persistence and degradability				
Rescocast 110G QT (Mixture)				
Persistence and degradability	Not established.			
cristobalite (14464-46-1)				
Persistence and degradability	Mineral. Not applicable.			
Chemical oxygen demand (COD)	Not applicable			
ThOD	Not applicable			
BOD (% of ThOD)	Not applicable			
aluminium oxide, non-fibrous (1344-28-1)				
Persistence and degradability	Not applicable.			
Chemical oxygen demand (COD)	Not applicable			
ThOD	Not applicable			
quartz (14808-60-7)				
Persistence and degradability	Not applicable.			
Biochemical oxygen demand (BOD)	Not applicable			
Chemical oxygen demand (COD)	Not applicable			
ThOD	Not applicable			
12.3. Bioaccumulative potential				
Rescocast 110G QT (Mixture)				
Nescocast 1100 Q1 (MIXture)				
Bioaccumulative potential	Not established.			
	Not established.			

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

aluminium oxide, non-fibrous (1344-28-1)			
Bioaccumulative potential	No data available.		
quartz (14808-60-7)			
Bioaccumulative potential	No data available.		
12.4. Mobility in soil			
cristobalite (14464-46-1)			
Ecology - soil	No data available.		
aluminium oxide, non-fibrous (1344-28-1)			
Surface tension	No data available in the literature		
Ecology - soil	No data available.		

12.5. Other adverse effects

Effect on the global warming : None known

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

Department of Transportation (DOT)

In accordance with DOT

Not regulated

Transportation of Dangerous Goods

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

aluminium oxide, non-fibrous (1344-28-1)

Not subject to reporting requirements of the United States SARA Section 313

Note

Note: The section 313 chemical list contains "CAS # 1344-28-1 Aluminum Oxide (Fibrous forms)"; the Aluminum oxide contained in this product is non-fibrous, and thus is not a section 313 material. Only manufacturing, processing, or otherwise use of aluminum oxide in the fibrous form triggers reporting.

15.2. International regulations

Calcium Aluminate Cement (65997-16-2)

Listed on the Canadian DSL (Domestic Substances List)

cristobalite (14464-46-1)

Listed on the Canadian DSL (Domestic Substances List)

aluminium oxide, non-fibrous (1344-28-1)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

8/7/2024 (Revision date) EN (English US) 6/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Not	ono	l regu	los	one
Ival	iviia	ııeyu	ıaı	IUIIS

quartz (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

Rescocast 110G QT (Mixture)

U.S. - California - Proposition 65 - Other information

This product contains crystalline silica, a chemical known to the state of California to cause cancer. For more information go to WWW.P65Warnings.ca.gov

cristobalite (14464-	46-1)				
U.S California -	U.S California -	U.S California -	U.S California -	No significant risk	Maximum allowable
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	level (NSRL)	dose level (MADL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity	Reproductive Toxicity	, í	, , ,
		- Female	- Male		
Yes	No	No	No		

quartz (14808-60-7)					
U.S California -	U.S California -	U.S California -	U.S California -	No significant risk	Maximum allowable
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	level (NSRL)	dose level (MADL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity	Reproductive Toxicity		
		- Female	- Male		
Yes	No	No	No		

State or local regulations
U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous
Substance List; U.S Pennsylvania - RTK (Right to Know) List
U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous
Substance List; U.S Pennsylvania - RTK (Right to Know) List
U.S New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 8/7/2024

Other information : Report language name. English. In the event of any conflict between English and other language

versions, the English version shall prevail.

	· · · · · · · · · · · · · · · · · · ·	
Full text of H-	phrases	
H315	Causes skin irritation	
H320	Causes eye irritation	
H350	May cause cancer	

Safety Data Sheet (SDS), USA

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.

8/7/2024 (Revision date) EN (English US) 7/7