

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Product name : Rescoweld S
CAS-No. : Mixture
Product code : 7569

1.2. Other means of identification

Other means of identification : Silica Weld Powder

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Refractory
Recommended use : Industrial use

1.4. Supplier's details

RHI Magnesita
425 South Salem Church Road
York, PA, 17408
United States
T 717-792-3611
Resco_SDS.TDS@rhimagnesita.com - WWW.RescoProducts.com

1.5. Emergency phone number

Emergency number : EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300
Outside USA & Canada +1 703-741-5970

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Serious eye damage/eye irritation, Category 2B	H320	Causes eye irritation.
Carcinogenicity, Category 1A	H350	May cause cancer (Inhalation).

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) : H350 - May cause cancer (Inhalation).
H320 - Causes eye irritation
H315 - Causes skin irritation

Precautionary statements (GHS US) : P260 - Do not breathe dust.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P280 - Wear Respiratory Protection, protective gloves, eye protection, In case of insufficient ventilation, wear suitable respiratory equipment.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

Other hazards which do not result in classification : Dust may form explosive mixture in air.

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
cristobalite	CAS-No.: 14464-46-1	60 – 80	Carc. 1A, H350
Silicon Metal Powder	CAS-No.: 7440-21-3	10 – 30	Not classified
quartz	CAS-No.: 14808-60-7	0.1 – 0.5	Carc. 1A, H350

Rescoweld S

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person.
First-aid measures after inhalation	: Allow affected person to breathe fresh air.
First-aid measures after skin contact	: Gently wash with plenty of soap and water.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting.

4.2. Most important symptoms/effects, acute and delayed

Potential Adverse human health effects and symptoms	: Danger of serious damage to health by prolonged exposure through inhalation.
Symptoms/effects after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. May cause cancer by inhalation.
Symptoms/effects after skin contact	: Contact during a long period may cause slight irritation.
Symptoms/effects after eye contact	: Causes eye irritation.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Dry powder. Dry sand. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	: Do not use extinguishing media containing water.

5.2. Specific hazards arising from the chemical

Fire hazard	: Dry Silicon Metal in the form of lumps or granules (Bottom Screen >200 mesh) is not combustible.
Explosion hazard	: Dust cloud can be ignited by a spark.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Prevent entry to sewers and public waters.
---------------------------	--

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Avoid contact with skin and eyes.
For non-emergency personnel	
Protective equipment	: Do not breathe dust.
For emergency responders	
Protective equipment	: Use personal protective equipment as required.
Emergency procedures	: Ventilate area.
Environmental precautions	: Prevent entry to sewers and public waters.

6.2. Methods and materials for containment and cleaning up

Methods for cleaning up	: Collect spillage. Prevent dust cloud formation.
For further information refer to section 8: "Exposure controls/personal protection"	

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Avoid raising powdered material due to explosion hazard. Avoid contact with skin and eyes.
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including incompatibilities

Storage conditions	: Store this product in a dry location where it can be protected from the elements. Store in a well-ventilated place.
Incompatible materials for storage	: Strong acids, bases. water.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

cristobalite (14464-46-1)

USA - ACGIH® - Threshold Limit Values

ACGIH® TLV® TWA	0.025 mg/m ³ respirable dust
-----------------	---

USA - OSHA - Occupational Exposure Limits

OSHA PEL TWA	0.05 mg/m ³ respirable dust
--------------	--

Rescoweld S

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

quartz (14808-60-7)	
USA - ACGIH® - Threshold Limit Values	
ACGIH® TLV® TWA	0.025 mg/m³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)
USA - OSHA - Occupational Exposure Limits	
Local name	Silica, crystalline quartz, respirable dust
OSHA PEL TWA	0.05 mg/m³ respirable dust
Remark (OSHA)	(3) See Table Z-3.

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide adequate ventilation to minimize dust concentrations.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:
Wear protective gloves.
Eye protection:
Chemical goggles or safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of inadequate ventilation wear respiratory protection.

Other information:

Do not eat, drink or smoke when using this product.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Solid
Appearance	: Granular powder.
Color	: Gray
Odor	: None
Odor threshold	: No data available
pH	: No data available
Melting point	: > 1100 °F
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Flammability (solid, gas)	: Not flammable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: ≈ 1.3
Solubility	: Insoluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosion limits	: No data available
Explosive properties	: Product not explosive, although dusts may form explosive mixtures with air.
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

None known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Prolonged contact with water may release hydrogen. Reactions with acids and alkalis may release hazardous gases, including hydrogen.

Rescoweld S

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

10.4. Conditions to avoid

Avoid dust formation. Product not explosive, although dusts may form explosive mixtures with air.

10.5. Incompatible materials

Acids. Oxidizing agent. Strong bases. Water :

10.6. Hazardous decomposition products

May release flammable gases.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified
Skin corrosion/irritation : Causes skin irritation.

cristobalite (14464-46-1)

pH	6 – 7
----	-------

quartz (14808-60-7)

pH	6 – 7
----	-------

Serious eye damage/irritation : Causes eye irritation.

cristobalite (14464-46-1)

pH	6 – 7
----	-------

quartz (14808-60-7)

pH	6 – 7
----	-------

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : May cause cancer (Inhalation).

quartz (14808-60-7)

IARC group	1 - Carcinogenic to humans
------------	----------------------------

Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified
Potential Adverse human health effects and symptoms : Danger of serious damage to health by prolonged exposure through inhalation.
Symptoms/effects after inhalation : Danger of serious damage to health by prolonged exposure through inhalation. May cause cancer by inhalation.
Symptoms/effects after skin contact : Contact during a long period may cause slight irritation.
Symptoms/effects after eye contact : Causes eye irritation.

SECTION 12 Ecological information

12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Not classified

12.2. Persistence and degradability

Rescoweld S (Mixture)

Persistence and degradability	Not established.
-------------------------------	------------------

cristobalite (14464-46-1)

Persistence and degradability	Mineral, Not applicable.
-------------------------------	--------------------------

Chemical oxygen demand (COD)	Not applicable
------------------------------	----------------

ThOD	Not applicable
------	----------------

BOD (% of ThOD)	Not applicable
-----------------	----------------

Rescoweld S

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Silicon Metal Powder (7440-21-3)	
Persistence and degradability	Rapidly degradable
quartz (14808-60-7)	
Persistence and degradability	Not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
12.3. Bioaccumulative potential	
cristobalite (14464-46-1)	
Bioaccumulative potential	No data available.
quartz (14808-60-7)	
Bioaccumulative potential	No data available.
12.4. Mobility in soil	
cristobalite (14464-46-1)	
Ecology - soil	No data available.
12.5. Other adverse effects	
Ozone	: Not classified
Fluorinated greenhouse gases	: No
SECTION 13 Disposal considerations	
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
SECTION 14 Transport information	
In accordance with DOT / TDG / IMDG / IATA	
Department of Transportation (DOT)	
In accordance with DOT	
Not regulated	
Transportation of Dangerous Goods	
Not regulated	
Transport by sea	
Not regulated	
Air transport	
Not regulated	
SECTION 15 Regulatory information	
15.1. Federal regulations	
All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory	
15.2. International regulations	
CANADA	
cristobalite (14464-46-1)	
Listed on the Canadian DSL (Domestic Substances List)	
Silicon Metal Powder (7440-21-3)	
Listed on the Canadian DSL (Domestic Substances List)	
EU-Regulations	
No additional information available	
National regulations	
quartz (14808-60-7)	
Listed on IARC (International Agency for Research on Cancer)	

Rescoweld S

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

15.3. State regulations	
Rescoweld S (Mixture)	
U.S. - California - Proposition 65 - Other information	This product contains crystalline silica, a chemical known to the State of California to cause cancer. For more information go to WWW.P65Warnings.ca.gov

cristobalite (14464-46-1)					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

quartz (14808-60-7)					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

Component	State or local regulations
cristobalite(14464-46-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Silicon Metal Powder(7440-21-3)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
quartz(14808-60-7)	U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16 Other information	
according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)	
Revision date	: 9/3/2026
Issue date	: 2/21/2019
Other information	: Report language name. English. In the event of any conflict between English and other language versions, the English version shall prevail.

Full text of hazard classes and H-statements	
H315	Causes skin irritation
H320	Causes eye irritation
H350	May cause cancer.

Safety Data Sheet (SDS), USA
This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, RHI Magnesita makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.