

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date: 11/05/2021 Supersedes: 05/09/2017 Issue date: 11/05/2021

SECTION 1: Identification

Identification

Product form : Article

Product name Uniform R Max 4%HCA

CAS-No. Mixture Product code 4491

Other means of identification Alumina-Silicate Pre-Cast Shape

Recommended use and restrictions on use 1.2.

Use of the substance/mixture Industrial

Supplier

Resco Products, Inc.

One Robinson Plaza, Suite 300

6600 Steubenville Pike

Pittsburgh, PA 15205 - United States

412-494-4491

SDS@RescoProducts.com - WWW.RescoProducts.com

Emergency telephone number

: EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300 Emergency number

Outside USA & Canada +1 703-741-5970

SECTION 2: Hazard(s) identification

Classification of the substance or mixture

GHS US classification

Not classified

2.2. GHS Label elements, including precautionary statements

This product meets the definition and criteria for an article according to OSHA 29 CFR 1910.1200 and the EU REACH 1907/2006 Article 3(3)

regulations.

Other hazards not contributing to the : Note: This product contains metallic fiber, hand protection required. Pre-cast shape may be classification

heavy and cause pinch and drop hazards, use of gloves and safety shoes should be

considered.

Unknown acute toxicity (GHS US) 2.4.

Not applicable

SECTION 3: Composition/Information on ingredients

Substances

Not applicable

Mixtures

Name	Product identifier	%	GHS US classification
aluminium oxide, non-fibrous	(CAS-No.) 1344-28-1	50 – 75	Not classified
Calcium Aluminate Cement	(CAS-No.) 65997-16-2	5 – 10	Skin Irrit. 2, H315 Eye Irrit. 2B, H320
quartz	(CAS-No.) 14808-60-7	1 – 5	Carc. 1A, H350
cristobalite	(CAS-No.) 14464-46-1	0.5 – 1	Carc. 1A, H350

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. **Description of first aid measures**

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible).

Allow affected person to breathe fresh air. Allow the victim to rest. First-aid measures after inhalation

First-aid measures after skin contact Gently wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present First-aid measures after eye contact

and easy to do. Continue rinsing.

First-aid measures after ingestion Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms

: Based on available data, the classification criteria are not met.

Symptoms/effects after inhalation

: Danger of serious damage to health by prolonged exposure through inhalation. May cause

cancer by inhalation. Symptoms/effects after skin contact Causes skin irritation. Symptoms/effects after eye contact Causes eye irritation.

Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media Use extinguishing media appropriate for surrounding fire.

In case of fire, all extinguishing media allowed. Unsuitable extinguishing media

11/01/2021 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2. Specific hazards arising from the chemical

Fire hazard : Not flammable.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering

environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Avoid contact with skin and eyes. Do not breathe dust.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Emergency procedures : On land, sweep or shovel into suitable containers.

6.2. Environmental precautions
No additional information available

6.3. Methods and material for containment and cleaning up For containment : Collect spillage.

Methods for cleaning up : On land, sweep or shovel into suitable containers. Minimize generation of dust.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Avoid contact with

skin and eyes. Do not breathe dust.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store this product in a dry location where it can be protected from the elements.

Incompatible products : Strong bases. Strong acids.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Uniform R Max 4%HCA (Mixture)				
No additional information available				
Calcium Aluminate Cement (65997-16-2)				
No additional information available				
cristobalite (14464-46-1)				
USA - ACGIH - Occupational Exposure Limits				
ACGIH TWA (mg/m³)	0.025 mg/m³ respirable dust			
USA - OSHA - Occupational Exposure Limits				
OSHA PEL (TWA) (mg/m³)	0.05 mg/m³ respirable dust			
aluminium oxide, non-fibrous (1344-28-1)				
USA - ACGIH - Occupational Exposure Limits				
ACGIH TWA (mg/m³)	1 mg/m³ respirable dust			
quartz (14808-60-7)				
USA - ACGIH - Occupational Exposure Limits				
ACGIH TWA (mg/m³)	0.025 mg/m³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)			
USA - OSHA - Occupational Exposure Limits				
Local name	Silica, crystalline quartz, respirable dust			
OSHA PEL (TWA) (mg/m³)	0.05 mg/m³ respirable dust			
Remark (OSHA)	(3) See Table Z-3.			

8.2. Appropriate engineering controls

Appropriate engineering controls : Dust on tear out. Provide adequate ventilation to minimize dust concentrations.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves.

Eye protection:

Safety glasses

Skin and body protection:

11/01/2021 EN (English US) 2/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Wear suitable protective clothing. Safety shoes

Respiratory protection:

Dust when sawing or tear out. Wear appropriate mask

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid

Appearance : Solid in various shapes.

Color: Light grayOdor: odorlessOdor threshold: Not applicablepH: No data available

Melting point : > 2000 °F Freezing point : Not applicable Boiling point : Not applicable Critical temperature Not applicable Critical pressure Not applicable Not applicable Flash point Relative evaporation rate (butyl acetate=1) : Not applicable Relative evaporation rate (ether=1) Not applicable Flammability (solid, gas) Non flammable. : Not Applicable Vapor pressure Vapor pressure at 50 °C Not Applicable Relative vapor density at 20 °C No data available

Relative density : ≈ 2.6

Solubility : Insoluble in water. Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature Not applicable Decomposition temperature : No data available Viscosity, kinematic No data available Viscosity, dynamic Not Applicable **Explosion limits** Not applicable Explosive properties : No data available Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Avoid dust formation.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified

aluminium oxide, non-fibrous (1344-28-1)				
LD50 oral rat	> 15900 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)			
LC50 Inhalation - Rat	7.6 mg/l air (Equivalent or similar to OECD 403, 1 h, Rat, Male, Experimental value, Inhalation (aerosol))			

Skin corrosion/irritation : Not classified Serious eye damage/irritation : Not classified

11/01/2021 EN (English US) 3/6

Safety Data Sheet

according to Federal	Register / Vol	. 77, No. 58 / Mor	nday, March 26, 20	012 / Rules and Regulations

ccording to Federal Register / Vol. 77, No. 58 / Monday, N	arch 26, 2012 / Rules and Regulations
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	: Not classified
quartz (14808-60-7)	A Contract to be seen
IARC group	1 - Carcinogenic to humans
Reproductive toxicity STOT-single exposure	: Not classified : Not classified
STOT-single exposure STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Potential Adverse human health effects and	: Based on available data, the classification criteria are not met.
symptoms Symptoms/effects after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. May cause
Symptomo, on coto and minaration	cancer by inhalation.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes eye irritation.
SECTION 12: Ecological information	
12.1. Toxicity	
No additional information available	
12.2. Persistence and degradability	
Uniform R Max 4%HCA (Mixture)	Net established
Persistence and degradability	Not established.
cristobalite (14464-46-1)	
Persistence and degradability	Mineral. Not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
aluminium oxide, non-fibrous (1344-28-1)	
Persistence and degradability	Not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
quartz (14808-60-7)	Nat analizable
Persistence and degradability	Not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
12.3. Bioaccumulative potential	
Uniform R Max 4%HCA (Mixture)	
Bioaccumulative potential	Not established.
cristobalite (14464-46-1)	
Bioaccumulative potential	No data available.
aluminium oxide, non-fibrous (1344-28-1)	
Bioaccumulative potential	No data available.
<u>'</u>	The water strainbliff
quartz (14808-60-7)	All data and Sable
Bioaccumulative potential	No data available.
12.4. Mobility in soil	
cristobalite (14464-46-1)	
Ecology - soil	No data available.
aluminium oxide, non-fibrous (1344-28-1)	
Ecology - soil	No data available.
12.5. Other adverse effects	140 data available.
Effect on the global warming	None known
Other information	: No other effects known.
SECTION 13: Disposal considerations	
13.1. Disposal methods	
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.

11/01/2021 EN (English US) 4/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated

Transportation of Dangerous Goods

Not regulated

Transport by sea

Not regulated

Air transport Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

Uniform R Max 4%HCA (Mixture)

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

aluminium oxide, non-fibrous (1344-28-1)

Not subject to reporting requirements of the United States SARA Section 313

Note

Note: The section 313 chemical list contains "CAS # 1344-28-1 Aluminum Oxide (Fibrous forms)"; the Aluminum oxide contained in this product is non-fibrous, and thus is not a section 313 material. Only manufacturing, processing, or otherwise use of aluminum oxide in the fibrous form triggers reporting.

15.2. International regulations

CANADA

Calcium Aluminate Cement (65997-16-2)

Listed on the Canadian DSL (Domestic Substances List)

cristobalite (14464-46-1)

Listed on the Canadian DSL (Domestic Substances List)

aluminium oxide, non-fibrous (1344-28-1)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

quartz (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

Uniform R Max 4%HCA (Mixture)	
U.S California - Proposition 65 - Other	This product contains crystalline silica, a chemical known to the state of California to
information	cause cancer. For more information go to WWW.P65Warnings.ca.gov

cristobalite (1446	cristobalite (14464-46-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

quartz (14808-60-7)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

Component	State or local regulations	
Cristobalite (14464-46-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List	
aluminium oxide, non-fibrous (1344-28-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List	
Quartz (14808-60-7)	U.S New Jersey - Right to Know Hazardous Substance List	

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 11/05/202

Other information : Report language name. English. In the event of any conflict between English and other

language versions, the English version shall prevail.

11/01/2021 EN (English US) 5/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H315	Causes skin irritation
H320	Causes eye irritation
H350	May cause cancer

SDS US (GHS HazCom 2012)

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.

11/01/2021 EN (English US) 6/6