

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 5/1/2015 Revision date: 12/11/2024 Supersedes: 12/6/2021

SECTION 1: Identification			
1.1. Identification			
Product form	: Mixture		
Product name	: Unicrete 60 Flowz		
CAS-No.	: Mixture		
Product code	: 3134		
Other means of identification 1.2. Recommended use and restrictions or	: Alumina-Silicate Cement Bonded Castable		
Use of the substance/mixture	: Refractory		
Recommended use	: Industrial use		
1.3. Supplier			
Resco Products, Inc. One Robinson Plaza, Suite 300 6600 Steubenville Pike Pittsburgh, PA, 15205 United States T 412-494-4491 <u>SDS@RescoProducts.com</u> - <u>WWW.RescoProducts</u>	om		
1.4. Emergency telephone number			
Emergency number	: EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-42 Outside USA & Canada +1 703-741-5970	24-9300	
SECTION 2: Hazard(s) identification	Outside USA & Callada +1 705-741-5970		
2.1. Classification of the substance or mix	Ire		
GHS US classification			
Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2B Carcinogenicity Category 1A Full text of H statements : see section 16	H315Causes skin irritationH320Causes eye irritationH350May cause cancer (Inhalation)	
2.2. GHS Label elements, including precau	onary statements		
GHS US labeling Hazard pictograms (GHS US)			
Signal word (GHS US) Hazard statements (GHS US) Precautionary statements (GHS US)	zard statements (GHS US) : H315 - Causes skin irritation H320 - Causes eye irritation H350 - May cause cancer (Inhalation)		
	P260 - Do not breathe dust.		
2.3. Other hazards which do not result in c	assification		
No additional information available			
2.4. Unknown acute toxicity (GHS US)			
No additional information available			
SECTION 3: Composition/Information	n ingredients		
3.1. Substances			
Not applicable			
3.2. Mixtures			
Name		GHS US classification	
aluminium oxide, non-fibrous		Not classified	
Calcium Aluminate Cement		Skin Irrit. 2, H315 Eye Irrit. 2B, H320	
quartz			
cristobalite		Carc. 1A, H350	
quartz cristobalite		Carc. 1A, H350 Carc. 1A, H350	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of hazard classes and H-statements : see se	ection 16
SECTION 4: First-aid measures	
4.1. Description of first aid measures	
First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact First-aid measures after eye contact	 Gently wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present
	and easy to do. Continue rinsing.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.
4.2. Most important symptoms and effects (
Potential Adverse human health effects and symptoms	: Danger of serious damage to health by prolonged exposure through inhalation.
Symptoms/effects after inhalation	: May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure
	through inhalation.
Symptoms/effects after skin contact Symptoms/effects after eye contact	: Causes skin irritation. : Causes eye irritation.
4.3. Immediate medical attention and specia	
No additional information available	,
SECTION 5: Fire-fighting measures	
5.1. Suitable (and unsuitable) extinguishing	
Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: In case of fire, all extinguishing media allowed.
5.2. Specific hazards arising from the chem	ical
Fire hazard	: Not flammable.
5.3. Special protective equipment and preca	
Firefighting instructions	: Fight fire with normal precautions from a reasonable distance. Prevent fire-fighting water from
Protection during firefighting	entering environment. : Do not enter fire area without proper protective equipment, including respiratory protection.
SECTION 6: Accidental release measur	
6.1. Personal precautions, protective equip	
6.1.1. For non-emergency personnel	ment and emergency procedules
Emergency procedures	: Do not breathe dust. Avoid contact with skin and eyes.
6.1.2. For emergency responders	E w 's also any activity and a start of the
Protective equipment Emergency procedures	 Equip cleanup crew with proper protection. Ventilate area. On land, sweep or shovel into suitable containers.
6.2. Environmental precautions	
Prevent entry to sewers and public waters.	
6.3. Methods and material for containment	and cleaning up
Methods for cleaning up	: On land, sweep or shovel into suitable containers. Minimize generation of dust.
6.4. Reference to other sections	
See Heading 8. Exposure controls and personal prot	ection.
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Avoid raising dust. Avoid contact with skin and eves. Do not breathe dust.
Hygiene measures	 Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
7.2. Conditions for safe storage, including a	
Storage conditions	: Store this product in a dry location where it can be protected from the elements.
Incompatible products	: Strong bases. Strong acids.
SECTION 8: Exposure controls/persona	al protection
8.1. Control parameters	
cristobalite (14464-46-1)	
USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA	0.025 mg/m ³ respirable dust

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

cristobalite (14464-46-1)	
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA	0.05 mg/m ³ respirable dust
aluminium oxide, non-fibrous (1344-28-1)	
USA - ACGIH - Occupational Exposure Limits	A sector 9 sector bland set
ACGIH OEL TWA	1 mg/m ³ respirable dust
quartz (14808-60-7)	
USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA	0.025 mg/m ³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV -
ACGITOLETWA	Adopted Value; Respirable fraction)
USA - OSHA - Occupational Exposure Limits	
Local name	Silica, crystalline quartz, respirable dust
OSHA PEL TWA	0.05 mg/m ³ respirable dust
Remark (OSHA)	(3) See Table Z-3.
8.2. Appropriate engineering controls	
Appropriate engineering controls	: Provide adequate ventilation to minimize dust concentrations.
8.3. Individual protection measures/Persona	al protective equipment
Personal protective equipment:	
Avoid all unnecessary exposure.	
Hand protection:	
Wear protective gloves.	
Eye protection:	
Chemical goggles or safety glasses	
Skin and body protection:	
Wear suitable protective clothing	
Respiratory protection:	
Wear appropriate mask	
Other information: Do not eat, drink or smoke during use.	
SECTION 9: Physical and chemical pro	perties
9.1. Information on basic physical and chen	nical properties
Physical state	: Solid
Appearance	: Granular mixture.
Color Odor	: Gray : None
Odor threshold	: None : No data available
рН	: ≈ 10.5
pH solution concentration	: 10 %
Melting point	: > 3000 °F
Freezing point Boiling point	: No data available : No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not flammable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available : ≈ 2.6
Relative density Solubility	. ≈ 2.6 : Slightly soluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: Not Applicable
Viscosity, dynamic Explosion limits	: No data available : No data available
Explosion minus Explosive properties	: No data available
Oxidizing properties	: No data available
9.2. Other information	

No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity	
10.1. Reactivity	
Hydraulic setting.	
10.2. Chemical stability	
Stable under normal conditions of use.	
10.3. Possibility of hazardous reactions	
Not established.	
10.4. Conditions to avoid	
Avoid dust formation.	
10.5. Incompatible materials	
Strong acids. Strong bases.	
10.6. Hazardous decomposition products	
No additional information available	
SECTION 11: Toxicological information	
11.1. Information on toxicological effects	
Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
aluminium oxide, non-fibrous (1344-28-1)	
LD50 oral rat	> 15900 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LC50 Inhalation - Rat	> 2.3 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))
Skin corrosion/irritation	: Causes skin irritation. pH: ≈ 10.5
Calcium Aluminate Cement (65997-16-2)	
рН	≤ 13
cristobalite (14464-46-1)	
рН	6 – 7
aluminium oxide, non-fibrous (1344-28-1)	
рН	9 – 10.5 (aqueous suspension, 33 %)
quartz (14808-60-7)	
рН	6 - 7
Serious eye damage/irritation	: Causes eye irritation. pH: ≈ 10.5
Calcium Aluminate Cement (65997-16-2)	
рН	≤ 13
cristobalite (14464-46-1)	
рН	6 – 7
aluminium oxide, non-fibrous (1344-28-1)	
рН	9 – 10.5 (aqueous suspension, 33 %)
quartz (14808-60-7)	
рН	6 – 7
Respiratory or skin sensitization	Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer (Inhalation).

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

quartz (14808-60-7)				
IARC group	1 - Carcinogenic to humans			
Reproductive toxicity STOT-single exposure STOT-repeated exposure Aspiration hazard Viscosity, kinematic	 Not classified Not classified Not classified Not classified Not classified Not classified Not Applicable 			
aluminium oxide, non-fibrous (1344-28-1)				
Viscosity, kinematic	Not applicable (solid)			
Potential Adverse human health effects and symptoms Symptoms/effects after inhalation Symptoms/effects after skin contact Symptoms/effects after eye contact	 Danger of serious damage to health by prolonged exposure through inhalation. May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure through inhalation. Causes skin irritation. Causes eye irritation. 			
SECTION 12: Ecological information				
12.1. Toxicity				
aluminium oxide, non-fibrous (1344-28-1)				
LC50 - Fish [1]	> 100 mg/l (96 h, Salmo trutta, Literature study)			
EC50 - Crustacea [1]	> 100 mg/l (48 h, Daphnia magna, Literature study)			
12.2. Persistence and degradability				
Unicrete 60 Flowz (Mixture)				
Persistence and degradability	Not established.			
Calcium Aluminate Cement (65997-16-2)				
Persistence and degradability	Rapidly degradable			
cristobalite (14464-46-1)				
Persistence and degradability	Mineral, Not applicable.			
Chemical oxygen demand (COD)	Not applicable			
ThOD	Not applicable			
BOD (% of ThOD)	Not applicable			
aluminium oxide, non-fibrous (1344-28-1)				
Persistence and degradability	Not applicable.			
Chemical oxygen demand (COD)	Not applicable			
ThOD	Not applicable			
quartz (14808-60-7)				
Persistence and degradability	Not applicable.			
Biochemical oxygen demand (BOD)	Not applicable			
Chemical oxygen demand (COD)	Not applicable			
ThOD	Not applicable			
12.3. Bioaccumulative potential				
Unicrete 60 Flowz (Mixture)				
	Not established.			
Bioaccumulative potential				
cristobalite (14464-46-1)				

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

aluminium oxide, non-fibrous (134	aluminium oxide, non-fibrous (1344-28-1)			
Bioaccumulative potential	No data available.			
quartz (14808-60-7)				
Bioaccumulative potential	No data available.			
12.4. Mobility in soil				
cristobalite (14464-46-1)				
Ecology - soil	No data available.			
aluminium oxide, non-fibrous (134	14-28-1)			
Surface tension	No data available in the literature			
Ecology - soil	No data available.			
12.5. Other adverse effects				
Effect on the global warming	: None known			
SECTION 13: Disposal conside	rations			
13.1. Disposal methods				
Product/Packaging disposal recommenda				
SECTION 14: Transport inform				
In accordance with DOT Not regulated Transportation of Dangerous Goods Not regulated Transport by sea Not regulated Air transport Not regulated				
SECTION 15: Regulatory inform	nation			
15.1. US Federal regulations				
All components of this product are prese (TSCA) inventory	nt and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act			
aluminium oxide, non-fibrous (134	14-28-1)			
Not subject to reporting requirements of				
Note	Note: The section 313 chemical list contains "CAS # 1344-28-1 Aluminum Oxide (Fibrous forms)"; the Aluminum oxide contained in this product is non-fibrous, and thus is not a section 313 material. Only manufacturing, processing, or otherwise use of aluminum oxide in the fibrous form triggers reporting.			
15.2. International regulations				
CANADA				
Calcium Aluminate Cement (65997-16-2)				
Listed on the Canadian DSL (Domestic Substances List)				
cristobalite (14464-46-1)				
Listed on the Canadian DSL (Domestic Substances List)				
aluminium oxide, non-fibrous (1344-28-1)				
Listed on the Canadian DSL (Domestic S	Substances List)			
EU-Regulations				

EU-Regulations No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

National regulations	
quartz (14808-60-7)	
Listed on IARC (International Agency for Research on	Cancer)
15.3. US State regulations	
Unicrete 60 Flowz (Mixture)	
U.S California - Proposition 65 - Other information	This product contains crystalline silica, a chemical known to the state of California to cause
	cancer. For more information go to WWW.P65Warnings.ca.gov

cristobalite (14464-46-	1)				
U.S California -	U.S California -	U.S California -	U.S California -	No significant risk	Maximum allowable
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	level (NSRL)	dose level (MADL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity	Reproductive Toxicity		
		- Female	- Male		
Yes	No	No	No		

quartz (14808-60-7)					
U.S California - Proposition 65 -	No significant risk level (NSRL)	Maximum allowable dose level (MADL)			
Carcinogens List	Developmental Toxicity	Reproductive Toxicity - Female	Reproductive Toxicity - Male	× /	
Yes	No	No	No		

Component	State or local regulations	
Cristobalite (14464-46-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous	
	Substance List; U.S Pennsylvania - RTK (Right to Know) List	
aluminium oxide, non-fibrous (1344-28-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous	
	Substance List; U.S Pennsylvania - RTK (Right to Know) List	
Quartz (14808-60-7)	U.S New Jersey - Right to Know Hazardous Substance List	
SECTION 16: Other information		
according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations		

2 / Rules and Regulations

Revision date Other information

: 12/11/2024 Report language name. English. In the event of any conflict between English and other language versions, the English version shall prevail. :

Full text of hazard classes and H-statements H315 Causes skin irritation H320 Causes eye irritation

May cause cancer H350

Safety Data Sheet (SDS), USA

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.