

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 03/22/2022 Revision date: 03/22/2022 Supersedes: 04/01/2019

## **SECTION 1: Identification**

1.1. Identification

Product form : Mixture
Product name : Vibrocast 80SC
CAS-No. : Mixture
Product code : 0456

Other means of identification : Alumina Cement Bonded Castable

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Refractory Recommended use : Industrial use

1.3. Supplier

Resco Products. Inc.

One Robinson Plaza, Suite 300

6600 Steubenville Pike

Pittsburgh, PA 15205 - United States

412-494-4491

SDS@RescoProducts.com - WWW.RescoProducts.com

1.4. Emergency telephone number

Emergency number : EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300

Outside USA & Canada +1 703-741-5970

## SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

**GHS US classification** 

Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2B

H315 Causes skin irritation
H320 Causes eye irritation

Carcinogenicity Category 1A H350 May cause cancer (Inhalation)

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

**GHS US labeling** 

Hazard pictograms (GHS US)





Signal word (GHS US) : Danger

Hazard statements (GHS US)

: H315 - Causes skin irritation
H320 - Causes eye irritation
H350 - May cause cancer (Inhalation)

Precautionary statements (GHS US) : P280 - Wear eye protection, Dust respirator, protective gloves.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention.

P260 - Do not breathe dust.

#### 2.3. Other hazards which do not result in classification

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## **SECTION 3: Composition/Information on ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
silicon carbide	(CAS-No.) 409-21-2	75 – 95	Carc. 1B, H350
aluminium oxide, non-fibrous	(CAS-No.) 1344-28-1	5 – 10	Not classified
Calcium Aluminate Cement	(CAS-No.) 65997-16-2	5 – 10	Skin Irrit. 2, H315 Eye Irrit. 2B, H320
cristobalite	(CAS-No.) 14464-46-1	0.1 – 0.5	Carc. 1A, H350

Full text of hazard classes and H-statements : see section 16

#### **SECTION 4: First-aid measures**

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

03/18/2022 EN (English US) Page 1

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after inhalation : Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Gently wash with plenty of soap and water.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

First-aid measures after ingestion : Rinse mouth. Get medical advice/attention if you feel unwell. Do not induce vomiting.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure

through inhalation.

Symptoms/effects after skin contact : Causes skin irritation.
Symptoms/effects after eye contact : Causes eye irritation.

3. Immediate medical attention and special treatment, if necessary

No additional information available

#### **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : In case of fire, all extinguishing media allowed.

5.2. Specific hazards arising from the chemical

Fire hazard : Non-flammable.

5.3. Special protective equipment and precautions for fire-fightersFirefighting instructionsNo specific fire-fighting instructions required.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Avoid creating or spreading dust.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : On land, sweep or shovel into suitable containers.

6.4. Reference to other sections

# No additional information available SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Avoid contact with

skin and eyes. Do not breathe dust.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store this product in a dry location where it can be protected from the elements.

Incompatible products : Strong bases. Strong acids.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### Vibrocast 80SC (Mixture)

No additional information available

## aluminium oxide, non-fibrous (1344-28-1)

#### **USA - ACGIH - Occupational Exposure Limits**

ACGIH TWA (mg/m³) 1 mg/m³ respirable dust

#### Calcium Aluminate Cement (65997-16-2)

No additional information available

#### silicon carbide (409-21-2)

#### **USA - ACGIH - Occupational Exposure Limits**

ACGIH TWA (mg/m³) 3 mg/m³ (Silicon carbide, nonfibrous; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction. The value is for particulate matter containing no asbestos and < 1% crystalline silica.

#### cristobalite (14464-46-1)

OSHA PEL (TWA) (mg/m³)

## USA - ACGIH - Occupational Exposure Limits

ACGIH TWA (mg/m³) 0.025 mg/m³ respirable dust

USA - OSHA - Occupational Exposure Limits

0.05 mg/m3 respirable dust

#### .2. Appropriate engineering controls

Appropriate engineering controls : Provide adequate ventilation to minimize dust concentrations.

03/18/2022 EN (English US) 2/6

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Solid

Appearance : Granular mixture.

Color : Gray
Odor : odorless

Odor threshold : No data available pH : No data available

Melting point : > 2500 °F

Freezing point : No data available
Boiling point : No data available
Flash point : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Flammability (solid, gas) : Non flammable.
Vapor pressure : No data available
Relative vapor density at 20 °C : No data available

Relative density : ≈ 2.5

Solubility : Slightly soluble in water.

Partition coefficient n-octanol/water (Log Pow) No data available : No data available Auto-ignition temperature Decomposition temperature : No data available Viscosity, kinematic No data available Viscosity, dynamic No data available : No data available **Explosion limits** Explosive properties : No data available Oxidizing properties : No data available

**9.2.** Other information No additional information available

#### **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

Hydraulic setting.

## 10.2. Chemical stability

Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No additional information available 10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

#### **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified

aluminium oxide, non-ribrous (	1344-20-1)

LD50 oral rat > 15900 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))

03/18/2022 EN (English US) 3/6

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

LC50 Inhalation - Rat	> 2.3 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value,
LOGO IIIIlalation - Ital	Inhalation (aerosol), 14 day(s))
silicon carbide (409-21-2)	
LD50 oral rat	> 2000 mg/kg body weight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal)
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation Respiratory or skin sensitization	Causes eye irritation.     Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer (Inhalation).
silicon carbide (409-21-2)	
IARC group	2A - Probably carcinogenic to humans
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard Viscosity, kinematic	: Not classified : No data available
Symptoms/effects after inhalation	<ul> <li>May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure through inhalation.</li> </ul>
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes eye irritation.
ECTION 12: Ecological information	on
2.1. Toxicity	
aluminium oxide, non-fibrous (1344-28-1	
LC50 fish 1	> 100 mg/l (96 h, Salmo trutta, Literature study)
EC50 Daphnia 1	> 100 mg/l (48 h, Daphnia magna, Literature study)
silicon carbide (409-21-2)	
ErC50 (algae)	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 48 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, GLP)
2.2. Persistence and degradability	
aluminium oxide, non-fibrous (1344-28-1	
Persistence and degradability	Not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
silicon carbide (409-21-2)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
cristobalite (14464-46-1)	
Persistence and degradability	Mineral. Not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
2.3. Bioaccumulative potential	
aluminium oxide, non-fibrous (1344-28-1	
Bioaccumulative potential	No data available.
silicon carbide (409-21-2)	
Bioaccumulative potential	Not bioaccumulative.
cristobalite (14464-46-1)	
Bioaccumulative potential	No data available.
2.4. Mobility in soil	
2.7. Mobility III 30II	
aluminium oxide, non-fibrous (1344-28-1	
·	No data available in the literature

03/18/2022 EN (English US) 4/6

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

silicon carbide (409-21-2)		
Surface tension No data available in the literature		
Ecology - soil	Low potential for adsorption in soil.	
cristobalite (14464-46-1)		
Ecology - soil	Ecology - soil No data available.	

#### 12.5. Other adverse effects

No additional information available

## **SECTION 13: Disposal considerations**

#### 13.1. Disposal methods

Product/Packaging disposal recommendations : Do not discharge into the sewer.

#### **SECTION 14: Transport information**

**Department of Transportation (DOT)** 

In accordance with DOT

Not regulated

**Transportation of Dangerous Goods** 

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

## **SECTION 15: Regulatory information**

## 15.1. US Federal regulations

#### Vibrocast 80SC (Mixture)

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

#### aluminium oxide, non-fibrous (1344-28-1)

Not subject to reporting requirements of the United States SARA Section 313

Note

Note: The section 313 chemical list contains "CAS # 1344-28-1 Aluminum Oxide (Fibrous forms)"; the Aluminum oxide contained in this product is non-fibrous, and thus is not a section 313 material. Only manufacturing, processing, or otherwise use of aluminum oxide in the fibrous form triggers reporting.

## 15.2. International regulations

## CANADA

#### aluminium oxide, non-fibrous (1344-28-1)

Listed on the Canadian DSL (Domestic Substances List)

#### Calcium Aluminate Cement (65997-16-2)

Listed on the Canadian DSL (Domestic Substances List)

#### silicon carbide (409-21-2)

Listed on the Canadian DSL (Domestic Substances List)

#### cristobalite (14464-46-1)

Listed on the Canadian DSL (Domestic Substances List)

## **EU-Regulations**

No additional information available

## **National regulations**

#### silicon carbide (409-21-2)

Listed on IARC (International Agency for Research on Cancer)

#### 15.3. US State regulations

cristobalite (14464-46-1)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

Component	State or local regulations
aluminium oxide, non-fibrous (1344-28-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
silicon carbide (409-21-2)	U.S New Jersey - Right to Know Hazardous Substance List
Cristobalite (14464-46-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List

03/18/2022 EN (English US) 5/6

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date 03/22/2022

: Report language name. English. In the event of any conflict between English and other language versions, the English version shall prevail. Other information

#### Full text of H-phrases:

H315	Causes skin irritation
H320	Causes eye irritation
H350	May cause cancer

SDS US (GHS HazCom 2012)
This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.

03/18/2022 EN (English US) 6/6